



## Dynamics of a non-Newtonian Droplet Impact on a Micro-Textured Surface

Joo Hyun Moon, Dong Hwan Shin, and Seong Hyuk Lee  
 Chung-Ang University, Seoul, Korea  
 Chang Kyoung Choi  
 Michigan Technological University, Houghton, MI USA

This study investigated the impact dynamics of single Newtonian and non-Newtonian droplets impinging on a textured aluminum (Al 6061) surface fabricated by using a  $\mu$ -computer numerical control ( $\mu$ -CNC) machine. DI-water was chosen as a Newtonian fluid, while 0.5 wt.% Xanthan Gum (Sigma-Aldrich) solution was selected for a non-Newtonian fluid. The non-Newtonian droplets show a shear-thinning characteristics, higher zero shear viscosity than DI-water. The textured surfaces are composed of micro-holes (diameter: 250  $\mu$ m, depth: 500  $\mu$ m) with equivalent pitches, without showing very similar apparent equilibrium contact angles of both Newtonian and non-Newtonian droplets. We measured spreading and receding diameters from images captured by a high-speed camera of 10,000 fps (HG-LE, Redlake). 6.4  $\mu$ l droplets impinged on the textured surfaces ( $\phi_s=0.28$ ) with an impact velocity of 1.213 m/s. The normalized maximum spreading diameter ( $D^*$ ) of a non-Newtonian impinging droplet is the smaller, and the corresponding lamella thickness is the larger because of the increase in viscosity dissipation. For a non-Newtonian fluid, the receding is also slower than that of Newtonian fluid at the relaxation phase because of the viscosity effect.

*Acknowledgement:* This research was sponsored, in part, by a Michigan Technological University Research Initiation Grant (CKC) and this work also supported by the National Research Foundation of Korea (NRF) grant funded by the Korea government (MEST) (2011-0016837) (SHL).