

CORRECTION | AUGUST 23 2011

Publisher's Note: "Design and characterization of optical heads for interferometric ballistic velocity measurements" [Rev. Sci. Instrum. 82, 043302 (2011)] **FREE**

Garry Berkovic; Yossef Horovitz; Ella Moshe; Yair Sadi; Ehud Shafir



Rev. Sci. Instrum. 82, 089901 (2011)

<https://doi.org/10.1063/1.3628674>



**Optimize
Your
Research**

**Our Vacuum Gauges Provide
More Process Control
and Operational Reliability**



Publisher's Note: "Design and characterization of optical heads for interferometric ballistic velocity measurements" [Rev. Sci. Instrum. **82, 043302 (2011)]**

Garry Berkovic,^{a)} Yossef Horovitz, Ella Moshe, Yair Sadi, and Ehud Shafir
Applied Physics Division, Soreq NRC, Yavne 81800, Israel

(Received 27 April 2011; published online 23 August 2011)
[doi:[10.1063/1.3628674](https://doi.org/10.1063/1.3628674)]

This article was originally published online on 26 April 2011 with an incorrect version of Fig. 5. AIP apologizes for this error.

The figure was correct as it appeared in the printed version of the article. All online versions of the article were corrected on 29 April 2011.

^{a)}Electronic mail: garry@soreq.gov.il.