

A typical result of these experiments is as follows: With 1750 F gas a mean blade temperature of about 800 F can be attained with a water rate equal to 2.5 per cent of the gas flow. Data were taken for gas temperatures between 1150 and 2350 F. For the most useful range of spray rates at each gas temperature, the results of these tests can be summarized by the equations

$$T_G - T_{BU} = 0.15 (T_G - 150) \text{ and } \left( \frac{T_{BU} - T_B}{r} \right) T_G = 438,000$$

Here  $T_{BU}$  is the uncooled blade temperature in deg F,  $T_B$  is the cooled blade temperature,  $T_G$  is the gas temperature, and  $r$  is the water-spray rate, as per cent of gas flow. Calculations indicated that in a turbine of several thousand horsepower, with larger blade chords and higher pressures, the percentage of water required should be only about one third of that given in the foregoing formula.

The optimum configuration consisted of two spray tubes (180 deg apart), each set into the middle of a turbine-nozzle passage. Each tube was equipped with one spray hole near the roots of the rotating blades, and so directed as to spray perpendicular to the gas stream. Varying the spray direction and the number of tubes had only a moderate effect on the cooling, but setting the tubes into the tails of nozzle guide vanes made the cooling much worse.

Theoretical studies of the effect of spray cooling on cycle efficiency led to the conclusion that, for the spray rates required in the tests, approximately one third of the increase in efficiency made possible by higher temperatures is lost as a result of cooling. If cooling of a practical turbine could be accomplished with only one third as much water, these losses would be reduced proportionately. The large increases in output made possible by higher gas temperatures are virtually unaffected by spray cooling.

#### BIBLIOGRAPHY

- 1 "The Cooled Gas Turbine," by A. G. Smith and R. D. Pearson, *Proceedings of The Institution of Mechanical Engineers*, vol. 163, 1950, p. 221.
- 2 "New Drilling Technique Produces Curved Holes," *Product Engineering*, vol. 24, January, 1952, p. 198.
- 3 "Smithsonian Physical Tables," Smithsonian Institution, eighth edition, pp. 651 ff.
- 4 "Transmission of Heat to Boiling Liquids," by T. H. Insinger, Jr., and H. Bliss, *Trans. American Institute of Chemical Engineers*, vol. 36, 1940, pp. 491-513.
- 5 "Heat Transfer," by M. Jakob, John Wiley & Sons, Inc., New York, N. Y., vol. 1, 1949, p. 644.
- 6 "Heat Transfer to Water Boiling Under Pressure," by E. A. Farber and R. L. Scoriah, *Trans. ASME*, vol. 70, 1948, pp. 369-384.
- 7 "Some Recent Developments in Heat Transfer," by W. H. McAdams, Purdue University Engineering Experiment Station, Bulletin 104.
- 8 "Heat Transfer at High Rates to Water With Surface Boiling," by W. H. McAdams, et al., *Industrial and Engineering Chemistry*, vol. 41, 1949, p. 1945.
- 9 "NACA Investigations of Heat-Transfer of Cooled Gas Turbine Blades," by H. Ellerbrock, General Discussion on Heat Transfer, The Institution of Mechanical Engineers, September 11, 1951.
- 10 "Charts of Thermodynamic Properties of Air and Combustion Products From 300 to 3500 R.," by R. E. English and W. W. Wachtl, NACA TN 2071, April, 1950.
- 11 "Steam Turbine Theory and Practice," by W. J. Kearton, Pitman Publishing Corporation, London, England, 1951.
- 12 "The Advantages of High Inlet Temperatures for Gas Turbines and Effectiveness of Various Methods of Cooling the Blades," by O. W. Schey, ASME Preprint No. 48-A-105, 1948.
- 13 "Some Factors in the Use of High Temperatures in Gas Turbines," by T. W. F. Brown, *Proceedings of The Institution of Mechanical Engineers*, vol. 162, 1950, p. 167.
- 14 "Heat Transmission by Natural Convection . . . in Water-Cooled Gas Turbine Blades," by E. H. W. Schmidt, General Discussion on Heat Transfer, The Institution of Mechanical Engineers, September 11, 1951.
- 15 "Sweat Cooling," by N. P. W. Moore and P. Grootenhuis, *The Engineer*, vol. 189, 1950, p. 230.

16 "Contribution to the Theory of Effusion Cooling of Gas-Turbine Blades," by R. Staniforth, General Discussion on Heat Transfer, The Institution of Mechanical Engineers, September 11, 1951.

17 "Effect of Blade Cooling on Stage Efficiency of a Gas Turbine," by W. R. Hawthorne and A. B. Walker, M.I.T. Gas Turbine Laboratory, Report 6574-2, March, 1949.

18 "Effect of Blade Cooling on Efficiency of a Multistage Turbine," by Hawthorne and Walker, M.I.T. Report 6574-3, May, 1949.

19 "Preliminary Survey of Two Simple Plants," by W. R. Hawthorne, M.J.T. Report 6574-4, May, 1949.

20 "Effect of Blade Cooling on Efficiency of a Simple Gas Turbine Cycle," by W. M. Rohsenow and A. B. Walker, M.I.T. Gas Turbine Laboratory, Project D.I.C. 6888, Report 1, July, 1951.

21 "Gas Turbines in Naval Applications," by R. T. Simpson and W. T. Sawyer, *Mechanical Engineering*, vol. 72, 1950, p. 712.

22 "Compression Distillation," by A. Latham, *Mechanical Engineering*, vol. 68, 1946, p. 221.

23 "Turbojet Afterburning Without an Afterburner," by H. E. Schmitt, *Aero Engineering*, vol. 9, December, 1950, p. 18.

## Discussion

J. C. FRECHE.<sup>4</sup> The paper represents a pioneering effort in a field which offers definite possibilities as an effective cooling method for gas-turbine blades. The experimental data obtained are rather extensive including operation over a range of speeds and inlet-gas temperatures and employing various water-injection configurations. The authors are to be congratulated upon a thorough approach and excellent presentation.

The results would be still more valuable if the experiments had been conducted on a larger blade. Rather serious limitations may be imposed on spray cooling if scale effects are a major consideration, a possibility which can only be determined with certainty by actual test. Because of the basic behavior of the spray-cooling process, similar blade temperatures should result for larger blades where wetting of the blade surface occurs. However, for an appreciable difference in blade size, uniform wetting of the blade surface may not be achieved with the same water-injection configuration. Unless satisfactory configurations are then achieved, the resulting large chordwise temperature differences between the wetted and unwetted blade portions would result in the introduction of shear stresses capable of sharply curtailing blade life.

As indicated by the authors, spray cooling also affords a method of achieving thrust increases in turbojet engines by reducing the blade temperature sufficiently so that the material will withstand the higher gas temperatures required. It should be emphasized, however, that water-spray cooling in flight applications is limited to brief intervals since there are definite limitations as to the quantity of coolant which may be provided. Nevertheless, thrust augmentation may be provided with a minimum-weight penalty for such conditions as take-off, passing into the supersonic regime, or for high-speed maneuver. Length of application of spray cooling is, of course, not a limitation in most stationary installations.

F. K. FISCHER.<sup>5</sup> The authors in their paper describe a method of cooling gas turbines in which the blades can be held at a relatively low temperature while operating in an extremely hot gas stream. This is accomplished by direct injection of cooling water into the gas stream ahead of the blades. On first thought the writer believes we would all tend to reject this method as being impractical what with problems of moisture, erosion, corrosion, fouling, and the like. However, when considering a possible design of gas turbine using parts of ordinary

<sup>4</sup> Aeronautical Research Scientist, Lewis Flight Propulsion Laboratory, NACA, Cleveland, Ohio.

<sup>5</sup> Manager, Development Engineering, Westinghouse Electric Corporation, Steam Division, Lester, Philadelphia, Pa. Mem. ASME.

steel while operating at gas temperatures of the order of 2500 F, spray cooling appeared to be the only method offering a possible solution if we were to use structures essentially as we know how to build them today.

The results which the authors describe were carried out on a supercharger modified and instrumented to permit water spray cooling to check the possibilities of this type of cooling on rotating apparatus. The results were gratifying.

In selecting a method of cooling where the blades are to be held appreciably below the gas-stream temperature, a difficult problem is to cool the trailing edge of the blade so that the temperature difference across the blade cross section is not too great. Theoretical studies indicated the difficulty of cooling the trailing edge effectively by internal cooling of the blade even with liquid as the coolant. Cascade studies on stationary blade packs indicated that direct water injection would cool the trailing edge satisfactorily. The supercharger tests indicated that spray cooling is effective on rotating apparatus. However, the supercharger blades are too small to permit accurate determination of temperature distribution across a blade cross section.

The tests which the authors describe indicate that direct injection of water will cool turbine blades effectively. As to the problem of moisture erosion, this should not be too serious based

on steam-turbine experience where exhaust end blades operate in up to 14 per cent moisture at high tip speeds. The problem of fouling could be serious. The tests described were of relatively short duration and indicated some build-up of salts. It should be noted that there is plenty of exhaust heat to evaporate water if necessary, but this means added apparatus.

If appreciably higher temperatures than presently used in gas turbines are to be obtained, some method of effective cooling is necessary. Cooling permits the use of less-costly, less-difficult-to-fabricate materials thus reducing unit costs. This, combined with the other advantages of higher temperatures, such as increased efficiency and increased work per pound of air, resulting in smaller units, is so great that we will continue to see an increasing use of cooling of gas turbines. Water-spray cooling may well play an important part in this development of cooled gas turbines because of its extreme simplicity of application.

#### AUTHORS' CLOSURE

The authors wish to thank Messrs. Freche and Fischer for their comments on this paper. Furthermore, they wish to express their appreciation to Mr. Fischer for his advice and encouragement during the time when the research described in this paper was in progress.