

out on propane and perfluorocyclobutane fluids demonstrated that, for a maximum temperature of  $400 \div 450$  deg C, cycle efficiencies of  $35 \div 40$  percent are achievable. This makes the present cycle competitive with respect to regenerative steam cycles having similar turbine inlet temperature and pressures and with respect to closed-cycle gas turbine having maximum temperature several hundreds of degrees higher. In particular, for capacities ranging up to 10,000 kw, the present cycle could prove particularly advantageous due to the low internal efficiency of small capacity steam turbines [32].

Another field of possible application is the nuclear power industry, in which closed cycle and moderate maximum temperature are limitations imposed by the nuclear section of the plant and cannot be considered as drawbacks of the conventional power conversion station. Solar and nuclear space power systems can also offer interesting possibilities for practical application.

When fluids allowing safe operation at temperatures as high as 500 or 600 deg C become available, the liquid phase compression gas turbine will represent an alternative solution to the generalized use of steam stations for generation of basic power. As a matter of fact, under those conditions it is possible to attain cycle efficiencies of  $42 \div 48$  percent, which are comparable with the performance of the best high pressure, high temperature steam power stations [33, 34].

The use of carbon dioxide as working fluid raises a number of somewhat different problems. Thermal stability and chemical inertness are unquestioned, but only for very high turbine inlet pressures and low condensation temperatures cycle efficiencies are comparable with the best current steam practice.

## References

- 1 J. Ackeret and C. Keller, "Turbine Aérodynamique en Circuit Fermé," *Bulletin Escher Wyss*, tome 15/16, Zürich, 1942-1943, pp. 9-11.
- 2 G. Angelino, "Turbine a Gas con Compressione in Fase Liquida," *Atti della Accademia delle Scienze di Torino*, vol. 99, 1964, pp. 107-126.
- 3 O. A. Hougen, K. M. Watson, and R. A. Ragatz, *Chemical Process Principles—Part II*, John Wiley & Sons, Inc., New York, N. Y., second edition, pp. 588-591.
- 4 K. S. Pitzer and L. Brewer, *Thermodynamics*, McGraw-Hill Book Co., Inc., New York, N. Y. and Kogakusha Co., Tokyo, second edition, pp. 610-615.
- 5 B. J. McBride, S. HeimeI, J. G. Ehlers, and S. Gordon, "Thermodynamic Properties to 6000° K for 210 Substances Involving the First 18 Elements," NASA SP-3001, Washington, D. C., 1963.
- 6 R. L. Wilkins, *Theoretical Evaluation of Chemical Propellants*, Prentice-Hall, Englewood Cliffs, N. J., 1963, pp. 239-446.
- 7 D. R. Stull and G. C. Sinke, "Thermodynamic Properties of the Elements," American Chemical Society, Washington D. C., 1956.
- 8 K. S. Pitzer and L. Brewer, *Thermodynamics*, McGraw-Hill Book Co., Inc., New York, N. Y. and Kogakusha Co., Tokyo, second edition, pp. 191-192.
- 9 C. D. Hodgman, editor, *Handbook of Chemistry and Physics*, Chemical Rubber Publishing Co., Cleveland, Ohio, thirty-ninth edition, pp. 2282-2283.
- 10 F. Din, *Thermodynamic Functions of Gases*, vol. 1, Butterworths, London, 1962, pp. 123-134.
- 11 J. Hilsenrath, C. W. Beckett, W. S. Benedict, L. Fano, H. J. Hoge, J. F. Masi, R. L. Nuttall, Y. S. Touloukian, and H. W. Woolley, "Tables of Thermal Properties of Gases," National Bureau of Standards, Circular 564, Washington, D. C., 1955, pp. 198-200.
- 12 R. Plank, *Handbuch der Kältetechnik*, vol. IV, Springer-Verlag, Berlin/Göttingen/Heidelberg, 1956, p. 472.
- 13 D. R. Chapman, "Some Possibilities of Using Gas Mixtures Other Than Air in Aerodynamic Research," NACA Technical Note 3226, Washington, D. C., August, 1954, p. 42.
- 14 F. Din, *Thermodynamic Functions of Gases*, vol. 2, Butterworths, London, 1962, pp. 130-144.
- 15 A. M. Selvey and P. H. Knowlton, "Theoretical Regenerative-Steam-Cycle Heat Rates," *TRANS. ASME*, vol. 66, no. 6, August, 1944, pp. 489-499.
- 16 M. J. Zucrow, *Aircraft and Missile Propulsion*, vol. II, John Wiley & Sons, Inc., New York, N. Y., 1958, p. 25.
- 17 W. H. McAdams, *Heat Transmission*, McGraw-Hill Book Co., Inc., New York, N. Y., and Kogakusha Co., Tokyo, third edition, p. 219.
- 18 *Ibid.*, pp. 155-158.
- 19 V. Grignard, *Traité de Chimie Organique*, Masson et C. ie, Paris, 1935, tome III, p. 43.

20 "Tables of Chemical Kinetics—Homogeneous Reactions," National Bureau of Standards, Circular 510, Washington, D. C., 1951, pp. 507-511.

21 C. D. Shields, *Boilers*, F. W. Dodge Corporation, New York, N. Y., 1961, pp. 76-77.

22 J. H. Simons, *Fluorine Chemistry*, vol. I, Academic Press, New York, N. Y., 1950, pp. 432-433.

23 G. C. Rogers and G. H. Cady, "Pyrolysis of Perfluoro-n-pentane," *The Journal of the American Chemical Society*, vol. 73, July, 1951, pp. 3523-3524.

24 A. V. Grosse and G. H. Cady, "Properties of Fluorocarbons," *Industrial and Engineering Chemistry*, vol. 39, no. 3, March, 1947, pp. 367-374.

25 L. W. White, Jr., and O. K. Rice, "The Thermal Reaction of Hexafluoroethane With Quartz," *The Journal of the American Chemical Society*, vol. 69, February, 1947, pp. 267-270.

26 J. H. Simons, *Fluorine Chemistry*, vol. V, Academic Press, New York, N. Y., 1964, pp. 335 and 351.

27 J. A. Brown, "Physical Properties of Perfluoropropane," *Journal of Chemical and Engineering Data*, vol. 8, no. 1, January, 1963, pp. 106-108.

28 R. K. SteunenberG and G. H. Cady, "Pyrolysis of Fluorocarbons," *The Journal of the American Chemical Society*, vol. 74, July-September, 1952, pp. 4165-4168.

29 W. J. Pummer and L. A. Wall, "Preparation and Properties of Aromatic Fluorocarbons," *Journal of Chemical and Engineering Data*, vol. 6, no. 1, January, 1961, pp. 76-78.

30 I. B. Johns, E. A. McElhill, and J. O. Smith, "Thermal Stability of Some Organic Compounds," *Journal of Chemical and Engineering Data*, vol. 7, no. 2, April, 1962, pp. 277-281.

31 J. H. Simons, *Fluorine Chemistry*, vol. I, Academic Press, New York, N. Y., 1950, pp. 465-466.

32 G. A. Gaffert, *Steam Power Stations*, McGraw-Hill Book Co., Inc., New York, N. Y., and Kogakusha Co., Tokyo, fourth edition, p. 62.

33 J. Bartels, "Thermodynamics of Supercritical-Pressure Steam-Power Plants," *TRANS. ASME*, vol. 77, no. 5, July, 1955, pp. 705-714.

34 P. Profos, "Pression Hypercritique et Rendement dans les Centrales Motrices à Vapeur," *Revue Technique Sulzer*, 1958, no. 4, pp. 11-18.

## DISCUSSION

### R. T. Szwalski<sup>2</sup>

The problem under consideration is very exciting. If the perspectives of the proposed cycle are what we have in mind, the problem of sealing seems to be of basic importance. I would thankfully appreciate any information on this particular subject.

### Author's Closure

The question raised by Professor Szwalski points out one of the vital details of the cycle illustrated in my paper and I thank him for his interest. Before stating my opinion on the subject I should like to mention that there are many industries that have to cope with similar problems made more difficult by the particular nature of the fluids handled. This is the case in the nuclear industry, which employs fluids that are extremely expensive, like heavy water, or extremely fugacious, like helium.

Likewise, the chemical industry often treats chemically active, inflammable or toxic liquids and gases. More recently, the space industry and, in particular, the space power technology solved sealing problems for a particularly severe environment. Finally, the cold industry handles special fluids by means of machinery very like that required in power plants. The success in these branches of the technology makes it reasonable to hope that sealing problems can be solved also in the power generation field, in which the task is comparatively easier due to the chemical inertness and high molecular weight of the majority of the working fluids.

With respect to sealing of rotating machinery, two approaches seem the most promising. One envisages the use of canned

<sup>2</sup> Professor, Technical University, Gdansk, Poland. Mem. ASME.

machinery employing the working fluid as lubricant. This system, being of the zero leakage type, prevents any working fluid contamination by lubricating oil. Of special interest is the gas lubricated bearing, currently under development [35-37].<sup>3</sup> A variety of other systems employ a grazing contact. A comprehensive review of seals for special fluids can be found in reference [38]. An example of a very effective system employing a floating carbon ring is presented in reference [39]; working fluid contamination by the lubricating oil is prevented.

<sup>3</sup> Numbers in brackets designate Additional References at end of Closure.

#### Additional References

- 35 J. H. Laub and H. D. McGinness, "A Closed-Cycle System for Gas Bearings" *Astronautics*, vol. 6, no. 3, March, 1961, p. 70.
- 36 E. E. Bisson and W. J. Anderson, "Advanced Bearing Technology," National Aeronautics and Space Administration, Washington, D. C., 1964, chapter 5, p. 109.
- 37 J. Smith, D. C. Strimbeck, N. H. Coates, and J. P. McGee, "Bureau of Mines Progress in Developing Open and Closed-Cycle Coal-Burning Gas Turbine Power Plants," *JOURNAL OF ENGINEERING FOR POWER*, TRANS. ASME, Series A, vol. 88, 1966, pp. 313-322.
- 38 H. E. Tracy, "Select Best Pumps Seal," *Chemical Engineering*, April, 1957, pp. 239-254.
- 39 Anon., "Elliott Multistage Centrifugal Compressors," Carrier Corporation, New York, N. Y., Bulletin P-11, 1962, p. 10.