



Fig. 5 Wall pressure distribution downstream of backstep with $M_\infty = 2$

of the dividing streamline reattachment point. Although the latter information was not obtained experimentally the predicted pressure distribution is in general agreement with measurements.

The present computations also predicted the characteristic corner flow behavior which occurs because the approach boundary layer overexpands and clings to the vertical backstep surface before breaking away to form a free shear layer [12]. For the $M_\infty = 2$ case of Figs. 3, 4 with a step height of $10\Delta y$ the breakaway point is approximately $2.5\Delta y$ below the corner (point C of Fig. 1).

Concluding Remarks

The complete time-dependent Navier-Stokes equations have been solved numerically using the explicit method of Rusanov. This study represents one of the few successful applications of this differencing technique to flows involving both natural viscosity and associated non-slip boundary conditions. Through numerical experimentation, an extended range for the explicit stability parameter was established. An additional convergence parameter, which relates the incremental spatial steps, was also defined.

Computation times for the two geometries investigated were quite different. For the flat plate, which utilized 2500 nodal points, practical steady state was achieved in approximately 50 minutes of UNIVAC 1108 computer time which is considered quite satisfactory for a numerical solution of this nature. Flow fields for the backstep and near wake geometry required approximately 200 minutes to reach a steady state solution; this is due primarily to the low velocities in the recirculating region of the field. The generally favorable agreement of the predicted flow parameters with experimental results suggests that the current numerical technique can be confidently applied to a wide spectrum of laminar flows which include imbedded shock waves and/or separated flow regions.

References

- 1 Moretti, G., and Bleich, G., "Three-Dimensional Flow Around Blunt Bodies," *AIAA Journal*, Vol. 5, No. 9, 1967, pp. 1557-1562.
- 2 Von Neumann, J., and Richtmyer, R. D., "A Method for the Numerical Calculation of Hydrodynamic Shocks," *Journal of Applied Physics*, Vol. 21, 1950, pp. 232-237.
- 3 Emery, A. F., "An Evaluation of Several Differencing Methods for Inviscid Fluid Flow Problems," *Journal of Computational Physics*, Vol. 2, 1968, pp. 306-331.
- 4 Lundford, G. S. S., Polacheck, R. J., and Seeger, R., "On Unsteady Flow of Compressible Viscous Fluids," *Journal of Applied Physics*, Vol. 24, 1953, pp. 490-495.
- 5 Skoglund, V. J., Cole, J. K., and Staiano, E. F., "Development and Verification of Two-Dimensional Numerical Techniques for Viscous Compressible Flows with Shock Waves," *Proceedings of the 1968 Heat Transfer and Fluid Mechanics Institute*, Stanford University Press, 1968.
- 6 Skoglund, V. J., and Gay, B. D., "Improved Numerical Techniques and Solution of a Separated Interaction of an Oblique Shock Wave and a Laminar Boundary Layer," Report ME-41 (69) S-068, Bureau of Engineering Research, University of New Mexico, June 1969.

7 Lax, P., "Weak Solutions of Nonlinear Hyperbolic Equations and Numerical Computation," *Communications on Pure and Applied Mathematics*, Vol. 7, 1954, pp. 159-193.

8 Roberts, K. J., and Weiss, N. O., "Convective Difference Schemes," *Mathematics of Computation*, Vol. 20, No. 94, 1966, pp. 272-299.

9 Rusanov, V. V., "The Calculation of the Interaction of Non-stationary Shock Waves and Obstacles," National Research Council of Canada Library, Ottawa, Canada, Technical Translation 1027 by D. A. Sinclair, 1962. Translated from *Zhurnal Vychislitel'noi Fiziki, Akademiya Nauk, USSR*, Vol. 1, No. 2, 1961, p. 267.

10 Goodrich, W. D., "A Numerical Solution for Problems in Laminar Gas Dynamics," PhD dissertation, Department of Mechanical Engineering, University of Texas at Austin, 1969.

11 Courant, R., Isaacson, E., and Rees, M., "On the Solution of Nonlinear Hyperbolic Differential Equations by Finite Differences," *Communications on Pure and Applied Mathematics*, Vol. 5, 1952, pp. 243-255.

12 Roache, P. J., and Mueller, T. J., "Numerical Solutions of Laminar Separated Flows," *AIAA Journal*, Vol. 8, No. 3, 1970, pp. 530-538.

13 Lax, P. D., and Richtmyer, R. D., "Survey of the Stability of Linear Finite Difference Equations," *Communications of Pure and Applied Mathematics*, Vol. 9, 1956, pp. 267-293.

14 Richtmyer, R. D., and Morton, K. W., *Difference Methods for Initial-Value Problems*, Interscience, New York, 1967, pp. 70-90.

15 Courant, K., Friedrichs, K. O., and Lewy, H., "Über die Partiiellen Differenzgleichungen der Mathematischen Physik," *Mathematische Annalen*, Vol. 100, 1928, pp. 32-74.

16 De Jarnette, F. R., "Application of Lax's Finite-Difference Method to Nonequilibrium Hypersonic Flow Problems," Technical Report R-234, NASA, Mar. 1966.

17 Kurzrock, J. W., and Mates, R. E., "Exact Numerical Solutions of the Time-Dependent Compressible Navier-Stokes Equations," *AIAA Paper 66-30*, New York, 1966.

18 Seala, S. M., and Gordon, P., "Solution of the Navier-Stokes Equations for the Flow Around a Circular Cylinder," *AIAA Journal*, Vol. 6, No. 5, 1968, pp. 815-822.

19 Burstein, S. Z., "Numerical Methods in Multidimensional Shocked Flows," *AIAA Journal*, Vol. 2, No. 12, 1964, pp. 2111-2117.

20 Bertram, M. H., "Boundary Layer Displacement Effects in Air at Mach Numbers of 6.8 and 9.6," Technical Note No. 4133, NACA, 1957.

21 Hayes, W. D., and Probstein, R. F., *Hypersonic Flow Theory*, Academic Press, New York, N. Y., 1959, pp. 333-374.

22 Vas, I. E., and Bogdonoff, S. M., "Hypersonic Studies of Blunt Unswept Wings," Technical Note 59-127, Wright Air Development Center, Dayton, Ohio, Apr. 1959.

23 Chapman, D. R., Kuehn, D. M., and Larson, H. K., "Investigations of Separated Flows in Supersonic and Subsonic Streams With Emphasis on the Effects of Transition," Report 1356, NACA, 1958.

DISCUSSION

S. Gopalakrishnan⁴

The authors have attempted to solve a very complex problem, and the result in terms of the shock wave resolution is excellent. It is interesting to see that even with the use of artificial viscosity, a very thin shock layer can be obtained as part of the result. However, when the real boundary layer is also computed, the question arises as to the effect of the artificial viscosity on the real fluid behavior near the walls. Since the paper does not contain any specific statement with regard to this effect, I am suggesting the following analysis of the properties of the artificial viscosity device used in the paper.

A classic method for computing the accuracy of finite difference schemes applied to nonlinear partial differential equations is to linearize the governing equations. Two dimensional problems are even then intractable, and hence in the following analysis, the flow is assumed to be one dimensional. The results of such an analysis can be believed to be qualitatively correct.

The governing equation (2) is simplified to:

$$\frac{\partial f}{\partial t} + \frac{\partial F}{\partial x} = \frac{\partial}{\partial x} \left[A(x, t) \frac{\partial f}{\partial x} \right] \equiv D(x, t) \quad (7)$$

⁴Development Engineer, Avco Lycoming Division, Stratford, Conn.

where

$$f = \begin{bmatrix} \rho \\ \rho u \\ e \end{bmatrix}$$

and

$$F = \begin{bmatrix} \rho u \\ \rho u^2 + p + \tau_{xx} \\ (e + p)u + q_x + \tau_{xx}u \end{bmatrix}$$

The finite difference equation (3) applied to (7) gives

$$f_j^{n+1} = f_j^n - \frac{\Delta t}{2\Delta x} [F_{j+1}^n - F_{j-1}^n] + \Delta t \bar{D} \quad (8)$$

\bar{D} represents the finite difference representation for D .

Define J to be the Jacobian matrix of F with respect to f .

$$\frac{\partial F}{\partial x} = J \frac{\partial f}{\partial x}$$

When we assume J to be a constant, the left-hand side of (7) is linearized. The finite difference equation is then:

$$f_j^{n+1} = f_j^n - J \frac{\Delta t}{2\Delta x} [f_{j+1}^n - f_{j-1}^n] + \Delta t \bar{D} \quad (9)$$

Quantities f_{j+1}^n , f_{j-1}^n , and f_j^{n+1} can be expanded in a Taylor series about the value of f_j^n and truncated consistently. To evaluate terms involving time derivative, we can use the governing equation repeatedly.

$$\text{i.e.} \quad \frac{\partial f}{\partial t} = D - J \frac{\partial f}{\partial x}$$

$$\frac{\partial^2 f}{\partial t^2} = \frac{\partial D}{\partial t} - J \frac{\partial D}{\partial x} + J^2 \frac{\partial^2 f}{\partial x^2}$$

etc.

Substituting these expressions into (9), we can get:

$$\frac{\partial f}{\partial t} + J \frac{\partial f}{\partial x} = \bar{D} - \frac{\Delta t}{2} \left[\frac{\partial D}{\partial t} - J \frac{\partial D}{\partial x} + J^2 \frac{\partial^2 f}{\partial x^2} \right]$$

Since D is of order Δ [equation (4)], we may simplify the right-hand side (RHS) to:

$$\text{RHS} = \bar{D} - \frac{\Delta t}{2} J^2 \frac{\partial^2 f}{\partial x^2}$$

If we neglect the errors occurring in the term \bar{D} due to finite difference representation (as this will be of order higher than Δ),

$$\bar{D} \simeq \frac{\partial}{\partial x} A \frac{\partial f}{\partial x} = \frac{\partial}{\partial x} \left[\frac{\Delta x^2}{2\Delta t} C_1 \sigma \frac{\partial f}{\partial x} \right]$$

For C_1 independent of x ,

$$\bar{D} = \frac{\Delta x^2}{2\Delta t} C_1 \sigma \frac{\partial^2 f}{\partial x^2}$$

Hence the finite difference system corresponds to an equivalent differential equation, which is:

$$\frac{\partial f}{\partial t} + J \frac{\partial f}{\partial x} = \frac{\partial^2 f}{\partial x^2} \left[C_1 \sigma \frac{\Delta x^2}{2\Delta t} - J^2 \frac{\Delta t}{2} \right] \quad (10)$$

The right-hand side can be shown to be dissipative, and therefore we can define the artificial viscosity to be:

$$\nu_{\text{art}} = C_1 \sigma \frac{\Delta x^2}{2\Delta t} - J^2 \frac{\Delta t}{2}$$

It is convenient to write a corresponding Reynolds number

$$\text{Re}_{\text{art}} = uL/\nu_{\text{art}}$$

where L is a characteristic length dimension.

$$\frac{\Delta t}{\Delta x} = \frac{1}{a(1+M)}$$

by the Courant Friedrichs Lewy criterion with a = local sound speed.

Finally we get:

$$\text{Re}_{\text{art}} = \frac{L}{\Delta x} \frac{2M}{1+M} \frac{1}{C_1 \sigma - \left(J \frac{\Delta t}{\Delta x} \right)^2}$$

$L/\Delta x$ represents spatial resolution of the finite difference mesh and would be approximately 100. The quantities $C_1 \sigma$ and $J \frac{\Delta t}{\Delta x}$ are of order 1. If we assume that their difference is also order (1), the Reynolds number is about 100.

In the two-dimensional computation with nonlinearities, the artificial Reynolds number may be somewhat higher. However, it will be far smaller than the true Reynolds number for high-speed flows which would be about 10^6 .

In conclusion, it appears that the artificial viscosity used for adequate thickening of the shock wave is very large compared to real viscosity. Therefore the real boundary layer effects would be completely masked by the artificial viscosity. The same conclusion has also been stated by Moretti.⁵

I would appreciate if the authors can indicate whether the computed boundary layer parameters compare reasonably with experimental values.

Since the dissipative term is proportional to the second derivative of the dependent variable [equation (10)], it appears that the computed shock thickness will be inversely proportional to the shock strength.⁶ I would like to know if the authors have found this to happen in their computations.

Authors' Closure

The previous one-dimensional, linear analysis, which attempts to assess the effects of numerical damping, or "artificial viscosity," on the real fluid behavior near the walls, does indeed provide some qualitative information concerning this numerical effect. However, I feel that it is necessary to supplement this analysis with some representative data from the present investigation. These data should also answer the question concerning comparisons of computed boundary layer parameters with experimental values of these parameters.

Computations from this numerical investigation were compared to compressible, isothermal ($M_\infty = 2.0$, $T_w = T$) flat plate boundary layer thickness computations reported in the open literature (viz. Schlichting's *Boundary Layer Theory*). The results of several comparisons indicated that the numerically calculated boundary layer thicknesses obtained in this investigation approached the values in the literature as the computational grid size across the boundary layer approached the magnitude of the local fluid mean free path. For example, the ratios of the numerically calculated boundary layer thicknesses to the thickness obtained in the literature at the same Mach number and Reynolds number ($M_\infty = 2.0$, $\text{Re}_\infty/\text{ft} = 10^4$) were 1.89 and 1.22 when the normal grid spacings were, respectively, 5 and 2.5 times the local mean free path. This indicates that the present error in the calculation of the boundary layer thickness varies as the square of the grid size.

Numerical data pertinent to the question concerning shock wave thickness are not available in a form suitable for assessing the influence of shock strength on shock thickness. However, I would speculate that the shock wave thickness will be inversely proportional to the shock strength.

⁵ Moretti, G., and Salas, M. D., "Numerical Analysis of the Viscous Blunt Body Problem, Part 1," Polytechnic Institute of Brooklyn, Report No. 70-48, Nov. 1970, p. 45.

⁶ Gopalakrishnan, S., and Bozzola, R., "Computation of Shocked Flows in Compressor Cascades," ASME Paper 72-GT-31.