

Index

a

abnormal wear 95–96
 chipping 95–96
 cracking 95–96
 fracture 95–96
 spalling 95–96
 abrasive wear 97
 actuators 18–19
 magnetostrictive actuators 18
 piezoceramic rings 21
 piezoelectric actuators 18
 adhesion wear 97
 analytical rigid body 148
 ANSYS 63
 Arbitrary Lagrangian Eulerian (ALE)
 formulation 148
 atomic force microscope (AFM) 171

b

block type chips 141
 boundary conditions 54
 brittle damage 95
 burr 8
 burr reduction 8, 108–115

c

Cartesian coordinate system 60
 Castigliano's second theorem 56
 ceramic stack 46
 chip generation 108
 chip geometric feature 120
 chip thickness 73, 89
 uncut chip thickness 106–107

undeformed chip thickness 7, 112, 145
 clamping mode 20, 35
 coated tool 97
 coating delamination 97
 cold welding 97
 compliance transformation matrix 60–63
 composite horns 53
 compound motion 34–35
 compression shear deformation 112
 constructive solid geometry 169
 contact angles 188
 continuous type chips 141
 controllable wettability surface 171
 coupling effect 31–33, 36–37, 45
 crater 96
 critical cutting depth 7
 critical up-feed velocity 76
 critical velocity 48, 100
 cross-coupling 32
 C type chips 141
 cut-off burr 109
 cutting-directional vibration-assisted (CDVA)
 74
 cutting-edge angle 89
 cutting-edge radius 89
 cutting energy 49, 69, 98
 cutting force 8, 119–144
 cutting force coefficient 127
 cutting paths 132
 cutting power 49
 cutting temperature 105
 cutting zone 89

d

- data acquisition (DAQ) 66–67
- data collection 66–67
- decoupling 28, 45
- DEFORM
 - 2D software 152
- deformation zone 104
- depth ratio 120
- diffusion wear 97
- drive and control 19
 - open loop control system 19
 - proportion integration differentiation (PID) 19, 66

e

- effective cutting time 48
- electrode plate 49
- electromechanical coupling coefficient
- elliptic vibration-assisted (EVA) cutting 74
- energy-dispersive X-ray spectroscopy (EDS) 101, 105
- excitation sources 47

f

- ferrous materials 98
- Fick's first law 105
- finite element analysis (FEA) 17, 22, 63–65
- fish scale surface 188
- fish squamous structure 188
- friction force 100
- front cover 49–53

g

- Gibbs free energy 104
- Gibbs–Helmholtz equations 105

h

- hard and brittle materials 1, 7, 36, 98, 102, 113
 - AISI 1045 steel 90
 - Steel and SiCp/Al composites 99
 - titanium alloys 102
- homogeneous transformation matrix 174
- horizontal speed ratio (HSR) 76

i

- ImageJ 172
- independent drive 34–35
- instantaneous uncut thickness 135
- Inverse kinematic modeling (IKM) 56

j

- Johnson–Cook damage model 89
- Johnson–Cook (JC) material model 89

l

- LabVIEW platform 66–67
- Langevin transducer 50
- linear Hooke's law 56

m

- matrix-based compliance modeling (MCM) 56
- maximum vibration velocity 85
- mechanical amplification 18, 46
- mechanical stiffness 29–30, 49
- mechanical wear 96–98
- micro-electro-mechanical systems 167
- micro-Euler–Bernoulli beam 56
- minimum chip thickness 106
- motion strokes 33

n

- natural frequency 17, 19, 22, 26, 28
- negative shear angle 110
- negative shear band 110
- nodal plane 46, 52
- node point 20, 27, 53
- nominal cutting velocity 85
- nonresonant system 27–36
- normal-directional vibration-assisted (NDVA) 74
- normal wear 95–96
 - boundary wear 96
 - flank wear 96
 - rake wear 96
 - tool tip wear 96

o

- output compliance 61–62
- oxidation wear 98

p

parasitic motions 33
 piezoelectric transducer (PZT) 2
 plastic-elastic deformation 106
 plastic hinge point 110
 ploughing effect 106
 Poisson burr 109
 polycrystalline diamond (PCD) tools 99
 processing parameters 9, 169
 cutting depth 123
 feed rate 74, 83, 106
 pseudo-rigid body (PRB) method 56
 pulse force 47, 49

q

quarter-wave horns 53

r

radial force 136
 rear cover 49–53
 relative rotational angle 178
 residual stress 108
 resonance rod 27
 resonant system 19–28
 right circular flexure hinge 56–58
 rollover burr 109
 rotation matrix 60
 rotation speed 87

s

scanning electron microscope (SEM) 99
 secondary damage 107
 shear angle 125
 shear yield stress 110
 signal generator 66–67
 Sindatek Water Contact Goniometer 187
 size effect 106
 spindle rotation frequency 88
 spindle rotation speed 185
 stress concentration 22, 31, 64
 structural compliance 63–64
 structural stiffness 63–64
 surface quality 9–10, 159
 surface roughness 107, 108, 146
 surface simulation 185

surface texture 10, 146, 167–171, 185–187
 surface topography 188
 sweep signal 66

t

tangential force 136
 tear burr 109
 thermochemical wear 96–98
 thermo-elastic-plastic material 148
 tool-chip contact length 152
 tool geometry 108
 tool holder 20–21, 30–31
 tool life 9, 95–108
 tool materials 35, 96, 145
 tool parameters 9, 98, 170
 tool paths 8, 87
 elliptical tool paths 87
 tool tip motion 75
 tool trajectory 25, 30, 101, 120, 155
 elliptical tool trajectory 101
 tool-workpiece separation (TWS) 73–75, 80
 top burr height 163
 top burrs 112
 transmission efficiency 47
 transmission mechanisms 18–19
 acoustic waveguide booster 19–20
 double parallel four bar linkage 19, 32
 flexible hinges 18, 32, 33, 56–59
 hollow ultrasonic horn 22
 sonotrode 19–20
 ultrasonic horn 18–19, 22
 ultrasonic transducer 19–20

u

ultrasonic generator 46
 ultrasonic transducer 46
 ultrasonic vibration 22–25, 35
 uncut work material 76
 unloaded power 49–50
 up-feed increment 76

v

vibration amplitude 18, 22, 26, 29, 49, 67,
 78, 82
 vibration assisted machining process 3

- vibration assisted machining process (*contd.*)
 - vibration-assisted drilling 3–4
 - vibration-assisted grinding 4–6
 - vibration-assisted machining process 3
 - vibration-assisted milling 3
 - vibration-assisted polishing 6
 - vibration-assisted turning 4
- vibration frequency 29, 36, 47, 49, 53–54, 74
- vibration resolutions 33