

INDEX

Page numbers followed by f and t indicate figures and tables, respectively.

- ABMA. *See* American Boiler Manufacturers Association
- Abnormal Occurrence Reports (AORs), 3-2
- ABWR. *See* Advanced boiling water reactor
- ACC. *See* Advanced accumulator
- Acceleration drag force, 8-10–8-11
- Accelerometers, 3-18
- Acceptable damage, 6-3
- Acceptable vibration limits, determination of, 3-28–3-29
 - acoustic analysis and time history piping analysis for, 3-29
 - response spectra (RS) piping analyses for, 3-29
 - simple beam analogies for, 3-28, 3-29
- Acceptance Standards for flaw in Section XI, revisions to, 27-4–27-6.
 - See also* Section XI (flaw Acceptance Standards development and analytical evaluation procedures)
 - for consistency improvement, 27-5
 - for materials susceptible to stress corrosion cracking, 27-5–27-6
- Access building (AC/B), 15-29
- Accumulation, 28-1
- Accumulator system, advanced, 15-26
- Acoustical resistant element, 3-32
- Acoustical response, of piping, 3-31–3-33
- Acoustic compliance, 3-32
- Acoustic disturbances, 8-13–8-14
- Acoustic effects, 8-12
- Acoustic equations, 8-14
- Acoustic inertance, 3-32
- Acoustic resonance
 - in BWR steam dryer evaluations in EPU, 30-15–30-16
 - single and double vortex, 30-16
- Acoustic sensing devices, for leak detection in pipelines, 11-49
- Active components, 7-17
- Active failure, 6-3
- Actual *versus* design cyclic duty, 19-20–19-21
- Addenda to the Code
 - 2002 Addenda to Section XI, 27-8–27-11
 - 2009 Addenda to Section XI, 27-5
- Adjusted Reference Temperature (ART), 20-1
- 1983 Adoption of the Grade 91 Code Case, 26-1
- ADS. *See* Automatic depressurization system
- Advanced accumulator (ACC), 15-25, 15-26
- Advanced boiling water reactor (ABWR), 16-1, 16-2, 16-5
 - current code and environmental fatigue usage, 16-20
 - feedwater nozzle, 16-16
 - forged steel ring, 16-17
- Advisory Committee for Reactor Safeguards (ACRS), 17-8
- AEC. *See* Atomic Energy Agency
- Aerial patrols, of right of way, 11-49
- AFR. *See* Away From Reactor
- AFT Impulse, 6-3
- AGA. *See* American Gas Association
- “Against the Gods,” 29-1
- Aging concerns in PWR vessel internals
 - irradiation-assisted stress corrosion cracking, 20-17
 - irradiation embrittlement, 20-17
 - stress corrosion cracking (SCC), 20-17
 - stress relaxation, 20-17
 - thermal aging embrittlement, 20-17
 - void swelling, 20-17
- Aging management of PWR vessel internals, 20-15–20-18
 - aging concerns in PWR vessel internals, 20-17–20-18
 - aging management program attributes, 20-16–20-17
 - aging management review, 20-15–20-16
 - overview, 20-15
 - status, 20-18
- Aging management practices, 20-17–20-18
- Aging management program (AMP), 18-4, 18-6, 19-21, 20-15
- Aging management program (AMP) attributes
 - acceptance criteria, 20-16–20-17
 - administrative controls, 20-17
 - confirmation process, 20-17
 - corrective actions, 20-17
 - detection of aging effects, 20-16
 - monitoring and trending, 20-16
 - operating experiences, 20-17
 - parameters monitored/inspected, 20-16
 - preventive actions, 20-16
 - scope of program, 20-16
- Aging management review (AMR), 18-5
- AIA. *See* Authorized Inspection Agency
- AICHE (The American Institute of Chemical Engineers), 28-3
- Algor, for stress analysis, 6-11
- Allowable pressure determination, 20-7
- Allowable stresses
 - in B31.1, 4-18
 - in B31.3, 4-18
- Allowed Outage Times (AOTs), 7-2
- Alloy 600, 20-18
- Alloy 82 and 182 weld metal, 21-3

- Alloy 600 applications
 - alloy 82 and 182 weld metal, 21-3
 - alloy 600 base metals, 21-1–21-3
 - BMI penetrations, 21-3–21-4
 - butt welds, 21-4
 - core support attachments, 21-4
 - miscellaneous, 21-4
 - RPV top-head penetrations, 21-3
- Alloy 82/182 dissimilar metal butt welds, 21-12–21-13
- Alloys, structural, 17-10
- Alloy X-750, 16-18
- Alternate inspection frequency, 19-11–19-12
- Alternate inspection method for nozzle inner radii, 19-9–19-11
- Alternate seismic rules (new), pressure piping system protection, 14-4
- Alternating current (ac), 15-26
- Alternative life cycle management
 - economic evaluation, 21-27
 - identification, 21-26
- Aluminum flanges, 9-6
- American Boiler Manufacturers Association (ABMA), 1-1
- American Engineering Standards Committee, 23-1
- American Gas Association (AGA), 11-27
- The American Institute of Chemical Engineers (AIChE), 28-3
- American National Standards Institute (ANSI), 1-2, 9-1, 23-1
- American Nuclear Society (ANS), 6-1, 22-22
 - ANS-2.8 (Design Basis Flooding), 22-22
 - ANS-2.30 (Assessing Capability for Surface Faulting), 22-22
 - ANS-2.31 (Estimating Extreme Precipitation), 22-22
 - ANS-3.87 (Drills/Exercises for Emergency Preparedness), 22-22
 - ANS-20.1 (Safety/Design Criteria for Fluoride Salt Cooled), 22-22
 - ANS-50.1 (Design Criteria for Light Water Reactors), 22-22
 - ANS-54.1 (Design Criteria for Liquid Metal Reactors), 22-22
 - ANS-57.2 (Design Requirements for LWR Spent Fuel Storage), 22-22
 - ANS-57.3 (Design Requirements for LWR New Fuel Storage), 22-22
 - Risk-Informed Standards Committee (RISC), 22-22
- American Petroleum Institute (API), 11-8, 26-5
- American Petroleum Institute (API) (Pressure Relief Standards), 28-9
 - API 520, Part 1 (Sizing and Selection), 28-9
 - API 520, Part 2 (Installation), 28-10
 - API 521 (Pressure Relieving and Depressurizing Systems), 28-10
 - API 526 (Flanged Steel Pressure Relief Valves), 28-10
 - API 527 (Valve Seat Tightness), 28-10
 - API 2000 (Venting Atmospheric and Low Pressure Storage Tanks), 28-10
 - API Documents (Updates, Interpretations, and Membership), 28-10–28-11
 - API Std 2510 (Design and Construction of LPG Installations), 28-10
- American Society of Civil Engineers (ASCE), 6-1
- American Society of Civil Engineers Standard ASCE/SEI 7, 24-4
- American Society of Mechanical Engineers Board on Nuclear Codes and Standards (BNCS), 25-1, 25-3
- American Society of Mechanical Engineers (ASME), 1-1, 26-5
 - nuclear certification programs, 1-14–1-19
 - Section III, Nuclear Vessels, 1-2, 1-3
- American Society of Mechanical Engineers Board on Nuclear Codes and Standards (BNCS), 22-2
 - Risk Management Strategic Plan, 22-20, 22-22
- American Society of Mechanical Engineers (ASME) Boiler and Pressure Vessel Code (Code)
 - initiatives
 - CRTD-86, “Development of Reliability-Based Load and Resistance Factor Design (LRFD) Methods for Piping,” 22-20–22-21
 - safety classification, 22-20
 - Section XI, 22-21
 - American Society of Mechanical Engineers (ASME) Boiler and Pressure Vessel Code Section III, 30-15
 - fatigue analysis, 30-7–30-8
 - American Society of Mechanical Engineers (ASME) B16 Standard, 23-1–23-9
 - background, 23-1–23-2
 - B16 Committee (overview), 23-1–23-2
 - elements, 23-3
 - generic table of contents, 23-3, 23-3t–23-4t
 - groups, 23-1
 - maintenance, 23-2–23-3
 - organization of, 23-2–23-3
 - Subcommittee B (Threaded Fittings [Except Steel]), Flanges and Flanged Fittings, 23-2, 23-4, 23-5t
 - B16.1, 23-7
 - B16.4, 23-4
 - B16.5, 23-4
 - B16.42, 23-6
 - B16.45, 23-4
 - Subcommittee C (Steel Flanges and Flanged Fittings), 23-2, 23-5–23-6, 23-5t
 - B16.5, 23-5–23-6
 - B16.36, 23-6
 - B16.47, 23-6
 - B16.48, 23-6
 - Subcommittee F (Steel Threaded and Welding Fittings), 23-2, 23-6–23-7, 23-7t
 - B16.7, 23-6
 - B16.9, 23-6, 23-7
 - B16.11, 23-6
 - B16.25, 23-6–23-7
 - B16.49, 23-7
 - B16.53, 23-7
 - Subcommittee G (Gaskets for Flanged Joints), 23-2, 23-7, 23-7t
 - B16.20, 23-7
 - B16.21, 23-7
 - Subcommittee J (Copper and Copper Alloy Flanges, Flanged Fittings and Solder Joint Fittings), 23-2, 23-7, 23-8t
 - Subcommittee L (Gas Shutoffs and Valves), 23-2, 23-8, 23-8t
 - Subcommittee N (Steel Valves and Face to Face and End to End Dimensions of Valves), 23-2, 23-8–23-9, 23-9t
 - B16.5, 23-9
 - B16.10, 23-8
 - B16.34, 23-9
 - B16.36, 23-9
 - B16.47, 23-9
 - American Society of Mechanical Engineers (ASME) Codes
 - graphite joining components, 26-9
 - thermoplastic components joining
 - ASME BPV Code, Section IX (Article XXIV, Plastic Fusing Data), 26-8
 - ASME BPV Code, Section IX, Article XXI (Plastic Fusing General Requirements), 26-8
 - ASME BPV Code, Section IX, Article XXII (Fusing Procedure Qualification), 26-8

- ASME BPV Code, Section IX, Article XXIII (Plastic Fusing Performance Qualifications), 26-8
- thermoset plastic components joining
- ASME B31.1 Code, Power Piping, Nonmandatory Appendix III, 26-9
 - ASME B31.3 Code, Process Piping, Chapter VII, 26-9
 - ASME B31.9 Code, Building Services Piping, Part 3, 26-9
 - ASME BPV Code, Section III, Code Cases N155-2, 26-9
 - ASME BPV Code, Section X, Fiber-Reinforced Plastic Pressure Vessels, Article RF-7, 26-9
 - ASME RTP-1 Standard, 26-9
- American Society of Mechanical Engineers (ASME) Codes (pressure relief devices)
- Appendix 11 (Mandatory) (Capacity Conversion for Safety Valves), 28-7
 - Appendix M (Non-Mandatory) (Installation and Operation), 28-7
 - ASME B31.1 (Power Piping), 28-8–28-9
 - ASME B31.3 (Process Piping), 28-9
 - ASME IV (Heating Boilers), 28-6
 - ASME Section I (Power Boilers), 28-5–28-6
 - ASME Section VIII (Division 1 – Pressure Vessels), 28-6–28-7
 - Non-Self-Limiting (UG-140[b]), 28-7
 - Self-Limiting (UG-140[a]), 28-6
 - U-1(c)(2)(h)(1) (Vessels Not Exceeding the Design Pressure of 15 psig), 28-6
 - UG-140 (Overpressure Protection by System Design), 28-6
 - UG-127(d) (Open Vents), 28-6
 - ASME Section VIII, Divisions 2 and 3 (High Pressure Vessels), 28-8
 - ASME Section X (Fiber-Reinforced Plastic Pressure Vessels), 28-8
 - jurisdictional requirements and, 28-5
 - National Board (NB-18) Pressure Relief Device Certification (The Redbook), 28-8
 - pressure relief valve inlet pressure drop (the 3% rule), 28-7
 - pressure relief valve outlet pressure drop (the 10% rule), 28-7–28-8
 - pressure vessels with internal pressures of 15 psi and less, 28-8
- American Society of Mechanical Engineers (ASME) Codes and Standards
- B31.1 (Power Piping Code), 31-1. *See also* B31.1 (Power Piping Code)
 - B31.3 (Process Piping Code), 31-1. *See also* B31.3 (Process Piping Code)
- American Society of Mechanical Engineers (ASME) Flange design methodology, 9-7
- Appendix Y flanges, 9-24–9-27
 - clamp connections, design rules for, 9-27–9-29
 - Figure 9.1 (Flange Discontinuity Analysis), 9-8
 - Figure 9.2 (Forces Acting on a Flange Joint), 9-9
 - Figure 9.3 (Types of Flanges), 9-11–9-12
 - Figure 9.4 (Values of T , U , Y , and Z [Terms Involving K]), 9-15
 - Figure 9.5 (Values of F [Integral Flange Factors]), 9-16
 - Figure 9.6 (Values of f [Hub Stress Correction Factor]), 9-17
 - Figure 9.7 (Values of V [Integral Flange Factors]), 9-17
 - Figure 9.8 (Values of F_L [Loose Hub Flange Factors]), 9-18
 - Figure 9.9 (Values of V_L [Loose Hub Flange Factors]), 9-18
 - Figure 9.10 (Reverse Flange), 9-21
 - Figure 9.11 (Loose Ring-Type Reverse Flange), 9-22
 - Figure 9.12 (Flange Dimensions and Forces), 9-25
 - Figure 9.13 (Typical Hub and Clamp), 9-28
 - Figure 9.14 (Typical Clamp-Lug Configurations), 9-29
 - flange design for external pressure, 9-23–9-24
 - flange stresses, 9-18–9-21
 - flat-flanged heads and blind flange, 9-22–9-23
 - full-face gaskets, flange design for, 9-29–9-30
 - header flange design, 9-30
 - historical background and technical basis, 9-7–9-8
 - integral flanges, 9-15–9-16
 - lap-joint flanges, 9-18
 - loose flanges, 9-16
 - loose split-ring flanges, 9-24
 - noncircular flanges with circular bore, 9-24
 - raised-face and ring-joint flanges using ring-type gaskets, 9-8–9-15
 - rectangular flanges, 9-30
 - reverse flanges, 9-21–9-22
 - scope and design philosophy, 9-8
 - slip-on flanges, 9-16
 - socket-welding flanges, 9-16, 9-18
 - Table 9.2 (Moment Arms), 9-9
 - Table 9.3 (Effective Gasket Width), 9-10
 - Table 9.4 (Gasket Materials and Contact Facings), 9-13–9-14
 - Table 9.5 (Bolt Area and Spacing), 9-15
 - threaded flanges, 9-18
- American Society of Mechanical Engineers (ASME) Flange standards, 9-7, 9-21
- B16.5, 9-1, 9-2, 9-7
 - B16.47, 9-1, 9-7
 - gaskets and, 9-7
- American Society of Mechanical Engineers (ASME) Nuclear Systems-Based Code development, 22-21–22-22, 22-21f
- American Society of Mechanical Engineers (ASME) Piping Codes, 9-1, 9-5
- ASME B31.4, *Liquid-Transmission Piping*, 9-7
 - ASME B31.1, *Power Piping*, 9-6
 - paragraph 104.5, 9-6
 - paragraph 108.5, 9-6
 - Table 112, 9-6
 - ASME B31.3, *Process Piping*, 9-5–9-6
 - Appendix L, 9-6
 - Chapter IX (High-Pressure Piping), 9-6
 - F312, 9-5
 - paragraph 301.3.2, 9-5–9-6
 - paragraph 302.2.4, 9-6
 - paragraph 306.4, 9-6
 - paragraph K304.5.1, 9-6
 - ASME B31.8, *Gas-Transmission Piping*, 9-6–9-7
- American Society of Mechanical Engineers (ASME) Pressure Vessel Codes, 9-1
- Section I, 9-23–9-6
 - Appendix A-360 Table, 9-3
 - PG-3, 9-3
 - PG-31, 9-3
 - PG-42.1, 9-4
 - PG-42.4.4, 9-4
 - PG-42.4.5, 9-4
 - PG-42.4.7, 9-4
 - PG-42.4.8, 9-4
 - PG-59.1.1.2, 9-3
 - Table A-361, 9-3
 - Section III, 9-4–9-5
 - Class 1 bolting, 9-4
 - Class 1 components, 9-4
 - Class 2 piping, 9-5
 - Class 1 piping systems, 9-4–9-5

American Society of Mechanical Engineers (ASME) Pressure Vessel

Codes (*continued*)

Class 2 vessels, 9-5

NB-3132, 9-4

NB-3200, 9-4

NB-3222, 9-4

NB-3226, 9-4

NB-3227.4, 9-4

NB-3230, 9-4

NB-3232, 9-4

NB-3232.3, 9-4

NB-3647, 9-4

NB-3658, 9-4–9-5

NC-3262.1, 9-5

NC-3262.2, 9-5

NC-3262.3, 9-5

NC-3262.4, 9-5

NC-3658.1, 9-5

NC-3658.2, 9-5

NC-3658.3, 9-5

Section VIII, Division 1, 9-1–9-2

Appendix 2, 9-2

Appendix 24, 9-2

Appendix S, 9-2

Appendix Y, 9-2

Section II, Part D, 9-2

Table U-3, 9-2

UG-22, 9-2

UG-34, 9-2

UG-44, 9-1

UG-11(a)(2), 9-2

Section VIII, Division 2, 9-2–9-3

Section VIII, Division 3, 9-3

Appendix G, 9-3

KD-601, 9-3

KD-621, 9-3

American Society of Mechanical Engineers (ASME) Probabilistic

Risk Assessment (PRA) Standard, 22-2–22-6. *See also*

Probabilistic risk assessment (PRA)

application of, 22-4

ASME/ANS PRA Standard, 29-4

configuration control, 22-5

evolution of, 22-2–22-3

introduction of, 22-3–22-4

objectives of, 22-2–22-3

overview, 22-2

PRA models and, 29-7

scope of, 22-3–22-4

and technical adequacy of PRAs

industry standards, 29-4

Regulatory Guides, 29-4

technical requirements, 22-4–22-5

American Society of Testing and Materials (ASTM) Standards

epoxy materials

ASTM D445, 26-6

ASTM D1544, 26-6

ASTM D1652, 26-6

ASTM D1763, 26-6

ASTM D2393, 26-6

graphite materials

ASTM C709, 26-8

ASTM C781, 26-6

ASTM C838, 26-6, 26-8

ASTM D346, 26-8

ASTM D2638, 26-8

ASTM D7219, 26-6

thermoplastic components joining

ASTM C1147, 26-8

ASTM D2657, 26-8

ASTM D3261, 26-8

ASTM F905, 26-8

ASTM F1055, 26-8

ASTM F1056, 26-8

ASTM F1290, 26-8

ASTM F2620, 26-8

thermoplastic materials

ASTM C177, 26-5

ASTM D92, 26-7

ASTM D224, 26-5

ASTM D256, 26-5

ASTM D638, 26-5

ASTM D695, 26-5

ASTM D696, 26-5

ASTM D785, 26-5

ASTM D790, 26-5

ASTM D792, 26-5

ASTM D883, 26-7

ASTM D1238, 26-5, 26-7

ASTM D1248, 26-5

ASTM D1505, 26-5

ASTM D1598, 26-7

ASTM D1599, 26-7

ASTM D1603, 26-6, 26-7

ASTM D1693, 26-7

ASTM D1929, 26-6

ASTM D2122, 26-7

ASTM D2290, 26-7

ASTM D2412, 26-6

ASTM D2683, 26-7

ASTM D2774, 26-7

ASTM D2837, 26-6

ASTM D2839, 26-7

ASTM D3035, 26-7

ASTM D3261, 26-7

ASTM D3350, 26-5

ASTM D4218, 26-6

ASTM D4349, 26-5

ASTM D4883, 26-6

ASTM D4976, 26-5

ASTM F412, 26-7

ASTM F714, 26-7

ASTM F1055, 26-7

ASTM F1248, 26-7

ASTM F1473, 26-7

ASTM F2206, 26-7

ASTM F2634, 26-6

thermoset plastic components

ASTM D570, 26-8

ASTM D648, 26-8

ASTM D2583, 26-8

ASTM D2996, 26-7

ASTM D3299, 26-7

ASTM D3517, 26-8

ASTM D4021, 26-8

- ASTM D4024, 26-8
 ASTM D4097, 26-8
 ASTM D5421, 26-8
 ASTM D5685, 26-8
 ASTM D5813, 26-8
 ASTM D6041, 26-8
 ASTM F1668, 26-8
- American Standards Association (ASA), 1-2, 23-1
 AMP. *See* Aging management program
 AMR. *See* Aging management review
 Anaerobic digester, for sewage treatment, 6-16
 Analysis of Public Comments on the Revised License Renewal Guidance Documents (NUREG-1832), 18-9
- Ancillary systems
 chemical and volume control system (CVCS), 15-15
 component cooling water system (CCWS), 15-16
 emergency feedwater system (EFWS), 15-16
 essential service water system (ESWS), 15-16
 extra borating system (EBS), 15-16
 in-containment refueling water storage tank (IRWST), 15-16
 ITER, 33-9
 safety injection system/residual heat removal system (SIS/RHRS), 15-15–15-16
- ANI. *See* Authorized Nuclear Inspector
 ANIS. *See* Authorized Nuclear Inspector Supervisor
 ANL. *See* Argonne National Laboratory
 Annex building, 15-8
 Westinghouse SMR, 32-19
- Anode-to-electrolyte resistance, 11-47
 ANS. *See* American Nuclear Society
 ANSI. *See* American National Standards Institute
 ANSI/ANS-58.21-2007, 22-22
 ANSI/ANS-58.23-2007, 22-22
 ANSI/ASME B31 G manual, 11-29
 ANSI B16.9, 4-8, 4-9
 ANSI Standards, 1-2
 ANS Standard 58.2, 1988, 6-1
 ANS Standard 58.3, Appendix B, 6-1
 Ansys, for stress analysis, 6-11
 Anticipated trips without scram (ATWS), 16-14
 Anti-electron, 33-2
 AOTs. *See* Allowed Outage Times
- API-590, 23-6
 API 1104, 11-31–11-32
 API 579-1/ASME FFS-1, 31-4
 API 579-1/ASME FFS-1 (*Fitness-For-Service*), 24-2, 24-15, 24-20
 API Standard 520, Part I
 backpressure defined, 28-7
 API Standard 620, 6-13
 API Standard 650, 6-13
 Apparent wave-propagation speed, 6-3
 Appendices, 1-5
 Appendix BFJ, ASME Section VIII, Division 1, 9-36
 Appendix D of NUMARC 87-00, 2-12
 Appendix E of Section XI Code, 7-11
 Appendix H, Reactor Vessel Material Surveillance Program Requirements, 20-3
 Appendix II of ASME B31.1 Code, 6-1
 Appendix J of 10CFR50, 2-10
 Appendix L (Section VIII, Division 1 [Rules for Construction of Pressure Vessels]), 24-9
 Appendix N of ASME B&PV Code Section III, 6-1
- Appendix N, Tables N-1221(a & b)-1, 6-8
 Appendix S of Section VIII, Division 1, 9-34–9-35
 Appendix U (ASME Section XI), 27-15
 Appendix Y flanges, 9-24–9-27
 design of, procedure for, 9-25
 example, 9-25–9-27
 flange categories, 9-24–9-25
 flange classification, 9-24
- AP1000® plant, 32-13, 32-14, 32-16, 32-20, 32-21
 vs. Westinghouse SMR, 32-13, 32-13f
- AP1000 PWR
 CRDM and driveline, 15-3
 fuel, 15-4
 in-core instrumentation, 15-4
 operational technology, 15-3–15-4
 plant design, 15-2
 pressurizer, 15-4
 pumps, 15-4
 reactor internals, 15-3
 reactor pressure vessel, 15-3
 steam generators, 15-3
 thermocouple instrumentation, 15-4
- Argonne National Laboratory (ANL), 16-3, 17-2
 fatigue life models, 30-7, 30-8
- ASA. *See* American Standards Association
 ASA B16.5–1957, 1-2
 ASA B31.1–1955, 1-2
- Asbestos, detection of, 12-4, 12-6
- ASCE. *See* American Society of Civil Engineers
 ASCE Standard 4-98, 6-1
 ASCE Standard 7-02, 6-1, 6-7, 6-13
- ASME. *See* American Society of Mechanical Engineers
 ASME/ANS Joint Committee on Nuclear Risk Management (JCNRM), 22-3
 ASME/ANS RA-S1-2008, 22-2
 ASME/ANS RA-Sb-2013 PRA Standard, 22-2
 application, 22-4
 capability categories, 22-4t
 configuration control, 22-5
 evolution and objectives, 22-2–22-3
 introduction and scope, 22-3–22-4
 technical requirements, 22-4–22-5
- ASME B16.9 (Factory-Made Wrought Butt welding Fittings), 31-5
 ASME B31.1, power piping, 4-18
 ASME B31.1-2012, on piping vibration, 3-2–3-3
 ASME B31.3, process piping, 4-18
 ASME B31G (Manual for Determining the Remaining Strength of Corroded Pipelines), 31-4
- ASME Boiler and Pressure Vessel (B&PV) Code, history of, 1-1–1-2
 authorized inspection and, 1-5–1-6
 Boiler and Pressure Vessel Committee, establishment of, 1-2
 certification for nuclear construction, 1-3–1-4
 developments of 1970s, 1-4–1-5
 and future developments, 1-25, 1-28, 1-30, 1-32–1-34, 1-36
 inservice inspection and, 1-7
 nuclear components, incorporation of, 1-2
 piping, pumps, and valves in 1960s, 1-3
 piping, vessels, pumps, and valves in 1950s, 1-2
 Quality Assurance Program requirements and, 1-6–1-7
 Registered Professional Engineer and, 1-5
 repair and replacement program and, 1-7–1-8

- ASME Boiler and Pressure Vessel (B&PV) Code, history of
(*continued*)
Section III Code, 1-3
Section XI and, 1-7
- ASME Boiler & Pressure Vessel Code, 16-19
- ASME Boiler & Pressure Vessel Code, Section III, Case N-47, 17-3
- ASME B31.1 piping code, 30-12
- ASME BPVC Appendix G (Article G-2120), 20-14
- ASME BPVC IWB-3640, 19-18
- ASME B&PV Code
Section III, 3-2
Section VIII, 1-2
- ASME B&PV Code Section III, 14-4
Appendix N, 6-1
operating life of the plant in, 6-1
- ASME BPVC reactor vessel inspection requirements, 21-10–21-11
Table IWB-2500-1, Examination Category B-F, 21-11
Table IWB-2500-1, Examination Category B-J, 21-11
Table IWB-2500-1, Examination Category B-N-2, 21-11
Table IWB-2500-1, Examination Category B-O, 21-11
Table IWB-2500-1, Examination Category B-P, 21-11
Table IWB-2500-1 for primary system piping (Examination Categories B-F and B-J), 21-11
- ASME BPVC Section III, 19-14
Appendix G and WRC 175, 20-2–20-3
NB-3200, 19-20
- ASME BPVC Section VIII, 20-1
- ASME BPVC Section XI
Addenda of, 19-19
Appendix A, 19-22
Appendix C, 19-18
- ASME BPVC Section XI, Appendix G
circumferential reference flaw, 20-6–20-7
pressure stress intensity factors, 20-5–20-6
revised stress intensity factor, 20-5
revisions to, 20-3–20-4
thermal stress intensity factors, 20-6
- ASME BPVC Section XI, Appendix G, G-2216, Risk-Informed Allowable Pressure, 20-15
- ASME BPVC Section XI, Appendix G, G-2500, Risk-Informed Hydrostatic Leak Testing, 20-15
- ASME BPVC Section XI, Appendix G, improvement to probabilistic P-T limit curves, 20-14–20-15
reference flaw size reduction, 20-14
- ASME BPVC Section XI, Appendix G method. *See* ASME BPVC Section XI, Appendix G
- ASME BPVC Section XI, IWB-3740, 19-21
- ASME BPV II (Materials), 26-3
- ASME B31.8 standard, 11-7–11-8
- ASME Certification Mark, 28-4
- ASME Code aspects, 15-30
- ASME Code Case 2695
VIII-1, 24-5t, 24-9
VIII-2, 24-18
- ASME Code Case N-47, 17-7
- ASME Code Case N-411, 14-3
- ASME Code Case N-716, 29-5
- ASME Code Edition, 16-20
- ASME Code fatigue curves, 5-3. *See also* Cyclic loading, Code design and evaluation for
- ASME Code for very high-temperature service
creep fatigue, 17-12
environmental effects, 17-12
material creep behavior, 17-12
simplified design analysis methods, 17-12
structural integrity of welds, 17-12
verification testing, 17-12–17-13
- ASME Code Section VIII, 28-3
- ASME Conformity Assessment, 1-28
- ASME Innovative Technologies Institute, LLC, 22-23
- ASME Nuclear Quality Assurance (NQA) Committee, 22-22
- ASME OM-S/G, Part 3, 6-1
- ASME Operations and Maintenance (O&M) Code, 22-15–22-19
Code Cases
OMN-3 for Risk Categorization, 22-16–22-17
OMN-10 for Snubbers, 22-18–22-19
OMN-4 for Treatment of Check Valves, 22-17
OMN-11 for Treatment of Motor-Operated Valves, 22-18
OMN-12 for Treatment of Pneumatic and Hydraulic Valves, 22-18
OMN-7 for Treatment of Pumps, 22-18
Subsection ISTE, “Risk-Informed Inservice Testing of Components in Light-Water Reactor Nuclear Power Plants,” 22-18–22-19
overview, 22-15–22-16
- ASME Piping Codes, 4-18
B31.1, 4-18
B31.3, 4-18
- ASME PTB-4-2013 (*ASME Section VIII-1 Example Problem Manual*), 24-4, 24-9–24-10
- ASME RA-S-2002, 22-2, 22-19, 22-20
- ASME RA-Sa-2003, 22-2
- ASME RA-Sb-2005, 22-2
- ASME RA-Sc-2007, 22-2
- ASME Section III, Appendix F, paragraph F-1334, 7-15
- ASME Section III, Appendix F, paragraph F-1335, 7-15
- ASME Section III, Division 1 Code Classes 1, 2, and 3 safety-related piping, 14-1
- ASME Section XI Code Case N-504-4, 21-21
- ASME Section XI Code Case N-638, 21-23
- ASME standards
nuclear fusion, 33-14
- ASME Subcommittee on Safety Valves, 28-3
- ASME Subgroup on Fatigue Strength (SGFS), 5-22
- Assembly, ITER, 33-11
- ASTM E 900-02, Guide for Predicting Radiation-Induced Transition Temperature Shift in Reactor Vessel Materials, 20-12, 20-13
- ASTM E 900-87, Standard Guide for Predicting Neutron Radiation Damage to Reactor Vessel Materials, 20-12
- Atomic Energy Act, 18-1
- Atomic Energy Agency (AEA), 10-1, 10-3, 10-5, 10-8–10-11
- Atomic Energy Commission (AEC), 1-3, 22-1, 25-1, 29-2, 29-3
- Augmented inspection requirements
for alloy 82/182 dissimilar metal butt welds in PWR primary, 21-12–21-13
for RPV BMI nozzles, 21-12
for RPV top-head nozzles, 21-11–21-12
- Austenitic and nickel-based materials, 19-23
- Austenitic stainless steels (SSs), 16-17–16-18, 19-22
in LWR environments, fatigue lives of, 30-10
- Authorized Inspection Agency (AIA), 1-5–1-6, 28-6
- Authorized Nuclear Inspector (ANI), 1-5–1-6
- Authorized Nuclear Inspector Supervisor (ANIS), 1-5–1-6
- Automatic depressurization system (ADS), 15-5

- Auxiliary building (A/B), 15-8, 15-29
 Aviation and Transportation Act (PL107-71), 11-54
 AWWA C906, 26-7
 AWWA C950, 26-8
 Axial bending stress, 4-11
 Axial cracks, 21-13
 Axial shrinkage magnitude, 19-18, 19-19
- B31.1 (Power Piping Code), 28-8–28-9, 31-1
 failures, 31-1–31-6
 expansion joints, 31-2–31-3
 Flexibility Factors, 31-5
 flow assisted corrosion (FAC), 31-4
 gas blows, 31-3
 material identification/verification, 31-4
 pipe fittings and, 31-5
 Stress Intensification Factors (SIF), 31-5
 vacuum conditions, 31-5–31-6, 31-6f
 vibration problems, 31-4–31-5
 water hammer/steam hammer, 31-3
 welded piping operation in creep range, 31-1
 B31.1–1955, 1-3
 B31.3 (Process Piping Code), 28-9, 31-1
 failures, 31-1–31-6
 expansion joints, 31-2–31-3
 Flexibility Factors, 31-5
 flow assisted corrosion (FAC), 31-4
 material identification/verification, 31-4
 pipe fittings and, 31-5
 Stress Intensification Factors (SIF), 31-5
 vacuum conditions, 31-5–31-6, 31-6f
 vibration problems, 31-4–31-5
 water hammer/steam hammer, 31-3
 welded piping operation in creep range, 31-1
- Backfitting, of new code requirements, 1-8
 Backpressure, defined, 28-7
 Back-to-back fittings, use of, 3-15
 Baku-Tbilisi-Ceyhan crude oil pipeline, 11-2, 11-53
 Balance of plant (BOP), 16-1
 Balkey, Kenneth R., 22-1
 Ball expansion joints, 31-3t
 Ballistic Research Laboratory, 6-18
 Bare metal visual inspections, 21-10
 Barrier, 6-3
 Barrier structural integrity, 17-11
 Bayes, Thomas, 29-1
 BCA. *See* Board on Conformity Assessment
 B31 code, 23-1
 B31.12 code, 23-2
 B31 committee, 1-2, 1-3
 Beck, Clifford, 29-3
 Bellows expansion joints, 31-2t
 Bending moment, 19-4
 BEP. *See* Boiler External Piping
 Bernoulli equation, 8-3
 Bernoulli's assertion, 29-1
 Bernsen, Sidney A., 22-1
 Bernstein, Peter, 29-1
 Beta testing, VIII-2 and, 24-13–24-14
 results of, 24-14, 24-15t, 24-16t
 BFN (Browns Ferry nuclear power plant), 29-5
 Bio-corrosion, 11-41. *See also* Corrosion
- Biphase systems, 6-14. *See also* Biphase systems
 fluidhammer in, 6-14
 Blach method, 9-30
 Blanket system, ITER, 33-8, 33-8f
 Blind flanges, 9-2
 BMI. *See* Bottom-mounted instrument
 BMN. *See* Bottom mounted nozzles
 BNCS. *See* American Society of Mechanical Engineers Board on
 Nuclear Codes and Standards
 Board on Conformity Assessment (BCA), 1-15, 1-18
 Boiler and Pressure Vessel Committee, establishment of, 1-2
 Boiler Code Committee, 1-1
 Boiler External Piping (BEP)
 requirements for, 31-4
 Boiling water reactor (BWR)
 advantages of, 16-4
 ASME Code Edition, 16-20
 BWR product line, evolution of, 16-1–16-9
 containment design, 16-7–16-9
 disadvantages of, 16-4
 environmental fatigue rules, 16-19–16-20
 ESBWR, features of, 16-9–16-15
 Figure 16.1 (Evolution of the BWR Reactor System Design), 16-3
 Figure 16.2 (ESBWR Steam and Power Conversion System), 16-6
 Figure 16.3 (Evolution of the BWR Containment Design), 16-8
 Figure 16.4 (ESBWR Reactor Assembly), 16-10
 Figure 16.5 (Comparison of ESBWR Operating Power/Flow Map
 with Operating BWRs), 16-11
 Figure 16.6 (ESBWR Key Safety Systems), 16-11
 Figure 16.7 (ESBWR Gravity-Driven Cooling System), 16-12
 Figure 16.8 (ESBWR Passive Containment Cooling System),
 16-13
 Figure 16.9 (ESBWR Standby Liquid Control System), 16-14
 Figure 16.10 (ESBWR Isolation Condenser System), 16-15
 Figure 16.11 (ABWR/ESBWR RPV Feedwater Nozzle), 16-16
 Figure 16.12 (ABWR RPV Forged Steel Ring), 16-17
 Figure 16.13 (Schematic of an ABWR Feedwater Piping System),
 16-19
 materials selection/water chemistry controls, 16-17–16-19
 modularization techniques, 16-20
 natural circulation design, 16-9
 operating domain, 16-9–16-10
 overview, 16-1
 passive safety features, 16-10–16-15
 progression of BWR designs, 16-1–16-3
 reactor system design, 16-3–16-5
 RPV design, 16-16
 safety system design, 16-5–16-7
 Table 16.1 (Evolution of the GE BWR), 16-2
 Table 16.2 (Comparison of Key Features of GE BWR), 16-5
 Table 16.3 (Comparison of Key Features of GE BWR
 Containments), 16-9
 Table 16.4 (Current Code and Environmental Fatigue Usage
 Factors for an ABWR Feedwater Line), 16-20
 Boiling water reactor experiment (BORAX), 16-3
 Boiling water reactor (BWR) internals. *See also* Reactor pressure
 boundary piping, BWR; Weld overlay repairs
 alternate inspection frequency, 19-11–19-12
 alternate inspection method for nozzle inner radii, 19-9–19-11
 crack initiation, growth relationships, plant monitoring, 19-20–
 19-24
 feedwater nozzle, 19-8–19-9

Boiling water reactor (BWR) internals (*continued*)

- Figure 19.1 (Overview of BWR Pressure Vessel and Internal Components), 19-2
 - Figure 19.2 (BWR Core Shroud Weld Designations), 19-3
 - Figure 19.3 (A Distributed Ligament Length Example), 19-3
 - Figure 19.4 (Typical Geometry of a BWR Jet Pump), 19-5
 - Figure 19.5 (Sample of Stress Time History at Cracked Location), 19-5
 - Figure 19.6 (Predicted Crack Lengths for Various Core Flow Levels), 19-6
 - Figure 19.7 (BWR Steam Dryer Assembly), 19-7
 - Figure 19.8 (Steam Dryer Damage), 19-8
 - Figure 19.9 (Cross-Section of Feedwater Nozzle with Cracking Location), 19-9
 - Figure 19.10 (Improved Thermal Sleeve Design and Temperature Variations with and without Bypass), 19-10
 - Figure 19.11 (Fracture Mechanics Results for Several BWRs), 19-10
 - Figure 19.12 (BWR Feedwater Nozzle Inspection Zones [Clad-Removed Nozzle]), 19-12
 - Figure 19.13 (A Typical BWR Set-In CRD Stub Tube Design), 19-12
 - Figure 19.14 (Stub Tube Narrow Groove Welded Partial Design), 19-13
 - Figure 19.15 (BWR-2 Shroud Support Geometry), 19-14
 - Figure 19.16 (Calculated Values of Total K and the Polynomial Fit), 19-14
 - Figure 19.17 (Predicted Crack Growth as a Function of Operating Hours), 19-14
 - Figure 19.18 (Steam Dryer Support Bracket Crack), 19-15
 - Figure 19.19 (Temperature-Time Variations during Automatic Blowdown Transient [Level C Condition]), 19-16
 - Figure 19.20 ($J_{0.1}$ Assessment for Level C Conditions), 19-16
 - Figure 19.21 (Weld Overlay Repair), 19-17
 - Figure 19.22 (Core Spray Safe End to Safe-End Extension Weld Overlay), 19-19
 - Figure 19.23 (Design *versus* Actual Number of Transient Events for a Typical BWR Plant), 19-21
 - Figure 19.24 (Severity of Transient Actual Temperature Change *versus* Percentage of Design Basis), 19-21
 - Figure 19.25 (Effect of Loading Conditions on $\Delta a/\Delta N_{EAC}$ and Comparison with ASME Section XI Curves), 19-22
 - Figure 19.26 (Schematic Oxidation Charge Density/Time Relationship for a Strained Crack Tip and Unstrained Crack Sides), 19-22
 - Figure 19.27 (Comparison of BWRVIP-14 and Japan Maintenance Code Predictions), 19-23
 - Figure 19.28 (BWRVIP-60 SCC Disposition Lines), 19-23
 - Figure 19.29 (Crack Length *versus* Total Time-On-Test for Type 304 Stainless Steel), 19-24
 - Figure 19.30 (Predicted Crack Growth in Safe End), 19-24
- inspection, evaluation, repair methods, 19-1
 - jet pumps, 19-4–19-6
 - low upper shelf energy evaluation, 19-15–19-16
 - other internals, 19-6
 - pressure vessel, 19-6–19-16
 - probabilistic fracture mechanics for inspection exemption, 19-6–19-8
 - reactor pressure boundary piping, 19-16–19-20
 - shroud, 19-1–19-4
 - steam dryers, 19-6
 - stub tube cracking, 19-12–19-13
 - Table 19.1 (Jet Pump FIV Stress Range versus Cycle Data [100 HR of Operation]), 19-6
 - Table 19.2 (Feedwater Nozzle/Sparger Inspection Recommendations), 19-11
 - Table 19.3 (BWR RPV Equivalent Margin Review Summary), 19-16
 - Table 19.4 (Comparison of Required Thickness of Weld Overlay Repair), 19-20
 - vessel attachment weld cracking, 19-13–19-15
- Boiling Water Reactor Owners Group (BWROG), 25-5
 - Boiling water reactor (BWR) pressure vessel
 - alternate inspection frequency, 19-11–19-12
 - alternate inspection method for nozzle inner radii, 19-9–19-11
 - feedwater nozzles, 19-8–19-9
 - low upper shelf energy evaluation, 19-15–19-16
 - probabilistic fracture mechanics for inspection exemption, 19-6–19-8
 - stub tube cracking, 19-12–19-13
 - vessel attachment weld cracking, 19-13–19-15
 - Boiling water reactors (BWRs)
 - LWR environments effect on fatigue life of components, 30-7, 30-8
 - mitigation capabilities enhancement, 30-2
 - Boiling water reactor vessels and internals project (BWRVIP), 19-1, 19-12, 19-23
 - Bolted flange joints. *See* Flanged joints
 - Bolt spacing, in flange design, 9-35
 - Bolt-stress limits, 9-31
 - Boric Acid Corrosion Guidebook, 21-14
 - Boric acid wastage
 - core damage and, 21-26
 - for larger leaks, 21-14–21-15
 - Boron, 16-14
 - Bottom-mounted instrument (BMI), 21-3, 21-4
 - penetrations, 21-3–21-4
 - Bottom mounted nozzles (BMN), 21-3
 - Boundary conditions, 14-3
 - Bounding spectra, 6-3
 - Branch connection
 - class 2 or 3 piping
 - check of branch end, 4-17
 - check of run ends, 4-17
 - class 1 piping, 4-17
 - Brittle fracture prevention, codes and regulations for. *See also* Pressurized water reactor (PWR) vessel integrity
 - 10 CFR 50, Appendix G, 20-2
 - factor of safety, 467
 - K_{IR} index and temperature indexing, 20-2
 - postulated flaw size and location, 20-2–20-3
 - Section III, Appendix G and WRC 175, 20-2–20-3
 - Broadband-response spectrum, 6-3
 - Browns Ferry nuclear power plant (BFN), 29-5
 - BS 4994 Standard, 26-9
 - B16 Standard. *See* American Society of Mechanical Engineers (ASME) B16 Standard
 - B16.1 standard, 23-4
 - B16.5 standard, 23-4, 23-5, 23-5–23-6, 23-9
 - scope of, 23-5
 - B16.7 standard, 23-6
 - B16.9 standard, 23-6, 23-7
 - B16.10 standard, 23-8
 - B16.11 standard, 23-6

- B16.20 standard, 23-7
- B16.21 standard, 23-7
- B16.25 standard, 23-6–23-7
- B16.34 standard, 23-9
- B16.36 standard, 23-6, 23-9
- B16.42 standard, 23-4
- B16.45 standard, 23-4
- B16.47 standard, 23-6, 23-9
- B16.48 standard, 23-6
- B16.49 standard, 23-7
- B16.53 standard, 23-7
- B*-stress indices, 4-12–4-13
 - elbows and, 4-13
 - seismic analyses, 4-13
 - straight pipe and, 4-12
- Building configuration, US-APWR, 15-28–15-29
 - access building, 15-29
 - reactor building complex, 15-29
 - turbine building, 15-29
- Built-up backpressure, 28-7
- Bulk flow, 8-8–8-10
- Buried metallic pipe, flaw evaluation in (Section XI), 27-15–27-19
 - Acceptance Standards for metal loss, 27-17
 - level 2 analytical evaluation method, 27-17–27-19
 - for internal pressure, 27-17–27-18
 - of longitudinal stresses, 27-18
 - of shear stresses, 27-18–27-19
 - metal loss characterization, 27-16–27-17
 - overview, 27-15–27-16
- Buried pipe-leakage issues
 - overview, 30-11
 - protection measures, 30-11
- Butt-welding, 23-6
- Butt-welding tees, 4-8–4-9
- Butt welds, 21-4
- BWR. *See* Boiling water reactor
- BWR/2 bottom head, 19-12
- BWR-2 in Japan, 19-13, 19-14
- BWROG. *See* Boiling Water Reactor Owners Group
- BWR Owners Group IGSCC Research Program, 19-17
- BWRs. *See* Boiling water reactors
- BWR steam dryers, for EPU operation, 30-1, 30-15
 - acoustic mitigation device, 30-16
 - acoustic resonance, 30-15–30-16
 - single and double vortex, 30-16
 - analytical methodology related issues, 30-17–30-18
 - bias errors and uncertainties related issues, 30-17
 - fabrication, installation, and quality control, 30-18
 - monitoring, 30-18
 - MSL and dryer instrumentation related issues, 30-17
 - steam dryer margin, 30-16–30-17
- Bypass leakage, 19-9
- CAB. *See* Customer Advisory Board
- Cable resistance, 11-47
- Caesar-II, 6-11
- “Call before you dig” program, 11-49
- Canada Deuterium Uranium (CANDU) reactors, 17-7
- Canadian Transportation Safety Board, 11-3
- Cantilever tests, 4-3
- Caprolactam plant accident (Flixborough, UK), 31-3, 31-3f
- Carbon
 - F_{en} for, 30-10
- Carbon steel piping
 - HDPE for replacement of, in safety related class 3 buried piping, 30-11–30-15
 - lessons learned and special design considerations, 30-12
 - material, fabrication, and examination related issues, 30-14–30-15
 - overview, 30-11–30-12
 - structural related issues, 30-13–30-14
 - thermal gradient stress, 30-12–30-13
 - values of properties, 30-12t
- CASS. *See* Cast austenitic stainless steel
- Cast austenitic stainless steel (CASS), 20-17
- Cathodic protection, 11-45
 - calculations, 11-47
 - ground bed types and location, 11-47–11-48
 - impressed current system, 11-45
 - monitoring of, 11-48
 - sacrificial anode systems, 11-46–11-47
- Cavitation, 3-7–3-8
- CAVS. *See* Crack arrest/advance verification system
- CBPVCA. *See* Committee on Boiler and Pressure Vessel Conformity Assessment
- CCDP (conditional core damage probability) values, 22-12
- CCS. *See* Component cooling water system
- CCWS. *See* Component cooling water system
- CDF. *See* Core damage frequency
- CEC. *See* Cavity Enclosure Container
- CEDM. *See* Control element drive mechanism
- Central and eastern United States (CEUS), 14-1
- Central and Eastern United States Seismic Source Characterization (CEUS-SSC), 14-1
- Central axis, 19-4
- Central solenoid (CS), ITER, 33-5, 33-7, 33-7f
- Centrifugal pumps, 8-7
- Certificate Holder, 1-6
- Certificate of Compliance (COC), 1-10–1-13
- Certified seismic design response spectra (CSDRS), 15-28
- CET. *See* Critical exposure temperature
- CEUS. *See* Central and eastern United States
- CFD. *See* Computational fluid dynamics
- CFD Finite Element (FE) codes, 6-3
- 10 CFR 50, Appendix G, 20-2
- 10CFR50.69, 29-6
- 10CFR50.48(c), 29-5
- 10 CFR 50.54(f) letter, 30-5, 30-6
- 10 CFR 50.54(hh)(2), 30-2–30-3, 30-6
- 10 CFR Part 50, NUREG-1860, July 2006, 17-10–17-11
- CGA. *See* Common Ground Alliance
- CGD. *See* Commercial Grade Dedication
- CGR. *See* Crack growth rates
- Charpy shift data, 20-3
- Charpy V-notch (ASTM E 370-88a), 20-8
- Check valve closure, 8-4, 8-6
- Chemical and volume control system (CVCS), 15-15
 - NPM, 32-2, 32-3
- Chemical Safety Board, 31-3
- Chilled water system (CHWS), 33-10
- Chlorinated polyvinyl chloride (CPVC), 26-5
- Choking cavitation, 3-8
- Chromium concentration, 21-5

- Circumferential cracks, 20-19
- Circumferential reference flow, 20-6–20-7
- CIS. *See* Consolidated Interim Storage; Containment internal structure
- Clamp connections, 9-2
design rules for, 9-27–9-29
- CLB. *See* Current licensing basis
- Cleanup Technology Roadmap, DOE, 12-1
- Clemen, Robert T., 29-2
- CLERP (conditional large early release probability) values, 22-12
- Clinch River breeder reactor (CRBR) plant, 17-1, 17-2, 17-6
- CMT. *See* Core make-up tanks
- CNC. *See* Committee on Nuclear Certification
- Coatings, pipelines, 11-41–11-45
adhesive strength of, 11-43
and cathodic protection, 11-43
characteristics of, 11-41–11-42
chemical resistance of, 11-43
coal tar-based, 11-42
damage and repair, 11-44–11-45
electrical resistance of, 11-43
field applied joint coatings, 11-43–11-44
Figure 11.39 (History of Coating Development), 11-42
Figure 11.40 (Multi Layer Composite Coating), 11-42
flexibility of, 11-43
girth weld coating system and repair, 11-43
mechanical strength of, 11-43
primary function of, 11-41
selection and performance criteria, 11-42–11-43
selection of, 11-41
Table 11.15 (Advantages and Disadvantages of Pipeline Coatings), 11-44
Table 11.16 (Classification of Pipeline Coating Tests), 11-45–11-46
testing requirements, 11-44
thermal stability of, 11-43
types of, 11-42
water resistance property of, 11-43
- COC. *See* Certificate of Compliance
- Code Case 504, 19-18, 19-19
- Code Case, N-638, 19-19
- Code Case N-47, 17-3, 17-5, 17-6, 17-8
- Code Case N-201-4, 17-9
- Code Case N-499-1, 17-9
- Code Case N-513, 7-10
- Code Case N-549, 1-18
- Code Case N-606-1, 19-13
- Code Case N-640, 20-9
- Code Case N-641, 20-8
- Code Case N-643, 19-22
- Code Case N-648-1, 19-9, 19-11
- Code Case N-722-1, 21-12
- Code Case N-722-2, 21-12
- Code Case N-729, 25-3
- Code Case N-729-1, 21-11, 21-12
- Code Case N-733, 21-24
- Code Case N-740, 19-19
- Code Case N-754-1, 21-22
- Code Case N-770-1, 21-12
- Code Case No. 10, 1-2
- Code Cases
N-513-3
overview, 27-15
proposed revisions to, 27-15
- N-560 (Alternative Examination Requirements for Class 1, Category B-J Piping, Section XI, Division 1), 22-8
- N-577 (Risk-Informed Requirements for Class 1, 2, and 3 Piping, Method A, Section XI, Division 1), 22-8–22-9
- N-578 (Risk-Informed Requirements for Class 1, 2, and 3 Piping, Method B, Section XI, Division 1), 22-9–22-10
- N-597-2
activities to address NRC conditions on, 27-14–27-15
NRC conditions on, 27-14
overview, 27-14
- N-660 (Risk-Informed Safety Classification for Use in Risk-Informed Repair/Replacement Activities), 22-12–22-13
- N-662 (Alternative Repair/Replacement Requirements for Items Classified in Accordance with Risk-Informed Processes), 22-13–22-15
alternative provisions, 22-14
IWA-4130 Alternative Requirements, 22-14
IWA-4120 Applicability, 22-14
IWA-4300 Design, 22-15
IWA-4180 Documentation, 22-14
IWA 4500 Examination and Test, 22-15
IWA-4170 Inspection, 22-14
IWA-4200 Items Used for Repair/Replacement Activities, 22-14–22-15
IWA-4150 Repair/Replacement Program, 22-14
IWA-4140 Responsibilities, 22-14
IWA-4110 Scope, 22-14
IWA-4400 Welding, Brazing, Defect Removal, and Installation, 22-15
- N-711 (Alternative Examination Coverage Requirements for Examination Category B-F, B-J, C-F-1, C-F-2, and R-A, Piping Welds, Section XI, Division 1), 22-10
- N-716 (Alternative Piping Classification and Examination Requirements, Section XI, Division 1), 22-10
- N-747 (Reactor Vessel Head-to-Flange Weld Examinations, Section XI, Division 1), 22-10
- OMN-3 for Risk Categorization, 22-16–22-17
- OMN-10 for Snubbers, 22-18–22-19
- OMN-4 for Treatment of Check Valves, 22-17
- OMN-11 for Treatment of Motor-Operated Valves, 22-18
- OMN-12 for Treatment of Pneumatic and Hydraulic Valves, 22-18
- OMN-7 for Treatment of Pumps, 22-18
scope of, 22-11–22-12
- Code Cases N-122, 7-15
- Code Cases N-318, 7-15
- Code Cases N-391, 7-15
- Code Cases N-392, 7-15
- Code Cases N-740-2, 21-21
- Code Cases N-761, 19-21
- Code Cases N-629 and N-631, 20-12
- Code Class 2 and Class 3 piping. *See also* Piping system, seismic analysis of
new seismic (alternate) approach, 14-5–14-6
traditional approach, 14-5
- Code Class 1 piping. *See also* Piping system, seismic analysis of
new seismic (alternate) approach, 14-4–14-5
traditional approach, 14-4
- Code equations, elements of
defined, 4-1
- Code fatigue analysis, 18-7
- Code needs, 17-12

- Code of Federal Regulations (10 CFR) Part 54 (the license renewal rule), 18-2
- Code reconciliation
 - examples on, 1-8–1-13
 - need of, 1-8
- Codes for very high temperature generation IV reactors. *See also* Structural integrity evaluation; Structural integrity licensing concerns
 - ASME Code Case N-47, materials and design bases in, 17-7
 - background, 17-1
 - 10 CFR Part 50, NUREG-1860, July 2006, 17-10–17-11
 - elevated temperature service, 17-11–17-12
 - HTGR components, codes and procedures for, 17-8–17-9
 - HTGR environments, material behavior in, 17-9–17-10
 - INEEL/Ext-04-01816, June 30, 2004, 17-10
 - material engineering research needs, 17-8
 - next generation nuclear plant, 17-13
 - NGNP technical issues safety research needs, June 2006, 17-10
 - NRC licensing review, 17-4
 - NUREG/CR-5955, 17-7–17-8
 - NUREG/CR-6816, June 2003, 17-8–17-9
 - NUREG/CR-6824, July 2003, 17-9–17-10
 - power reactor innovative small module (PRISM) liquid-metal reactor, 17-8
 - regulatory issues, 17-4–17-7
 - risk-informed, performance-based process, 17-10–17-11
 - structural integrity evaluation approach, 17-3
 - structural integrity evaluation methods, 17-3–17-4
 - structural integrity licensing, 17-4–17-7
 - summary, 17-1–17-3
 - very high-temperature service, 17-12–17-13
- Code Symbol Stamping, 1-1–1-2
- Coherence, 6-3
- COL. *See* Combined License
- Combined License (COL), 15-31
- Combined operating licenses (COL), 15-2, 32-21
- Combustible gas control, 15-27–15-28
- Commercial boiling water reactor, 16-4, 16-5
- Commercial Grade Dedication (CGD), 1-13, 1-14
- Committee of Manufacturers on Standardization Pipe Fittings and Valves, 23-1
- Committee on Boiler and Pressure Vessel Conformity Assessment (CBPVCA), 1-15
- Committee on Construction of Nuclear Facility Components (III), 1-2
- Committee on Nuclear Inservice Inspection (XI), 1-2
- Committee on Nuclear Certification (CNC), 1-15
- Common Ground Alliance (CGA), 11-1
- Complete station blackout event, NuScale Power plants and, 32-8, 32-8f
- Component cooling water system (CCWS), 15-7, 15-16, 33-10
- Component procurement, for replacements, 1-14
- Component standard supports, 7-15
- Composite wrap repairs, 11-36
- Compressive disturbance propagation, 8-16
- Compressive stresses, 21-26
- Computational fluid dynamics (CFD), 6-3
 - multi-phase flow analysis with, 6-15–6-17
- Computational Fluid Dynamics computer codes, use of, 6-2
- Computational pipeline monitoring, 11-49
- ConAgra Foods incident (Garner, North Carolina), 31-3
- CONCAWE (Conservation of Air and Water Environment), 11-3
- Concrete expansion anchors, 7-15
- Concrete shield building, 15-8
- Condensation-induced waterhammer, 8-7
- Conditional core damage probability (CCDP) values, 22-12
- Conditional large early release probability (CLERP) values, 22-12
- Conical nozzles, 3-9
- Construction codes, 26-5
 - Westinghouse SMR, 32-21
- Construction permit – operating license application (COLA), 16-2, 16-3
- Containment cooling system, 16-7
- Containment design, 16-7–16-9
 - and hydrogen risk, 15-18–15-19
- Containment design, AP1000 plant, 15-7–15-8
 - auxiliary building, 15-8
 - concrete shield building, 15-8
 - nonseismic building, 15-8
 - steel containment, 15-8
- Containment heat removal, 15-19
- Containment internal structure (CIS), 15-29
- Containment isolation, 15-6
 - valves, 16-15
- Containment spray/residual heat removal (CS/RHR) heat exchanger, 15-26
- Containment spray/residual heat removal pump (CS-RHRP), 15-25
- Containment spray system (CSS), 15-26
- Containment vessel (CV)
 - NPM, 32-2, 32-3
 - high pressure CV, 32-5–32-6
 - Westinghouse SMR, 32-17–32-18, 32-17f
- Contamination, 16-18
- Continuous-monitoring systems, 3-17
- Contraction coefficient, 8-4
- Control assemblies, nuclear steam supply system, 15-14
- Control element drive mechanism (CEDM), 21-3
- Control rod drive mechanisms (CRDMs), 15-14, 20-18, 25-2
 - and driveline, 15-25
 - nozzles, 21-1, 21-7, 21-13
 - Westinghouse SMR, 32-16, 32-17f, 32-19
- Control rod drives (CRD), 16-4, 16-5, 19-8, 19-12
- Control room envelope (CRE), 15-27
- Control room simulator laboratory (NuScale), 32-1f, 32-10, 32-10f
- Conventional (non-balanced) pressure relief valves, 28-7
- Coolant pumps, Westinghouse SMR, 32-16, 32-16f
- Cooling water system
 - ITER, 33-10
- Copper, 16-19
- Core damage frequency (CDF), 15-4, 15-18, 15-27, 19-8, 22-2, 32-8
- Core debris cooling under severe accident conditions, 15-27
- Core instrumentation, 15-14
- Core make-up tanks (CMT), 15-4, 32-19
- Core melt
 - high-pressure, 15-18
 - probability of, 15-18
- Core power, 15-14
- Core support attachments, 21-4
- Corium retention and stabilization, 15-19
- Correction coils, ITER, 33-7
- Correction factors, 18-7
- Correlation coefficient, 6-3
- Corrosion, 11-3, 11-4, 16-19
 - costs and effects, 11-39–11-40
 - crevice, 11-41

- Corrosion (*continued*)
- defects, 11-29–11-31
 - definition of, 11-39
 - elements in, 11-39
 - environmental factors affecting, 11-41
 - erosion, 11-41
 - external, in buried pipe, 27-15–27-16, 27-16f. *See also* Buried metallic pipe, flaw evaluation in (Section XI)
 - external pipeline, 11-39
 - Figure 11.37 (Corrosion Cell), 11-39
 - Figure 11.38 (Methods of Mitigating Pipeline Corrosion), 11-41
 - galvanic, 11-41
 - general, 11-40–11-41
 - of heat-resistant materials, 17-10
 - inhibition, 11-48
 - internal pipeline, 11-39
 - microbial influenced, 11-41
 - microbiologically induced, 27-15, 27-15f
 - ratio of cathode to anode size and, 11-41
 - Table 11.13 (Pipeline Corrosion Prevention), 11-40
 - types of, 11-40–11-41
- Corrosion pits, repair of, 11-35
- Corrosion protection
- Subcommittee F Steel Threaded and Welding Fittings (ASME B16 Standard) and, 23-6
- Corrosion resistance
- post-fabrication cleanup and, 26-3
- Corrosion-resistant cladding (CRC), 19-17
- Corrosion-resistant materials, 26-3
- Cost benefit evaluation
- in SAMA analyses, PRAs and, 29-6
- Coulomb damping, 6-11
- Coupled, 6-3
- Crack arrest/advance verification system (CAVS), 19-24
- Crack growth, 21-15–21-18
- Crack growth rate relationships
- for fatigue. *See also* Fatigue initiation
 - austenitic stainless steels, 19-22
 - ferritic steels, 19-22
 - for SCC, 19-22–19-24
 - austenitic and nickel-based materials, 19-23
 - ferritic steels, 19-24
- Crack growth rates (CGR), 19-3
- monitoring, 19-24
 - tests, 5-15
- Cracking, 11-4, 19-12
- in BWR feedwater nozzles, 19-8
 - cause of, 19-16
 - at nozzle penetrations and dissimilar metal welds, 20-18–20-20
- Crack initiation, 5-6, 21-15
- Crack propagation, 5-9, 17-5, 20-9
- Crack(s), 21-9
- in J-groove weld of PWR vessel heads, 25-2–25-3, 25-3f
- CRBR plant. *See* Clinch River breeder reactor plant
- CRC. *See* Corrosion-resistant cladding
- CRD. *See* Control rod drives
- CRDM. *See* Control rod drive mechanism
- CRE. *See* Control room envelope
- Creep behavior, 17-3
- Creep deformation, 17-10
- Creep fatigue, 17-6–17-7, 17-11, 17-12
- Creep fatigue limits (T-1400), 17-5
- Creep relaxation, 17-6
- Creep rupture damage, 17-11
- evaluation methods, 17-6
- Creep Strength Enhanced Ferritic Steels (CSEF) alloys, 26-1–26-3
- Crevices, 16-18
- Critical cavitation, 3-8
- Critical damping, 14-3
- Critical exposure temperature (CET), 24-7
- 9Cr-1Mo CSEF Steels, 26-2
- 9Cr-1Mo ferritic alloy steel, 26-1
- CRTD-86, “Development of Reliability-Based Load and Resistance Factor Design (LRFD) Methods for Piping,” 22-20–22-21
- Cryogenic system, ITER, 33-10
- Cryostat, ITER, 33-9
- CS. *See* Central solenoid
- CSA Z 662-2007 (Canadian pipeline standard), 11-6–11-7
- CSDRSs. *See* Certified seismic design response spectra
- CSEF alloys. *See* Creep Strength Enhanced Ferritic Steels alloys
- CS-RHRP. *See* Containment spray/residual heat removal pump
- CSS. *See* Containment spray system
- CUF. *See* Cumulative usage factor
- Cumulative usage factor (CUF), 18-6, 18-7
- Current drive system, ITER, 33-9, 33-9t
- Current licensing basis (CLB), 7-16, 20-16, 20-17
- fatigue analysis, 18-7
- Customer Advisory Board (CAB), NuScale, 32-12
- Cutoff frequency, 6-3, 6-11–6-12
- CVCS. *See* Chemical and volume control system
- Cyber attack, SCADA systems and, 11-53
- Cycle, 6-3
- Cycle-based FMP, 18-7
- Cyclic finite element creep analysis, 17-12
- Cyclic loading, 17-11, 19-20
- Cyclic loading, Code design and evaluation for, 5-1
- alloy 800 and alloy 600 in air, proposed new fatigue design curve for, 5-11
 - austenitic stainless steels, environmental fatigue design curves for, 5-21–5-22
 - austenitic stainless steels in air, proposed new fatigue design curve for, 5-11
 - carbon and low alloy steels in high temperature water, environmental fatigue design curves for, 5-11–5-21
- Code current determinations, for new fatigue design life evaluation curves, 5-9–5-11
- cumulative damage, estimation of, 5-6
- current regulatory status, 5-24
- design fatigue curves, experimental verification of, 5-7–5-8
- environmental fatigue temperature corrections, 5-22–5-23
- austenitic stainless steels, 5-23
 - carbon and low alloy steels, 5-23
- exemption from fatigue analysis, 5-6–5-7
- fatigue evaluation, procedure for, 5-6
- fatigue failure data and, 5-4–5-6
- Figure 5.1 (Typical Relationship between Stress, Strain, and Cycles to Failure), 5-2
- Figure 5.2 (Stress Fluctuation around Mean Value), 5-2
- Figure 5.3 (Modified Goodman Diagram), 5-3
- Figure 5.4 (Strain History beyond Yield), 5-3
- Figure 5.5 (Graphical Determination of S_{eq}), 5-3
- Figure 5.6 (Idealized Stress vs. Strain History), 5-4
- Figure 5.7 (Fatigue Data, Low Alloy Steels), 5-5
- Figure 5.8 (Fatigue Data, Low Alloy Steels), 5-5

- Figure 5.9 (Fatigue Data, Stainless Steels), 5-5
- Figure 5.10 (PVRC Fatigue Tests), 5-7
- Figure 5.11 (Stable Cyclic Stress-Strain Response of Type 304 Stainless Steel), 5-8
- Figure 5.12 (Stable Cyclic Stress-Strain Response of Nickel-Chromium Alloy 718 at Room Temperature), 5-8
- Figure 5.13 (Fatigue Curve for Austenitic Stainless Steels and Nickel-Iron-Chromium Alloys 600 and 800), 5-9
- Figure 5.14 (Schematic Illustration of Crack Initiation and Propagation Behavior), 5-10
- Figure 5.15 (PVRC Data for Austenitic Stainless Steels in Air at Room Temperature), 5-11
- Figure 5.16 (PVRC Data for Austenitic Stainless Steels in Air at 288°C), 5-12
- Figure 5.17 (Compilation of Stainless Steel Fatigue Data in Air), 5-12
- Figure 5.18 (Comparison of Existing and New Fatigue Design Curves for Austenitic Stainless Steels in Air), 5-13
- Figure 5.20 (Proposed Fatigue Design Curve for Low Strength Nickel Based Alloys, Alloy 600 and Alloy 800 for Temperature Not Exceeding 800°F), 5-14
- Figure 5.21 (Proposed Reference Fatigue Crack Growth Curves for Low Alloy Ferritic Material in Water Environments), 5-15
- Figure 5.22 (Strain Rate Effect for Pressure Vessel Steels in Reactor Water Environment), 5-16
- Figure 5.23 (PVRC Data for Carbon Steels Obtained under Simulated PWR Conditions), 5-16
- Figure 5.24 (PVRC Data for Carbon Steels Obtained under Simulated BWR Reactor Water Environments), 5-16
- Figure 5.25 (PVRC Data for Low Alloy Steels Obtained under Simulated BWR Conditions), 5-17
- Figure 5.26 (Compilation of Environmental Fatigue Data for Carbon Steels), 5-17
- Figure 5.27 (Compilation of Environmental Fatigue Data for Low Alloy Steels), 5-17
- Figure 5.28 (Dissolved Oxygen Effects at 290°C [554°F] at Strain Rate of 0.001% sec), 5-17
- Figure 5.29 (Relative Fatigue Life of Several Heats of Carbon and Low-Alloy Steels at Different Levels of Dissolved Oxygen and Strain Rate), 5-18
- Figure 5.30 (Comparison of Fen Models with PVRC Strain Rate Thresholds for Carbon and Low Alloy Steels), 5-18
- Figure 5.31 (Proposed Environmental Fatigue Design Curves for Carbon and Alloy Steels), 5-19
- Figure 5.32 (Reactor Water Environmental Fatigue Design Curves for Carbon and Alloy Steels), 5-19
- Figure 5.35 (Data for Austenitic Stainless Steel Obtained under Simulated BWR Conditions), 5-21
- Figure 5.37 (Compilation of Environmental Fatigue Data for Stainless Steels), 5-21
- Figure 5.38 (Results of Argonne and Miti Models for Strain Rate Effects on Austenitic Stainless Steel), 5-22
- Figure 5.39 (Fatigue Data on Wrought Steels in Low Oxygen Water Compared to Lower Bound Curve), 5-22
- Figure 5.40 (Environmental Fatigue Design Curves for Types 304, 310, 316 and 348 Austenitic Stainless Steels), 5-23
- Figure 5.41 (Comparison of NUREG/CR-6909 Experimental Environmental Fatigue Data with Proposed Fatigue Design Curves for Austenitic Stainless Steels with Temperature Correction), 5-24
- Figure 5.19 (A) (Fatigue Curve for Nickel-Iron-Chromium Alloy 600), 5-13
- Figure 5.19 (B) (Fatigue Curve for Nickel-Iron-Chromium Alloy 800), 5-14
- mean stress, effect of, 5-2–5-4
- mean stress corrections and cyclic stress-strain properties, use of, 5-8–5-9
- strain-controlled fatigue data, use of, 5-1–5-2
- stress/strain concentration, effect of, 5-2
- Cyclic loads, 6-2
- earthquake or other building filter-cyclic loads, 6-2. *See also* Earthquake loads
- equations of motion, 6-6–6-7
- flutter or vortex-shedding loads, 6-2
- vibratory loads, 6-2
- Cyclic pressure tests, 11-28
- Damage states, 6-3
- Damping, 6-3–6-4, 6-11, 14-3–14-4
- for reducing vibrational response, 3-13–3-14
- Table 6.3 (Structural Percent Critical Modal Damping), 6-12
- Table 6.4 (Appendix N Damping Values), 6-12
- Data Report Form NP-1, 1-3
- Davis-Besse plant, 21-7
- DBA. *See* Design basis accident
- DBE. *See* Design basis earthquake
- DCD. *See* Design certification document; Design control document
- D&D processes, 12-1
- funding for, 12-1
- national efforts, 12-1–12-4
- strategic management of, 12-4
- Table 12.1 (Deactivation & Decommissioning Strategic Initiatives of US DOE), 12-2
- Table 12.2 (Focus of R&D in Various Phases of Provisional Implementation Plan), 12-3
- Table 12.3 (Compendium of Projected D&D Technology Development Needs), 12-5
- Table 12.4 (Other Related Factors and Policy Issues), 12-6
- technology development needs, 12-4–12-7
- Decay heat removal system (DHRS), NPM, 32-3, 32-6, 32-6f
- Decision analysis
- PRA and, 29-2
- Decision Pro Software (Vanguard Software Corporation), 29-2
- “Decision Traps,” 29-2
- Decompressive disturbance propagation, 8-16–8-17
- Degradation predictions
- crack growth, 21-15–21-18
- crack initiation, 21-15
- probabilistic analysis, 21-18–21-20
- Degraded condition, 7-17
- Deluge line flow, 16-12
- De Moivre, Abraham, 29-1
- Dents, 11-28
- Department of Defense, 22-1
- Department of Energy (DOE), 1-30, 12-1
- Department of Transportation (DOT), 10-2, 10-9–10-11
- Departure from nucleate boiling (DNB), 6-15–6-16, 32-16
- Deposition of Public comments and Technical Bases for Changes in the License Renewal Documents, NUREG-1800 and NUREG-1801, 18-10
- Depressurization valves (DPV), 16-3
- Design basis, 7-17
- Design basis accident (DBA), 16-6
- Design basis earthquake (DBE), 6-4, 14-2

- Design basis events, 7-17
- “Design by Analysis” method, 25-3
- Design-by-analysis procedure, 19-20
- Design-By-Analysis Requirements (Part 5, VIII-2), 24-12–24-13
- Design-By-Rule Requirements (Part 4, VIII-2), 24-12
- Design certification document (DCD), 16-20
- Design Certification Program, 16-3
- Design control document (DCD), 15-10
 - US-APWR, 15-22
- Design-ground acceleration, 6-4
- Design ground–response spectrum, 6-4
- Design pressure, 28-1
- Design Reports, 1-5, 1-6
 - fatigue usage values in, 7-6
 - peak stress values in, 7-6
- Design simplicity (size reduction and simplification)
 - NuScale’s economies of small and, 32-10–32-11
- Design Specific Review Plan (DSRP), NuScale, 32-12
- Destructive failure analysis, 21-8
- Deterministic crack growth rate, 21-17
- Deterministic fracture mechanics (DFM), 19-12
- Deuterium (hydrogen-2), 33-1, 33-2
- Deuterium–tritium fusion reaction, 33-3–33-4, 33-3f
 - power production theories, 33-4
 - vs. solar PPI fusion, 33-3
- DFM. *See* Deterministic fracture mechanics
- DHRS. *See* Decay heat removal system
- Diagnostic tools, ITER and, 33-9
- DIAL. *See* Differential Absorption LIDAR
- Diesel buildings, 15-13
- Diesel generator building, 15-8
- Differential Absorption LIDAR (DIAL), 11-50
- Differential shock, 6-14
- Direct current (dc), 15-26
- Direct-integration time-history method, 6-4
- Direct vessel injection (DVI), 15-25, 15-26
- Discharge dampeners, 3-7
- Diseconomies of scale, 32-10
- Displacement transducers, 3-17–3-18
- Dissimilar metal weld (DMW), 20-20
 - inspection, 21-21
 - overlays, 19-19
- Dissolved Oxygen Content (PPM), 5-17
- Divertor module, ITER, 33-8, 33-9f
- DNB. *See* Departure from nucleate boiling
- Document size
 - Section VIII, Division 1 (Rules for Construction of Pressure Vessels), 24-2
- DOE. *See* Department of Energy
- Doel-3 NPP, RPV indications in, 30-19
- DOT. *See* Department of Transportation
- Double containment for plutonium
 - elimination of, 10-17
 - 1974 final rule, 10-12–10-13
 - 1973 proposed rule, 10-11
- DPV. *See* Depressurization valves
- Draft Code Case for Alloy 617, 17-9
- Draft Regulatory Guide DG-1144, 19-21
- Dresden-2 reactor, 29-3
- Dresser couplings, 11-36
- DSRP. *See* Design Specific Review Plan
- Dual cycle design, 16-4
- Dual purpose ultrasonic tool, 11-19
- Dual steam cycle system, 16-4
- Ductile-brittle transition temperature, 15-14
- Duplex redundant digital architecture, 15-27
- DVI. *See* Direct vessel injection
- DWC. *See* Double wall canister
- Dynamic loads, 6-1, 14-4
 - types of
 - cyclic loads, 6-2
 - impact loads, 6-2
 - impulse loads, 6-2–6-3
 - multi-phase flow, 6-3
- Dynamic-transient vibration, 3-1
- EAC. *See* Environmentally-assisted cracking
- EAF. *See* Environmentally assisted fatigue
- Earthquake, 14-2
- Earthquake loads, 6-8
 - closely spaced modes, combinations of, 6-12
 - combined dynamic analysis, 6-12–6-13
 - cutoff frequency, 6-11
 - damping, 6-11
 - direction and time-phase considerations, 6-10–6-11
 - dynamic-earthquake analysis, methods of, 6-11
 - floor-response spectra, 6-9–6-10
 - ground-response spectra, 6-8–6-9
 - missing-mass effects, 6-12
 - time histories, 6-10
 - time-history duration, 6-10
- EBS. *See* Extra borating system
- ECCS. *See* Emergency core cooling system
- Economic simplified boiling water reactor (ESBWR), 16-9–16-15.
 - See also* Passive safety features, BWR
 - gravity-driven cooling system, 16-12
 - isolation condenser system, 16-15
 - natural circulation design, 16-9
 - operating domain, 16-9–16-10
 - passive containment cooling system, 16-13
 - passive safety, 16-10–16-15
 - reactor assembly, 16-10
 - safety systems, 16-11
 - standby liquid control system, 16-14
 - steam and power conversion system, 16-6
- Economies of scale, 32-10
- Economies of small, NuScale’s, 32-10, 32-10f
 - design simplicity (size reduction and simplification), 32-10–32-11
 - innovative operations, 32-12
 - NSSS factory fabrication, 32-11
 - simplified parallel construction, 32-11–32-12
- ECP. *See* Electrochemical potential
- ECT. *See* Eddy current test
- Eddy current, 21-10, 21-11
- Eddy current test (ECT), 15-30
- EDEAC. *See* EPRI Database on Environmentally-assisted Cracking
- EDG. *See* Emergency Diesel Generator
- Edge-localized mode (ELM) control coils, ITER, 33-8–33-9
- EDMGs. *See* Extensive damage mitigation guidelines
- EDY. *See* Effective Degradation Years
- Effective Degradation Years (EDY), 21-12
- Effective fullpower years (EFPY), 19-16
- Effective gasket-seating width, 9-9
- Effective mass, 6-4

- Effective mass ratio, 6-4
- EFPY. *See* Effective fullpower years
- EFWS. *See* Emergency feedwater system
- EGIG. *See* European Gas Pipeline Incident data Group
- Einstein, Albert, 33-2, 33-13
- EJMA (Expansion Joint Manufacturers Association, Inc.) Standard, 31-2t
- Elastic follow-up in piping, 17-6
- Elastic interaction, 9-35
- Elastic-plastic fracture mechanics (EPFM), 21-14
- Elastic-plastic fracture mechanics (EPFM) analysis, 27-1, 27-3, 27-8
 - structural integrity evaluation procedures, 27-13
- Elbows, *B*-stress indices, 4-13
- Elbows, examples, 4-15–4-17
- Electrical power system, safety-related, 15-26
- Electrical system
 - ITER plant, 33-10–33-11
- Electrical trains, 15-26
- Electric Power Research Institute (EPRI), 4-5, 14-1, 16-18, 19-17, 20-12, 21-1, 25-5, 30-13
 - EPRI TR-102792, 14-4
 - multiple structure piping system tests, 7-12
- Electrochemical potential (ECP), 16-18, 19-3, 19-17, 19-23
- Elevated temperature seismic effects, 17-6
- Elevated temperature service
 - creep fatigue, 17-11
 - environmental effects, 17-11
 - material creep behavior, 17-11
 - simplified design analysis methods, 17-12
 - structural integrity of welds, 17-11–17-12
 - verification testing, 17-12
- Ellipsoidal head rules, of VIII-1, 24-6
- ELMs. *See* Edge-localized mode (ELM) control coils, ITER
- EM. *See* Environmental Management Program
- EM corporate laboratory, 12-2
- Emergency core cooling system (ECCS), 15-26, 16-6, 16-7
- Emergency core cooling system (ECCS), NPM, 32-3, 32-6f–32-7f, 32-7
 - RRVs, 32-7
 - RVV, 32-7
- Emergency Diesel Generator (EDG), 29-5
- Emergency feedwater system (EFWS), 15-16
- Emergency operating procedures (EOPs), 30-3
- Emergency Preparedness (EP) enhancements (NRC Task Force Recommendations 9 through 11), 30-3–30-4
- Emergency Response Data System (ERDS), 30-3, 30-4, 30-7
- Emergency response organization (ERO), 30-4
- Emergency response plans, 11-54–11-55
- Encroachment, remote sensing of, 11-50
- Endurance limit, 3-4
- Energy-absorbing dampeners, 3-7
- Engineered Safety Feature Actuation Systems (ESFAS), 32-8
- Engineered safety features (ESFs), of NuScale Power plants, 32-667
 - DHRS, 32-6, 32-6f
 - ECCS, 32-6f–32-7f, 32-7
 - high pressure CV, 32-5–32-6
 - passive safety systems (elimination of LOCA), 32-6
- Environment. *See also* Primary water stress corrosion cracking
 - hydrogen concentration, 21-6
 - lithium concentration and pH, 21-6
 - temperature, 21-6
- Environmental degradation effects, 17-12
- Environmental fatigue
 - correction factor, 16-19
 - effects of, 19-21
 - rules, 16-19–16-20
 - usage, 16-20
- Environmentally-assisted cracking (EAC), 5-15
- Environmentally assisted fatigue (EAF), 18-8
- Environmental Management Program (EM), 12-1
- Environmental resistance
 - material selection and, 26-3
- Environmental reviews, license renewal process, 18-3
- EOPs. *See* Emergency operating procedures
- EPFM. *See* Elastic-plastic fracture mechanics
- EPFM analysis. *See* Elastic-plastic fracture mechanics analysis
- IE Power System Failsafe concept, 32-8
- Epoxy materials, 26-6
- EPR, 19-23
 - ancillary systems, 15-15–15-16
 - development, 15-12
 - economics, improved, 15-12
 - evolutionary, 15-12
 - fuel handling and storage, 15-16
 - instrumentation & control system, 15-16–15-17
 - layout, 15-12–15-13
 - nuclear steam supply system, 15-13–15-15
 - safety functions, 15-12
 - sustainability, 15-12
- EPRG. *See* European Pipeline Research Group
- EPRI. *See* Electric Power Research Institute
- EPRI Database on Environmentally-assisted Cracking (EDEAC), 5-13
- EPRI/GE methodology, 19-21
- EPRI Report NP-6443, 7-10, 7-15
- EPR layout
 - diesel buildings, 15-13
 - essential service water system cooling structures, 15-13
 - fuel building, 15-12
 - nuclear auxiliary building, 15-13
 - reactor building, 15-12
 - safeguard buildings, 15-12–15-13
 - turbine building, 15-13
 - waste building, 15-13
- EPR safety
 - Fukushima event, 15-19
 - internal/external hazards, 15-17
 - mitigation of severe accidents, 15-18–15-19
 - operator action, increased reliability of, 15-18
 - probability of core melt, reduced, 15-18
 - simplification/redundancy/diversity, 15-17–15-18
- Equipment
 - flexible, 6-4
 - rigid, 6-4
- Equivalency recommendation, 11-20
- Equivalent-axial-force method, 9-31
- Equivalent-pressure method, 9-31
- Equivalent static load, 6-4
- ERDS. *See* Emergency Response Data System
- ERO. *See* Emergency response organization
- Erosion/corrosion, 17-8, 31-4
- ESBWR. *See* Economic simplified boiling water reactor
- ESFAS. *See* Engineered Safety Feature Actuation Systems
- ESFs. *See* Engineered safety features

- Essential service water pipe chase (ESWPC), 15-29
- Essential service water system (ESWS), 15-16
- Essential service water system cooling structures, 15-13
- Essential variables
 - nuclear code case N-755 and, 30-14
- ESWPC. *See* Essential service water pipe chase
- E900 trend curves, 20-12–20-13
- Eulerian multi-phase (EMP) methods, 6-16
 - example
 - distillate charge heater, 6-16–6-17
 - separate steam drum WHB, 6-16
 - use of, 6-16
- European Gas Pipeline Incident data Group (EGIG), 11-3
- European Gas Pipeline Research Group (GERG), 11-50
- European Pipeline Research Group (EPRG), 11-28
- European standard EN 1594, 11-3
- Examination Requirements (Part 7, VIII-2), 24-13
- Expansion joints, 31-2–31-3
 - advantages, 31-2t
 - Caprolactam plant accident (Flixborough, UK), 31-2t
 - disadvantages, 31-2t
 - types, 31-2t
- Experimental Boiling water reactor (EBWR), 16-4
- Extended power uprate (EPU) conditions, 19-6
- Extended power uprate (EPU) operation, BWR steam dryers for,
 - 30-1, 30-15
 - acoustic mitigation device, 30-16
 - acoustic resonance, 30-15–30-16
 - single and double vortex, 30-16
 - analytical methodology related issues, 30-17–30-18
 - bias errors and uncertainties related issues, 30-17
 - fabrication, installation, and quality control, 30-18
 - monitoring, 30-18
 - MSL and dryer instrumentation related issues, 30-17
 - steam dryer margin, 30-16–30-17
- Extensive damage mitigation guidelines (EDMGs), 30-3
- External loads, flange joint and, 9-31
 - bolt-stress limits, 9-31
 - equivalent-axial-force method, 9-31
 - equivalent-pressure method, 9-31
 - finite-element method, 9-31
 - gasket reaction, 9-31
 - recommended approach, 9-31–9-32
 - rules of thumb, 9-31
- Extra boring system (EBS), 15-16
- EXtremely Low Probability of Rupture (xLPR) software package, 21-20

- Fabrication of components, 16-18
- Fabrication Requirements (Part 6, VIII-2), 24-13
- Fabric expansion joints, 31-2t
- FAC. *See* Flow assisted corrosion
- Failure Load Factor, 27-8
- Failure (structural) mode, 17-3
- Failure modes, for SSCs, 7-3
 - piping components, 7-3–7-6
 - pumps, 7-7
 - supports, 7-6
 - valves, 7-7
- FAPCS. *See* Fuel and auxiliary pools cooling system
- Faraday's Law, 19-23
- Farmer, F. R., 29-2
- Farmer, F. R., 29-3

- Fast flux test facility (FFTF), 17-1
- Fast valve closure, 3-10–3-11
- Fatigue, 5-1, 14-1. *See also* Cyclic loading, Code design and evaluation for
 - correction factor, 16-19
 - crack growth rate, 19-5
 - crack growth rate relationships for. *See* Crack growth rate relationships for fatigue
 - crack propagation, 19-4
 - rules, environmental, 16-19–16-20
- Fatigue analysis
 - of bolts, 9-4
 - of Class 1 and Class 2 or 3 piping, 4-11–4-12
 - exemption from, 5-6–5-7
- Fatigue initiation. *See also* Crack growth rate relationships for fatigue
 - actual *versus* design cyclic duty, 19-20–19-21
 - environmental fatigue effects, 19-21
- Fatigue life, defined, 30-9. *See also* Light Water Reactor (LWR)
 - environments, effect on fatigue life of nuclear plant components
- Fatigue monitoring program (FMP), 18-7–18-8
- Fatigue strength reduction factors, 5-2
- FBEs. *See* Fusion-bonded epoxies
- FE codes, computer, 6-11
- FED. *See* Fusion energy devices
- Federal Highway Agency, 11-39
- Federal Register*, 10-1, 10-2, 19-7, 22-11
- Feedwater nozzles, 16-16, 19-8–19-9, 19-11
- Feedwater piping system, 16-19
- Ferritic piping
 - transition temperatures for onset of upper-shelf behavior in, 27-13–27-14
- Ferritic steels, 19-22, 19-24
- FES. *See* Fusion Energy Sciences
- FFTF. *See* Fast flux test facility
- FGD vessels. *See* Flue Gas Desulfurization vessels
- Fiber-reinforced plastic (FRP) flanges, 9-30
- Field installation techniques, 19-17
- Final safety analysis report (FSAR), 18-8
- Finite element analyses, 492
- Finite element calculations, of weld residual stresses, 27-12
- Finite-element method, 9-31
- Finite element model, 14-3, 19-5
- Fire PRA methods, 29-7
- Fire protection licensing
 - NFPA 805 and, 29-5–29-6
 - “First Call” program, 11-49
 - First-of-a-Kind Engineering (FOAKE) program, 16-2
 - Fission product release, 15-7
- Fittings
 - standardization of, 23-1–23-9. *See also* American Society of Mechanical Engineers (ASME) B16 Standard
- FIV. *See* Flow-induced vibration
- Flanged and flued type expansion joints, 31-2t
- Flanged joints, 9-1
 - assembly, 9-34–9-36
 - Codes addressing design of, 9-1
 - design, for external loads, 9-31–9-32
 - flange standards, 9-7
 - future Code requirements, 9-36
 - methods for design of, 9-7–9-30
 - piping, flange design for, 9-5–9-7

- pressure vessels, flange design for, 9-1–9-5
- tightness-based design, 9-32–9-34
- Flange-joint assembly, 9-34–9-36
 - ASME Appendix S, 9-34–9-35
 - bolting and gasket considerations, 9-35–9-36
- Flange moments, 9-12, 9-14
- Flanges
 - lapped, 23-5
 - pressure temperature ratings, 23-6
 - socket welded, 23-5
 - standardization of, 23-1–23-9. *See also* American Society of Mechanical Engineers (ASME) B16 Standard
 - threaded, 23-5
 - types, 23-5
 - welding neck, 23-5
- Flange standards, applicability of, 9-1
- Flange stresses, 9-3, 9-18–9-21
 - integral flanges and loose flanges with hubs, 9-18–9-19
 - loose flanges without hubs, 9-19–9-20
 - for operating moment and gasket-seating moment, 9-20–9-21
 - optional flanges, 9-21
- Flashing, 3-7–3-8
- Flat heads, 9-2
- Flaw embedment, 21-21
- Flaw evaluation method, 20-5
- Flaw removal, 21-21
- Flaw tolerance evaluation, 20-18
- Flexibility factors, 31-5. *See also* Stress indices; Stress intensification factors
 - best estimate flexibility factors, 4-17
 - branch connection, 4-17
 - Code equations, 4-14
 - elbows, 4-15
 - estimate of, 4-17
 - example piping system, 4-14
 - Figure 4.7 (In-Plane Flexibility Factors), 4-9
 - Figure 4.8 (Out-of-Plane Flexibility Factors), 4-10
 - Girth butt welds, 4-14–4-15
 - moments, 4-14
 - piping system analyses and, 4-13–4-14
- Flexible core operation, US-APWR. *See also* US advanced pressurized water reactor
 - CRDM and driveline, 15-25
 - fuel, 15-25
 - incore instrumentation system, 15-25
 - pressurizer, 15-25
 - reactor coolant pumps, 15-25
 - reactor internals, 15-25
 - reactor pressure vessel, 15-25
 - steam generators, 15-25
 - thermocouple instrumentation, 15-25
- Floor acceleration, 6-4
- Floor-response spectra, 6-9–6-10
- Flow accelerated corrosion (FAC), 7-3
- Flow assisted corrosion (FAC), 22-6, 31-4
- Flow coefficient, 8-4
- Flow-Induced Vibration*, 6-14
- Flow-induced vibration (FIV), 6-13–6-14, 19-4, 19-6
 - and steady-state vibrations in piping, 3-1
- Flow stress-dependent assessment, 11-5
- Flow turbulence, vibration from, 3-7
- Flue Gas Desulfurization (FGD) vessels, 26-3
- Fluid-discharge load effects
 - computation of, 6-14
- Fluid disturbances, sources of, 8-3
 - bulk flow and propagative flow modeling in pipes, 8-8–8-10
 - centrifugal pumps, 8-7
 - check valve closure, 8-4, 8-6
 - condensation-induced waterhammer, 8-7
 - Figure 8.4 (Motor- or Manually Operated Valves), 8-4
 - Figure 8.5 (Flow Coefficient: Typical Globe Valve), 8-4
 - Figure 8.6 (Loss Coefficient: Typical Globe Valve), 8-4
 - Figure 8.7 (Cutaway Views: Safety/Relief Valve), 8-5
 - Figure 8.8 (Swing-Check Valve Schematic), 8-6
 - Figure 8.9 (Liquid Column Impact at Area Contraction), 8-6
 - Figure 8.10 (Liquid Column Separation), 8-6
 - Figure 8.11 (Condensation-Induced Waterhammer), 8-7
 - Figure 8.12 (Positive-Displacement Pump Schematic), 8-7
 - Figure 8.13 (Gas Cushion), 8-8
 - Figure 8.14 (Vortex-Shedding Frequency), 8-9
 - Figure 8.15 (Fluid Region: Bulk or Propagative Flow), 8-10
 - gas cushion, 8-8
 - liquid column impact, 8-6
 - liquid column separation, 8-6
 - motor- or manually operated valves (MOVs), 8-3–8-4
 - pipe movement, 8-7
 - pipe rupture, 8-6
 - positive displacement pumps, 8-7–8-8
 - safety/relief valves, 8-4
 - vortex shedding, 8-8
- Fluid forces, 8-1
 - buoyant force, 8-1
 - estimation of, 8-10
 - external flow systems and, 8-1
 - Figure 8.1 (Geometry of Submerged Flat Surface), 8-2
 - Figure 8.2 (Horizontal Force on Curved Surface), 8-2
 - Figure 8.3 (Vertical Force on Curved Surface), 8-2
 - fluid disturbances and, 8-1, 8-3–8-10. *See also* Fluid disturbances, sources of
 - fluid motion and, 8-1–8-3
 - hydrostatic forces, 8-1–8-2
 - internal flow systems and, 8-1
 - pressure and shear forces, 8-2–8-3
 - pressure forces, 8-1
 - stationary fluid and, 8-1
 - on submerged structures, 8-10–8-11
- Fluidhammer, 6-2, 6-14
 - in biphasic systems, 6-14
 - and design considerations, 6-14–6-15
 - hydraulic shock and, 6-14
 - thermal shock and, 6-14
- Fluid jets, 6-17
- Fluid-structure interaction (FSI), 8-11–8-12, 8-15
 - acoustic disturbances, 8-13–8-14
 - cavitation, 8-15
 - incompressible, non-acoustic flows, 8-14
 - normalized variables, 8-13
 - ratios of time scales, 8-14–8-15
 - scale-modeling fluid-structure-interaction, analysis for, 8-12–8-13
 - structural response, 8-14
- Fluor, 32-2
- FMP. *See* Fatigue monitoring program
- Folias factor, 11-27, 11-29
- Force transducers, 3-19

- Forcing functions, 6-18
 - hard missile impact, 6-18–6-19
 - soft missile impact, 6-19
 - typical missile, 6-19
- Form drag, 8-1
- Foundation, 6-4
- Fourier spectrum, 6-4
- Fracture mechanics, 19-9, 19-13
- Fracture toughness, 20-10–20-11
- Fracture toughness-dependent assessment, 11-5
- Fragility, 6-4
- Fragility level, 6-4
- Fragility response spectrum, 6-4
- Freeze plugging, 11-36
- French CEA-EDF formulation, 6-18
- Friction connections, 14-3
- FSAR. *See* Final safety analysis report
- FSI. *See* Fluid-structure interaction
- Fuel, 15-4, 15-25
 - assembly, 15-23, 15-24
 - handling and storage, 15-16
- Fuel and auxiliary pools cooling system (FAPCS), 16-13
- Fuel and core design
 - Westinghouse SMR, 32-18–32-19, 32-18f, 32-19f
- Fuel building, 15-12
- Fuel cladding, 15-7
- Fuel cycle systems, ITER, 33-9–33-10, 33-10f
- Fuel economy, US-APWR, 15-24
- Fukushima accident
 - insights from PRAs applications, 29-6–29-7
 - seismic PRA and, 29-7
- Fukushima Daiichi accident, 30-1–30-7
 - NTTF's recommendations and orders, 30-5, 30-6
 - 10 CFR 50.63, 30-2, 30-6
 - 10 CFR 50.54(f), 30-1
 - 10 CFR 50.54(f) letter, 30-5, 30-6
 - 10 CFR 50.54(hh)(2), 30-2–30-3, 30-6
 - effectiveness of hardened vents (Recommendation 5), 30-3
 - Emergency Preparedness (EP) enhancements
 - (Recommendations 9 through 11), 30-3–30-4
 - Ensuring Protection (Recommendations 2 and 3), 30-2
 - Mitigation Enhancement (Recommendations 4 through 8), 30-2–30-3
 - NRC Programs Efficiency Improvement (Recommendation 12), 30-4
 - NUREG-0737, 30-3
 - NUREG-1560 (Individual Plant Examination Program: Perspectives on Reactor Safety and Plant Performance), 30-2
 - NUREG-1742 (Perspectives Gained from the Individual Plant Examination of External Events [IPEEE] Program), 30-2
 - NUREG-1860, 30-2
 - onsite emergency response capabilities enhancement
 - (Recommendation 8), 30-3
 - Order EA-12-049, 30-5
 - Order EA-12-051, 30-5
 - Order EA-13-109, 30-5, 30-6
 - Recommendation 2.1, 30-5
 - Recommendation 2.3, 30-5
 - recommended rulemaking activities, 30-4–30-6
 - Regulatory Analysis Guidelines modification, 30-2
 - Regulatory Framework Clarification (Recommendation 1), 30-2
 - spent fuel pool makeup capability and instrumentation enhancement (Recommendation 7), 30-3
 - “Station Blackout Mitigation Strategies Rulemaking” (Recommendation 4), 30-2–30-3
- Fukushima Daiich plant accident (Japan), 32-1, 32-7
- Fukushima event, 15-19
- Full digital I&C, 15-27
- Full-face gaskets, flange design for, 9-29–9-30
- Full qualification, 7-17
- Full-scale tests, 17-4
- Furan, 26-6
- Fusion
 - deuterium–tritium fusion reaction, 33-3–33-4, 33-3f
 - ITER. *See* International Thermonuclear Experimental Reactor
 - light elements, 33-1–33-2, 33-2f
 - characteristics, 33-3t
 - nuclear. *See* Nuclear fusion
 - Oliphant theory, 33-3
 - overview, 33-1
 - proton–proton reaction (PPI), 33-2–33-3, 33-2f
 - terrestrial power production theories, 33-4
 - terrestrial-scale, 33-2–33-4
- Fusion-bonded epoxies (FBEs), 11-42
- Fusion energy devices (FED), 33-14
- Fusion Energy Sciences (FES), 33-13–33-14
 - goals, 33-13
 - website, 33-13
- Gadolinia, 15-25
- GALL Report. *See* Generic aging lessons learned Report
- Garrick, B. John, 29-2
- Gas blows, piping failure and, 31-3–31-4
- Gas cushion, 8-8
- Gasket constants, 9-32
- Gasket-load reaction, 9-9
- Gasket reaction, 9-31
- Gaskets, 9-7
 - standardization of, 23-1–23-9
- Gaskets and Gasketed Joints*, 9-29, 9-30
- Gas leak detection, 11-49–11-50
- Gas Research Institute (GRI), 11-27
- Gas tungsten arc welding (GTAW), 19-18, 19-19, 21-3
- Gas turbine generator (GTG), 15-26
- Gas turbine-modular helium reactor (GT-MHR), 17-8, 17-9
- GDC. *See* General design criteria
- GDCS. *See* Gravity-driven core cooling system
- GE BWR, 16-2, 16-4, 16-5
- GEIS. *See* Generic Environmental Impact Statement
- General design criteria (GDC), 15-28
 - nuclear plant PRAs and, 29-3
- General Requirements (Part 1, VIII-2), 24-12
- Generational reactors, 15-2
- Generation III+ PWR
 - AP1000 plant, future work, 15-10
 - AP1000 plant design, 15-2
 - ASME Code aspects, 15-10
 - code aspects, 15-20
 - construction, 15-19–15-20
 - containment design, 15-7–15-8, 15-19
 - CRDM and driveline, 15-3
 - EPR, overview of, 15-12
 - EPR development, 15-12

- EPR safety, 15-17–15-19
- Figure 15.1 (Generational Reactors), 15-2
- Figure 15A.1 (AP1000 PWR Reactor Coolant Systems), 15-3
- Figure 15A.2 (CMTs and Accumulator Piping System), 15-4
- Figure 15A.3 (AP1000 Plant Passive Residual Heat Removal System), 15-4
- Figure 15A.4 (AP1000 Plant Automatic Depressurization Systems), 15-5
- Figure 15A.5 (AP1000 Plant Passive Containment Cooling System), 15-6
- Figure 15A.7 (Comparison of Nuclear Island), 15-7
- Figure 15A.8 (AP1000 Plant), 15-8
- Figure 15A.9 (Illustration of AP1000 Plant Building Modularization), 15-9
- Figure 16A.6 (AP1000 Plant In-Vessel Retention of Core Damage), 15-7
- Figure 15B.1 (Layout of EPR Power Block), 15-12
- Figure 15B.2 (US-EPR Nuclear Steam Supply), 15-13
- Figure 15B.3 (Steam Generator), 15-14
- Figure 15B.4 (Quadruple Redundancy with Physical Separation of Divisions), 15-17
- Figure 15B.5 (General Arrangement of RV, IRWST, Reactor Pit, and Corium Retention), 15-19
- Figure 15B.6 (Construction of OLKILUOTO3), 15-20
- fuel, 15-4
- in-core instrumentation, 15-4
- modularization and construction, 15-9
- operational technology, 15-3–15-4
- operation and maintenance, 15-9–15-10, 15-20
- plant design, 15-12–15-17
- pressurizer, 15-4
- pumps, 15-4
- reactor internals, 15-3
- reactor pressure vessel, 15-3
- safety features, 15-4–15-7
- scope of commentary, 15-1
- steam generators, 15-3
- Table 15A.1 (AP1000 Plant Component Comparison with Operating 1000-MWe Plant), 15-2
- Table 15A.2 (AP1000 PWR Operational Technology), 15-3
- Table 15A.4 (Illustration of AP1000 Plant Building Modules), 15-9
- Table 15A.6 (AP1000 Plant Stress Criteria for ASME Code Section III Class 1, Core Support Structures and Component Supports), 15-10
- Table 15B.1 (NSSS Characteristics), 15-13
- Table 15B.2 (EPR Probabilistic Risk Assessment), 15-18
- thermocouple instrumentation, 15-4
- Generic aging lessons learned (GALL) Report, 18-9, 19-21
- Generic Environmental Impact Statement (GEIS), 18-3
- Generic Letter 81-11, NRC, 19-9
- Generic Letter 88-20
- issuance by US NRC, 29-3
- Generic table of contents (ASME B16 Standard), 23-3, 23-3t–23-4t
- Geographic information systems (GIS), 11-9
- Geometric damping, 6-11. *See also* Damping
- Geometric non-linearities, 14-2
- Geometry of piping system, 14-3
- GERG. *See* European Gas Pipeline Research Group
- GIS. *See* Geographic information systems
- GI 199 safety/risk assessment, 14-2
- Glass, 26-6
- Globalization, of ASME Boiler and Pressure Vessel Code, 1-19–1-25
- Figure 1.2 (United States: ASME Companies Holding B&PV Certificates), 1-20
- Figure 1.3 (Canada: ASME Companies Holding B&PV Certificates), 1-21
- Figure 1.4 (North America: ASME Companies Holding B&PV Certificates), 1-21
- Figure 1.5 (South America: ASME Companies Holding B&PV Certificates), 1-22
- Figure 1.6 (Europe: ASME Companies Holding B&PV Certificates), 1-22
- Figure 1.7 (Middle East: ASME Companies Holding B&PV Certificates), 1-23
- Figure 1.8 (Eastern Asia: ASME Companies Holding B&PV Certificates), 1-23
- Figure 1.9 (Africa: ASME Companies Holding B&PV Certificates), 1-24
- Figure 1.10 (Australia: ASME Companies Holding B&PV Certificates), 1-24
- Figure 1.11 (Summary of International Nuclear Companies and Certificates), 1-25
- Figure 1.12 (Distribution of Certificate Holders and Certificates by Regions), 1-26–1-27
- Figure 1.13 (Number of Code Symbol Stamps), 1-28
- Figure 1.14 (Certificate Holders Summary Count Listing for USA by Certificate Type, Boiler), 1-29
- Figure 1.15 (Certificate Holders Summary Count Listing for Canada by Certificate Type, Boiler), 1-30
- Figure 1.16 (Certificate Holders Summary Count Listing for International Countries by Certificate Type, Boiler), 1-31
- Figure 1.17 (Certificate Holders Summary Count Listing for USA by Certificate Type, Nuclear), 1-32
- Figure 1.18 (Certificate Holders Summary Count Listing for Canada by Certificate Type, Nuclear), 1-33
- Figure 1.19 (Certificate Holders Summary Count Listing for International Countries by Certificate Type, Nuclear), 1-34
- Figure 1.20 (Countries Accepting ASME Code), 1-35
- Goodman diagram, modified, 5-2–5-3
- Gouges, 11-27–11-28
- Grade 22 alloys, 26-1–26-2
- Graded quality assurance (QA), PRAs and, 29-6, 29-7
- “Grandfathering,” concept of, 28-4
- Grandfathering Clause, 10-13
- Grantom, C. Rick, 22-1
- Graphite materials, 26-6
- components, 26-8
- fabrication process, 26-11
- joining process, 26-9, 26-10f
- properties, 26-6
- Gravity-driven core cooling system (GDCCS), 16-3, 16-10–16-12. *See also* Passive safety features, BWR
- Green’s function, 18-8
- Greyloc style flange, 9-2
- GRI. *See* Gas Research Institute
- Ground acceleration, 6-4
- Ground Motions Response Spectra (GMRS), 30-5
- Ground-response spectra, 6-8–6-9
- Figure 6.2 (Generic Earthquake-Response Spectral Shape), 6-9
- Table 6.1 (Generic Earthquake Ground-Response Horizontal Component-Amplification Factor), 6-8
- Table 6.2 (Appendix N Horizontal Response Spectra Values), 6-9
- GTAW. *See* Gas tungsten arc welding
- GTCC Waste. *See* Greater-Than-Class C Waste

- GTG. *See* Gas turbine generator
- GT-MHR. *See* Gas turbine-modular helium reactor
- Guidance Documents*, 10-1
- Guidance for Screening and Prioritization Implementation Details (SPID), 30-5
- Haystack curves, 3-25
- HAZ. *See* Heat affected zone
- Hazard assessment, pipeline, 11-273
- Hazards, internal/external, 15-17
- Head replacement, RPV top-head cracking, 21-26
- Heald's tests, 4-3
- Heat affected zone (HAZ), 17-4, 17-11, 17-12, 19-1–19-2
- Heat exchangers, operability evaluation, 7-13
- Heating, ventilation, and air-conditioning (HVAC) system, 15-7, 15-13
- Heating system, ITER, 33-9, 33-9t
- Heat recovery steam generation (HRSG) boilers, 28-6
- Heat rejection system (HRS), 33-10
- Heat removal, 16-7, 16-10
- Heat-sink welding (HSW), 19-17
- Heat transfer, 16-13
- Heat transfer efficiency, 15-15
- Heaviside step function, 8-21
- Helium, 17-9, 17-10, 33-2
- Helium-3, 33-2, 33-3
- Helium-4, 33-2
formation, 33-2, 33-2f, 33-3
- Helium coolant, 17-9
- Helium-cooled reactor system, 17-10
- HHIS. *See* High-head injection system
- High-cycle fatigue and low-cycle fatigue, difference between, 5-1
- High density polyethylene (HDPE), 30-1
for carbon steel piping replacement in safety related class 3 buried piping, 30-11–30-15
advantages, 30-12
lessons learned and special design considerations, 30-12
material, fabrication, and examination related issues, 30-14–30-15
overview, 30-11–30-12
structural related issues, 30-13–30-14
thermal gradient stress, 30-12–30-13
values of properties, 30-12t
- High-energy corium/water interaction, prevention of, 15-18
- High-energy piping system, 6-4
- High-frequency vibration, piping failure and, 31-5
- High-head injection system (HHIS), 15-26
- High-level requirements (HLRs), PRAs and, 22-6
- High pressure containment vessel, NPM, 32-5–32-6
- High-pressure coolant injection (HPCI), 16-6, 16-7
- High-pressure core melt, prevention of, 15-18
- High-pressure core spray (HPCS) system, 16-7
- High pressure (HP) turbine, 15-23
- High safety significant (HSS) components, 22-2
- High-temperature gas-cooled reactors (HTGR)
Codes and Procedures for, 17-2, 17-8–17-9
material behavior, NUREG/CR-6824, July 2003, 17-9–17-10
NUREG/CR-6816, June 2003, 17-8–17-9
- Hindu-Arabic numbering system, 29-1
- Hinnant curve, 4-11
- Hinnant equation, 4-3
- Homeland Security Act of 2002, Section 403 of, 11-54
- Hoop membrane stress, 4-11
- Hot tap/stopple bypassing, 11-36
- Housner spectrum, 6-8
- HPCI. *See* High-pressure coolant injection
- HPCS. *See* High-pressure core spray
- HRS. *See* Heat rejection system
- HRSG boilers. *See* Heat recovery steam generation boilers
- HSW. *See* Heat-sink welding
- HTGR. *See* High-temperature gas-cooled reactors
- Huff, J. E., 28-3
- HWC. *See* Hydrogen water chemistry; Water Chemistry Improvement
- Hydraulic shock, 6-14
- Hydrogen, 19-19, 33-1, 33-13
ignition system, 15-27
- Hydrogen-1, 33-1, 33-2
- Hydrogen concentration, 21-6
adjustments of, 21-24
- Hydrogen flaking, 30-19
countermeasures for, 30-19
factors influencing steel's sensitivity to, 30-19
- Hydrogen fusion, 33-1. *See also* Fusion
overview, 33-1–33-2, 33-2f
principles, 33-1
- Hydrogen water chemistry (HWC), 16-18, 19-3, 19-17
- Hydrostatic testing, pipelines, 11-16–11-18
- IASCC. *See* Irradiation-assisted stress-corrosion cracking
- ICC. *See* Interstate Commerce Commission
- ICS. *See* Isolation condenser system
- Idaho National Engineering and Environmental Laboratory (INEEL), 17-2
- IDCOR program. *See* Industry Degraded Core Rulemaking program
- I*-factors. *See* Stress intensification factors
- Igniters, 15-27, 15-28
- IGSCC. *See* Inner granular stress corrosion cracking; Intergranular stress corrosion cracking
- IHSI. *See* Induction heating stress improvement
- IHX. *See* Intermediate heat exchanger
- IMP. *See* Integrity Management Program
- Impact damping, 6-11. *See also* Damping
- Impact loads, 6-2
equations of motion, 6-7–6-8
- Imposition of Code repair, 19-13
- Impulse loads, 6-2–6-3. *See also* Relief-valve discharge loads
equations of motion, 6-7
- Incipient cavitation, 3-8
- Inconel 600, 21-2
- Inconel Alloy 600, 20-18
- In-containment refueling water storage pit, 15-27
- In-containment refueling water storage tank (IRWST), 15-4, 15-8, 15-15, 15-16
- In-core instrumentation, 15-4, 15-13, 15-14, 15-25
- Independent safety trains
electrical trains, 15-26
mechanical trains, 15-26
- Independent support motion, 14-3
- Independent Technical Review Group (ITRG), 17-2
- Individual plant examination of external events (IPEEE), 18-5, 30-2
- Induction heating stress improvement (IHSI), 19-17, 21-25, 25-2
- Industry Degraded Core Rulemaking (IDCOR) program, 22-2

- INEEL. *See* Idaho National Engineering and Environmental Laboratory INEEL/Ext-04-01816, June 30, 2004, 17-10
- Inelastic analysis, material property representation for, 17-5
- INGAA. *See* Interstate Natural Gas Association
- In-line inspection, pipelines, 11-18–11-20
- Inner granular stress corrosion cracking (IGSCC), 22-6
- INPO. *See* Institute of Nuclear Power Plant Operations
- In-service inspection (ISI), 1-7, 15-30, 19-4, 20-18, 22-2, 29-5. *See also* Section XI (in-service inspection)
- In-service testing (IST), 22-2
- Inside diameter (ID), 19-7
- Inspection methods, PWSCC cracks and leaks
 - ASME BPVC reactor vessel inspection requirements, 21-10–21-11
 - augmented inspection requirements for alloy 82/182 dissimilar metal butt welds in PWR primary, 21-12–21-13
 - augmented inspection requirements for RPV BMI nozzles, 21-12
 - augmented inspection requirements for RPV top-head nozzles, 21-11–21-12
 - visual inspections, 21-10
- Inspection uncertainty, shroud, 19-3
- Institute of Nuclear Plant Operations' (INPO) NPRDS database, 7-6
- Institute of Nuclear Power Plant Operations (INPO), 3-2
- In-structure response spectra (ISRS), 15-29
- Instrumentation and control (I&C) system, 15-16
 - design philosophy, 15-17
 - EPR I & C architecture, 15-17
- Integral flanges, 9-15–9-16
- Integral pressurized water reactor (iPWR) design, 32-13
 - Westinghouse SMR nuclear island, 32-15, 32-16f
 - coolant pumps, 32-16, 32-16f
 - CRDMs, 32-16, 32-17f
 - pressurizer, 32-15
 - reactor internals, 32-16, 32-16f
 - steam generator, 32-15
- Integral welded attachments, 7-15
- Integrated plan assessment (IPA), 18-2–18-3, 18-4
- Integrity Management Program (IMP), pipeline, 11-5
 - current status and lessons learned, 11-11
 - definition of, 11-5
 - development of, 11-10–11-11
 - program overview, 11-11
 - roles and responsibilities, 11-11
 - support processes, 11-11
 - table of contents, 11-11
 - elements of, 11-8–11-9
 - consequence assessment, 11-9
 - data gathering and integration, 11-9–11-10
 - evaluation, 11-10
 - mitigation, 11-10
 - prevention and monitoring, 11-10
 - risk assessment, 11-9
 - threat/hazard assessment, 11-9
 - regulatory compliance, 11-10
 - regulatory requirements, 11-6–11-7
 - related standards, 11-7–11-8
- Intelligent/smart pig tool, 11-18
- Intensity, 6-4
- Interface, seismic/non-seismic, 14-6
- Interface anchor, 14-6
- Intergranular stress corrosion cracking (IGSCC), 16-17, 16-18, 19-1, 19-16, 19-17, 25-2, 25-5, 27-2, 27-4
 - crack growth rate, 27-11
- Interim Letter, 1-16. *See also* Nuclear certification programs
- Interim staff guidance (ISG), 18-8
- Intermediate heat exchanger (IHX), 17-4
- Intermediate piping transition weld, 17-7
- Internal coils, ITER, 33-8–33-9
- Internal corrosion direct assessment (ICDA), 11-26
- Internal steam separator, 16-1
- International activities, license renewal programs, 18-10
- International Atomic Energy Agency (IAEA), 10-1, 10-6–10-9
- International Building Code, 6-8, 6-9
- International Cooperative Group for Environmentally-assisted Cracking (ICG-EAC), 5-13
- International Cooperative Group on Cyclic Crack Growth Rates (ICCGR), 5-13
- International Nickel Corporation (INCO), 21-1
- International Thermonuclear Experimental Reactor (ITER), 1-30, 1-32–1-33. *See also* Fusion
 - background, 33-5
 - design, 33-5
 - ancillary systems, 33-9
 - assembly and maintenance, 33-11, 33-11f
 - blanket system, 33-8, 33-8f
 - cooling water system, 33-10
 - cryogenic system, 33-10
 - cryostat, 33-9
 - current drive system, 33-9, 33-9t
 - diagnostics, 33-9
 - divertor, 33-8, 33-9f
 - electrical system and power supplies, 33-10–33-11
 - fuel cycle systems, 33-9–33-10, 33-10f
 - heating system, 33-9, 33-9t
 - internal coils, 33-8–33-9
 - magnet system, 33-5–33-7
 - thermal shield, 33-9
 - Tokamak, 33-5, 33-5f, 33-6f
 - vacuum vessel, 33-7–33-8, 33-8f
 - tritiation systems in, 33-12
 - licensing, 33-11–33-12
 - parameters, 33-6t
 - safety considerations, 33-11–33-12
 - Tokamak Building, 33-5, 33-6f
- Interpretations, publication of, 1-5
- Interstate Commerce Commission (ICC), 10-5, 10-6
- Interstate Natural Gas Association (INGAA), 11-54
- In-vessel retention of core damage, 15-7
- IPA. *See* Integrated plan assessment
- IPWR design. *See* Integral pressurized water reactor design
- Iron-56, 33-2
- Irradiated stainless steel fracture toughness, 19-3
- Irradiation, 19-1, 20-8
- Irradiation-assisted stress-corrosion cracking (IASCC), 19-1, 20-17
- Irradiation embrittlement, 16-17, 20-17
- IRWSTR. *See* In-containment refueling water storage tank
- ISG. *See* Interim staff guidance
- ISI. *See* In-service inspection
- Isolation condenser system (ICS), 16-14–16-15. *See also* Passive safety features, BWR
- ISRS. *See* In-structure response spectra
- IST. *See* In-service testing
- ISTB of the O&M Code, 7-10
- ISTC of the O&M Code, 7-9

- ITER. *See* International Thermonuclear Experimental Reactor
 IWB-3514 of Section XI (ASME B&PV Code), 27-3
- Japan Maintenance Standard, 19-22
- Jet pumps, 16-5, 16-7, 19-4–19-6
- J-groove weld, 21-3
 of PWR vessel heads, cracks in, 25-2–25-3, 25-3f
- J-Integral elastic-plastic fracture mechanics, 5-15
- Joukowski equation, 8-6
- Jurisdictional requirements
 and ASME codes (pressure relief devices), 28-5
- KAPA sheet, 11-31
- Kettle type boilers, 6-15
- K_{IC} versus K_{IR} reference toughness. *See also* Reference toughness
 curves
 flaw size, 20-9–20-10
 fracture toughness, 20-10
 local brittle zones, 20-10–20-11
 margin, 20-9
 overall plant safety, 20-11
 technically correct use of K_{IC} , 20-9
- Kinematic viscosity, 8-13
- K_{IR} index, 20-2
- Kleen Energy Combined Cycle Plant incidents (Middletown
 Connecticut), 31-3
- Lagrangian CFD methods, 6-15
- Lapped flanges, 23-5
- LAR. *See* License amendment request
- Large-bore piping vibration, 3-2
- Large break loss-of-coolant accidents (LBLOCAs), 32-6
 elimination of, 32-6
- Large early release frequency (LERF) criteria, 19-8
- ‘Large quantity’ of licensed material, 10-3
- Larson-Miller Parameter analysis, 26-2
- Last-pass heat sink welding (LPHSW), 19-17
- LBLOCAs. *See* Large break loss-of-coolant accidents
- LCO. *See* Limiting Condition for Operation
- Leakage monitoring systems, 19-9
- Leakage tests, 16-13
- Leak-before-break (LBB) assessment, 21-20
- Leaks
 risk assessment, 21-26
 small, 21-13
- Leak-testing criteria, in ISTC-3600, 7-9
- Leak-tight integrity, 6-4
- LEFM analysis. *See* Linear elastic fracture mechanics analysis
- LER. *See* Licensee event reports
- LERs. *See* Licensee Event Reports
- Level control, 16-13
- LFRD. *See* Load factor and resistance design
- LHSI. *See* Low-head safety injection system
- License amendment request (LAR), 29-5
- Licensee event reports (LER), 3-2, 7-3, 18-2
- License renewal and aging management
 aging management programs (AMP), 18-6
 aging management review (AMR), 18-5
 environmental reviews, 18-3
 final safety analysis report (FSAR) supplement, 18-8
 GALL report, 18-9
 guidance documents, 18-8–18-10
 historical background, 18-1–18-2
 integrated plan assessment, 18-2–18-3
 interim staff guidance (ISG) process, 18-8
 international activities, 18-10
 issues of interest, 18-8
 license renewal applications (LRA), 18-4–18-6
 license renewal guidance documents updates, 18-9–18-10
 overview, 18-1
 principles and process, 18-2
 regulatory guide, 18-9
 safety reviews, 18-2–18-3
 scoping and screening methodology, 18-4
 standard review plan for license renewal (SRP-LR), 18-8–18-9
 Table 18.1 (Consistent with GALL Report Classification), 18-6
 Table 18.2 (Elements of an Aging Management Program), 18-7
 time-limited aging analyses (TLAA), 18-3, 18-6–18-8
- License renewal applications (LRA)
 aging management programs (AMP), 18-6
 aging management review (AMR), 18-5
 AMP/AMR audits, 18-6
 Appendix A, 18-4
 Appendix B, 18-4
 long-lived SC, 18-4
 passive SC, 18-4
 review process, 18-5
 scoping, 18-4, 18-5
 screening, 18-4, 18-5
 Section 4.0, 18-4
 Section 2.0 of, 18-4
 Section 3.0 of, 18-4
- License renewal guidance (LRG) documents
 GALL report, 18-9
 license renewal guidance documents updates, 18-9–18-10
 regulatory guide, 18-9
 standard review plan for license renewal (SRP-LR), 18-8–18-9
 updates, 18-9–18-10
- License renewal process
 PRAs and, 29-6
- Licensing
 ITER, 33-11–33-12
 Westinghouse SMR, 32-21
- LIDAR. *See* Light Detection and Ranging
- Light Detection and Ranging (LIDAR), 11-50
- Light elements fusion, 33-1–33-2, 33-2f
 characteristics, 33-3t
- Light water reactor (LWR), 16-1, 17-1, 18-6, 19-21
 safety, 29-3
- Light water reactor (LWR) environments
 effect on fatigue life of nuclear plant components, 30-1, 30-7–
 30-11
 fatigue considerations, 30-8–30-9
 fatigue lives of austenitic SSs, 30-10
 fatigue strain vs. life (ϵ - N) behavior in air, 30-9
 F_{en} for carbon and low-alloy steels, 30-10
 F_{en} for Ni-Cr-Fe alloys, 30-10–30-11
 NREG-6909, 30-7, 30-8, 30-9
 NUREG/CR-6909, 30-8, 30-9
 overview, 30-7–30-8
- Lightwater reactor (LWR) piping system, problems with, 3-2
- Limiting Condition for Operation (LCO), 7-2
- Linear elastic fracture mechanics (LEFM) analysis, 27-1, 27-8
- Linear-type supports, 7-15

- Linear-variable differential transformer (LVDT), 3-17–3-18
- Liquid capacity certification, 28-2
- Liquid column impact, 8-6
- Liquid column separation, 8-6
- Liquid flow dynamics, in pipe flow system, 8-12
- Liquid metal fast breeder reactor (LMFBR), 17-1
- “Listening ball,” for leak detection in pipelines, 11-49
- Lithium concentrations and pH, 21-6, 21-24
- LMFBR. *See* Liquid metal fast breeder reactor
- Load factor and resistance design (LFRD), 24-4
methodology, 11-31
- Loading conditions, 17-5
- LOCA. *See* Loss of coolant accident
- Local brittle zones, 20-10–20-11
- Longitudinal pipe bracing, 14-3
- Longitudinal primary membrane stress, 27-7
- Long-lived structures and components, 18-4
- LOOP. *See* Loss Of Offsite Power
- Loose flanges, 9-16
- Lorenz force, 11-19
- Loss-of-coolant accident (LOCA), 7-8, 15-6, 15-26, 15-27, 16-5–16-6, 16-9, 22-1
defined, 16-5
defined in GDC, 29-3
- Loss Of Offsite Power (LOOP), 15-26
- Low-alloy steels, 16-19
 F_{en} for, 30-10
- Low- and high-tuning, for reducing vibrational response, 3-13–3-14
- Low-cycle fatigue, 6-4
- Low-frequency vibration, piping failure and, 31-5
- Low-head safety injection system (LHSI), 15-15, 15-26
- Low potential stress corrosion cracking (LPSCC), 21-3
- Low pressure coolant injection (LPCI), 16-7
- Low pressure (LP) turbines, 15-22, 15-23
- Low safety significant (LSS) components, 22-2
- Low Temperature Operation (UCS-66), VIII-1, 24-6–24-7
- Low-temperature overpressure protection (LTOP), 19-8
setpoints, 20-7–20-8
- Low upper shelf energy evaluation
background, 19-15
generic BWR evaluation, 19-15–19-16
- LPCI. *See* Low pressure coolant injection
- LPHSW. *See* Last-pass heat sink welding
- LRA. *See* License renewal applications
- LRG documents. *See* License renewal guidance documents
- LTOP. *See* Low-temperature overpressure
- LVDT. *See* Linear-variable differential transformer
- LWR. *See* Light water reactor
- Mach number, 3-8
- Magnet system, ITER, 33-5–33-7
central solenoid, 33-5, 33-7, 33-7f
correction coils, 33-7
poloidal field (PF) coils, 33-5, 33-7, 33-7f
toroidal field (TF) coils, 33-5–33-7, 33-7f
- Magnitude, 6-4
- Main control room (MCR), 15-24
- Main control room emergency habitability system, 15-6, 15-27
- Main coolant lines, 15-15
- Maintenance
ITER plant, 33-11
- Maintenance-preventable functional failure (MPFF), 2-2, 2-9. *See also* Maintenance Rule
- Maintenance Rule, 2-1, 29-3
applicability of, 2-2
clause a(4), 29-4
development of, 2-1
documentation for, 2-13
Maintenance Rule scoping, 2-13
paragraph (a)(1) activities, 2-13
paragraph (a)(2) activities, 2-13
periodic assessment, 2-13
SSC section process, 2-13
general requirements, 2-4
MPFF failure, 2-9
- Nuclear Regulatory Commission (NRC) and, 2-1
- periodic assessments
availability and reliability for SSCs, optimization of, 2-12–2-13
10CFR50.65(a)(3), 2-12
corrective actions, effectiveness of, 2-12
goals under paragraph (a)(1), 2-12
SSC performance under paragraph (a)(2), 2-12
- responsibility in, 2-2
- risk and performance criteria, establishment of, 2-5
CFR50.65(a)(1), 2-5
goal setting and monitoring, 2-7–2-9
guidance, 2-5–2-6
performance criteria for SSCs, 2-6–2-7
- SSCs in programmed maintenance (PM) program, 2-9–2-10
- SSCs selection, method of, 2-4
10CFR50.65, 2-4
guidance for selection of SSCs, 2-4–2-5
non-safety-related SSCs, 2-5
safety-related SSCs, 2-4–2-5
SSCs outside scope of Maintenance Rule, 2-5
- structures, systems, and components (SSCs) within scope of, 2-1–2-2
- systems removal from service, evaluation of, 2-10–2-12
- terminology related to, 2-2
availability, 2-2
availability or reliability calculation, 2-3
cut sets, 2-2
function, 2-2
industrywide operating experience, 2-2
initial MPFF, 2-2
maintenance, 2-2
operating system, 2-3
performance, 2-3
performance monitoring, 2-3
programmed maintenance, 2-2
reliability, 2-3
repetitive MPFF, 2-2
risk, 2-3
risk-significant SSCs, 2-3
standby system or train, 2-3
system, 2-3
train, 2-3
unplanned automatic scrams, 2-3
unplanned capability loss factor, 2-3–2-4
unplanned safety system actuations, 2-4
use of existing standards and programs, 2-4
“Making Hard Decisions,” 29-2
- Mandatory Appendices, 1-5

- Manufacturer's Design Report (MDR), 24-12
- Manufacturers Standardization Society (MSS), 23-1, 23-9
- MAOP. *See* Maximum allowable operating pressure
- Margin in P-T operating limit curves, 20-13–20-14
- Mark I containment, 16-8
- Mark II containment, 16-8
- Mark III containment, 16-8, 16-9
- Massachusetts Boiler Law, 28-2
- Master curve, 20-2, 20-11
- application of, 20-12
 - reference toughness, 20-11–20-12
 - technique, defined, 20-12
- MAT. *See* Minimum allowable temperature
- Material creep behavior, 17-11, 17-12
- Material damping, 6-11. *See also* Damping
- Material engineering research needs for advanced reactors, 17-8
- Material identification/verification, piping failure and, 31-4
- Material non-linearities, 14-2
- Material property representation for inelastic analysis, 17-5
- Material Reliability Program (MRP), 20-15, 20-18
- Material Requirements (Part 3, VIII-2), 24-12
- Materials (industry experiences), 26-1–26-4
- “advanced” alloys, 26-2
 - ASME B&PV Code, 26-1–26-4
 - chemistry issues, 26-2
 - creep data analysis, 26-2
 - CSEF alloys, 26-1–26-2
 - environmental resistance and, 26-3
 - Grade 22 alloys, 26-1–26-2
 - Larson-Miller Parameter analysis, 26-2
 - overview, 26-1
 - physical properties and, 26-3–26-4
 - post-fabrication cleanup and, 26-3
 - Requirements for Acceptance of New Materials in B&PV Code, 26-2–26-3
- Materials and design bases in ASME Code Case N-47, NUREG/CR-5955, 17-7
- Materials degradation matrix (MDM), 21-1
- Material Specifications, 1-14
- Materials procurement, 1-13–1-14
- Materials Reliability Program (MRP), 21-1, 21-25
- Materials selection. *See also* Boiling water reactor
- austenitic stainless steel materials for internals/components, 16-17–16-18
 - component fabrication and design considerations, 16-18
 - nickel base alloys for ABWR/ESBWR application, 16-18
 - and water chemistry control, 16-18
 - for 60-year design life, 16-18–16-19
- Material susceptibility, 21-5
- chromium concentration, 21-5
 - microstructure, 21-5
 - weld flaws, 21-5
 - yield strength, 21-5
- Mathcad®, 24-13
- MAWP. *See* Maximum allowable working pressure
- Maximum allowable operating pressure (MAOP), 11-29
- Maximum allowable working pressure (MAWP), 24-7, 28-1, 28-7, 28-8
- for B16.5 flange, 9-3
- “Maximum credible accident” concept, 29-3
- Maximum Extended Load Line Limit Analysis Plus (MELLLA+) conditions, 16-10
- Maximum (peak) ground acceleration, 6-4
- MCR. *See* Main control room
- MDM. *See* Materials degradation matrix
- MDMT. *See* Minimum design metal temperature
- Mean stress, effect of, 5-2–5-4
- Mechanical Engineering Magazine*, 1-1
- Mechanical nozzle repair, 21-23–21-24
- Mechanical nozzle seal assembly (MNSA), 21-23
- Mechanical stress, 21-25
- Mechanical Stress Improvement Process (MSIP), 25-2
- Mechanical trains, 15-26
- Membrane pressure stress, 20-4
- Metal fatigue, 18-6–18-8
- critical locations, 18-7
 - environmentally assisted fatigue (EAF) evaluation, 18-8
 - fatigue monitoring, 18-7–18-8
 - operating transients, 18-7
- Metal welds, dissimilar, 20-18–20-20
- MIC. *See* Microbial induced corrosion
- Microbial induced corrosion (MIC), 11-41, 27-15, 27-15f, 30-11, 30-12. *See also* Corrosion
- Minimum allowable temperature (MAT), 24-7
- Minimum design metal temperature (MDMT), 24-6, 24-12
- Ministry of International Trade and Industry (MITI), 16-2
- Missiles, 6-17
- characteristics, 6-18
 - chemical energy type, 6-18
 - construction and maintenance type, 6-18
 - contained fluid energy type, 6-17
 - and forcing functions, 6-18–6-19
 - gravitational potential energy type, 6-17
 - hard missile impact, 6-18–6-19
 - local effects, 6-18
 - natural phenomena type, 6-18
 - nuclear excursion type, 6-18
 - overall effects, 6-18
 - penetration, 6-18
 - rotational energy type, 6-17
 - secondary missiles, 6-18
 - soft missile impact, 6-19
 - stored strain energy type, 6-17
 - transport missiles, 6-18
 - typical missile forcing functions, 6-19
- Missing-mass effect, 6-12
- Mitigating Systems Performance Index (MSPI), 29-4
- Mitigation of severe accidents
- containment design and hydrogen risk, 15-18–15-19
 - containment heat removal, 15-19
 - corium retention and stabilization, 15-19
 - high-energy corium/water interaction, prevention of, 15-18
 - high-pressure core melt, prevention of, 15-18
- Mitigation programs, 20-16
- Mitsubishi Heavy Industries, Ltd. (MHI), 15-22
- Moderate-energy piping system, 6-4
- Modularization
- AP1000 plant, 15-9
 - and construction, US-APWR, 15-29–15-30
 - techniques, 16-20
- Modularization and construction
- Westinghouse SMR, 32-20, 32-20f
- Modulus of Elasticity (α), 30-13

- Moisture removal, 19-6
 Moisture separator, 15-24
 Moisture separator reheater (MSR), 32-19
 Molten fuel, 15-27
 Moment arms for flange loads, 9-9
 Moments
 Table 4.1 (Range of Resultant Moments, MC and MA, FT. LB.;
 and Stresses, S_{OL} by Equation (C8) and S_{TE} by Equation
 (C11), 4-15
 Monte Carlo methods, 19-12
 Moore's Law, 29-2
 Motor- or manually operated valves (MOV_s), 8-3–8-4
 MOV_s. *See* Motor- or manually operated valves
 MPCs. *See* Multi-purpose canisters
 MPFF. *See* Maintenance-preventable functional failure
 MRP. *See* Material Reliability Program
 MSIP. *See* Mechanical Stress Improvement Process
 MSPI. *See* Mitigating Systems Performance Index
 MSR. *See* Moisture separator reheater
 MSS (Manufacturers Standardization Society), 23-1, 23-9
Multi-Application Small Light Water Reactor (MASLWR), 32-2
 Multi-dimensional waterhammer equations, 8-14
 Multi-phase flow analysis, with CFD, 6-15
 Eulerian multi-phase (EMP) methods, 6-16–6-17
 Lagrangian methods, 6-15
 volume of fluid methods, 6-15–6-16
 Multi-phase flow loading, 6-3
- N-132, 1-3
 N-133, 1-3
 N-153, 1-3
 N626.3–1993, 1-5
 N-761, 5-24
 N-792, 5-24
 N-131(a), 1-3
 NAB. *See* Nuclear auxiliary building
 Narrow band–response spectrum, 6-4
 NASA. *See* National Aeronautics and Space Administration
 Nastran, for stress analysis, 6-11
 National Aeronautics and Space Administration (NASA), 22-1
 National Association of Corrosion Engineers (NACE) standard
 SP0169-2007 Section 5.2.3, 30-14
 National Association of Steam and Hot Water Fitters, 23-1
 National Board Inspection Code (NBIC), 28-4
 National Board of Boiler and Pressure Vessel Inspectors, 28-2, 28-5
 National Board (NB-18) Pressure Relief Device Certification (The
 Redbook), 28-8
 National Board Synopsis NB-370, 28-5
 National Defense Research Committee, 6-18
 National Energy Board (NEB), Canada, 11-4, 11-5
 National Research Council (NRC), 12-2–12-3, 14-3
 letter 50.54f, 14-2
 Natural circulation design, 16-9, 16-20
 Natural frequency, 6-4
 NBIC. *See* National Board Inspection Code
 NCA-1140, 1-14
 NCA-3230, 1-15
 NCA-5220, 1-5
 NCA-8100, 1-15
 NCA-1130(a), 1-14
 NCA-1130(b), 1-14
 NC/ND-3653.1, 14-5
 NC/ND-3654, 14-5
 NC/ND-3655, 14-5
 ND-3600, 14-6
 NDA. *See* Nuclear Decommissioning Authority
 NDE. *See* Nondestructive examinations
 Near Term Task Force (NTTF), 29-7, 30-1
 NEB. *See* National Energy Board
 NEI. *See* Nuclear Energy Institute
 NEI 07-07, 30-11
 NEI 09-14, 30-11
 Net positive suction head (NPSH), 15-27, 20-3
 Neutral axis, 19-4
 Neutron, 33-1, 33-2
 Neutron absorber, 16-14
 Neutron embrittlement, 17-8
 Next generation nuclear plant (NGNP), 17-2
 design features and technology uncertainties for, 17-10
 technical issues safety research needs, June 2006, 17-10
 NFPA 805
 fire protection licensing using, 29-5–29-6
 304NG/304L wrought materials, 16-17
 316NG/316L wrought materials, 16-17
 NGNP. *See* Next generation nuclear plant
 NG18 surface flaw equations, 11-27
 Nickel, 20-12
 Nickel-based alloys, 16-18, 21-1
 Nickel-chromium-iron (Ni-Cr-Fe), 19-14, 19-16, 19-20
 alloys, F_{en} for, 30-10–30-11
 Nil-ductility reference temperature index (RT_{NDT}), 20-1, 20-8–20-9
 Niobium modified Alloy 600, 16-18
 NIST (NuScale Integral System Test) facility, 32-9, 32-9f
 Nonconforming condition, 7-17
 Nondestructive examinations (NDE), 1-6, 2-8, 21-8, 22-6, 25-4
 advancement of, 25-5
 methods, 30-13, 30-15
 Non-Mandatory Appendices, 1-5
 Nonmetallic materials
 application problems, 26-10–26-11
 components
 graphite, 26-8
 thermoplastic, 26-7
 thermoset plastic, 26-7–26-8
 construction codes, 26-5
 design specification, 26-6–26-7
 aspects, 26-7
 contents, 26-6–26-7
 references, 26-7
 fabrication processes
 graphite materials, 26-11
 thermoplastic materials, 26-11
 thermoset plastic materials, 26-11
 graphite, 26-6
 joining of components (and subcomponents)
 graphite, 26-9, 26-10f
 thermoplastic, 26-8, 26-9f
 thermoset plastic secondary bonding and joining, 26-9,
 26-9f–26-10f
 overview, 26-5
 quality assurance (QA), 26-11
 thermoplastic, 26-5–26-6
 thermoset plastic, 26-6
 types of, 26-5–26-6
 Non-reclosing device, 28-1

- Nonsafety active systems, AP1000 plant, 15-7
- Nonseismic building
 - annex building, 15-8
 - diesel generator building, 15-8
 - radwaste building, 15-8
 - turbine building, 15-8
- Non-seismic interface, 14-6
- Non-seismic piping, 14-6
- Normalized fluid flow equations, 8-13
- Normal mode, 6-4
- North Anna Nuclear Power Plant (NANPP), 14-2
- Notch weakening, 17-4–17-5
- Nozzles
 - ejection risk, 21-16
 - feedwater, 19-8–19-9
 - inner radii, alternate inspection method for, 19-9–19-11
- NPM. *See* NuScale Power Module
- NPP. *See* Nuclear power plants
- NPSH. *See* Net positive suction head
- NQA-1, 1-6–1-7
- NRC. *See* National Research Council; Nuclear Regulatory Commission
- NRC Branch Technical Position, 16-20
- NRC Inspection and Enforcement Bulletin 79-02, 7-15
- NRC Inspection Manual Part 9900, 7-2
- NRC licensing review, 17-4
- NRC order EA-03-009, 25-3
- NRC Policy Statement on PRA, 29-3–29-4
- NRC Regulatory Guide (Reg. Guide) 7.6, 10-13–10-14
- NREG-6909, 30-7, 30-8, 30-9
- NRELAP5-3D code, 32-9, 32-9f
- NRMCC Integrated Risk Management Milestone Schedule, 22-23
- NSSS. *See* Nuclear steam supply system
- N-Type Certificate of Authorization, 1-15–1-16. *See also* Nuclear certification programs
- Nuclear auxiliary building (NAB), 15-13
- Nuclear certification programs, 1-14–1-15
 - agreement with AIA in, 1-17
 - applicable codes, 1-17
 - ASME Accreditation, new developments in, 1-18–1-19
 - ASME Survey Team, 1-17
 - certification process, 1-16–1-17
 - Interim Letter, 1-16
 - issuance and renewal of certificates, 1-16
 - manual revisions and audits of QSCs in, 1-17
 - and new single ASME Certification Mark, 1-19
 - N-Type Certificate of Authorization, 1-15–1-16
 - Owners Certificate of Authorization (OWN), 1-15
 - Quality System Certificate (QSC), 1-15
 - survey in, 1-17–1-18
- Nuclear code case N-755, 30-12
 - related issues identified by NRC (buried polyethylene piping), 30-13
 - backfill for buried HDPE pipe, 30-14
 - essential variables, 30-14
 - examinations, 30-15
 - fusion procedure and equipment qualifications, 30-14–30-15
 - material, fabrication, and examination related, 30-14–30-15
 - performance demonstration qualifications, 30-14
 - structural related, 30-13–30-14
 - visual and ultrasonic testing qualifications, 30-15
- Nuclear Decommissioning Authority (NDA), 12-1, 12-3–12-4
- Nuclear energy, 1-2
- Nuclear Energy Institute (NEI), 18-1, 22-3, 30-11
- Nuclear Energy Institute criteria, for Maintenance Rule, 2-1. *See also* Maintenance Rule
- Nuclear fusion. *See also* Fusion
 - ASME standards, 33-14
 - FES, 33-13–33-14
 - process overview, 33-13
 - in US, 33-13
- Nuclear grade (NG), 16-17
- Nuclear island, Westinghouse SMR, 32-15, 32-15f
 - containment vessel, 32-17–32-18, 32-17f
 - fuel and core design, 32-18–32-19, 32-18f, 32-19f
 - integral reactor, 32-15, 32-16f
 - coolant pumps, 32-16, 32-16f
 - CRDMs, 32-16, 32-17f
 - pressurizer, 32-15
 - reactor internals, 32-16, 32-16f
 - steam generator, 32-15
 - steam generator/drum design, 32-16–32-17, 32-17f
- Nuclear Plant Reliability Data System (NPRDS), 7-3
- Nuclear power plants (NPP), 14-2, 30-1
- Nuclear Regulatory Commission, 32-21
- Nuclear Regulatory Commission (NRC), 1-3, 2-1, 3-2, 6-10, 6-11, 10-1, 16-2, 17-8, 22-1, 22-2, 33-14. *See also* Maintenance Rule
 - 10 CFR 50.69, “Risk-Informed Categorization and Treatment of Structures, Systems, and Components for Nuclear Power Plants,” 22-11
 - conditions on Code Case N-597-2, 27-14–27-15
 - issuance of Generic Letter 88-20, 29-3
 - license renewal rule, 18-2
 - Maintenance Rule, 29-3
 - NUREG-1150 study, 22-2
 - Policy Statement on PRA, 29-3–29-4
 - Regulatory Guides (risk-informed ISI and IST implementation)
 - RG 1.175, 22-19
 - RG 1.178, 22-19
 - RG 1.200, 22-19
 - regulatory process, 18-2
 - relief for nuclear plant technical specifications, PRAs and, 29-4–29-5
 - safety evaluation report (SER), 18-5
 - supplements issued by, 18-3
- Nuclear Regulatory Commission (NRC) (issues and lessons learned)
 - buried pipe-leakage issues
 - overview, 30-11
 - protection measures, 30-11
 - BWR steam dryers for EPU operation, 30-15
 - acoustic mitigation device, 30-16
 - acoustic resonance, 30-15–30-16
 - analytical methodology related issues, 30-17–30-18
 - bias errors and uncertainties related issues, 30-17
 - fabrication, installation, and quality control, 30-18
 - monitoring, 30-18
 - MSL and dryer instrumentation related issues, 30-17
 - single and double vortex acoustic resonances, 30-16
 - steam dryer margin, 30-16–30-17
 - Fukushima Daiichi accident, 30-1–30-7
 - 10 CFR 50.63, 30-2, 30-6
 - 10 CFR 50.54(f), 30-1
 - 10 CFR 50.54(f) letter, 30-5, 30-6

- 10 CFR 50.54(hh)(2), 30-2–30-3, 30-6
- effectiveness of hardened vents (Recommendation 5), 30-3
- Emergency Preparedness (EP) enhancements (Recommendations 9 through 11), 30-3–30-4
- Ensuring Protection (Recommendations 2 and 3), 30-2
- Mitigation Enhancement (Recommendations 4 through 8), 30-2–30-3
- NRC Programs Efficiency Improvement (Recommendation 12), 30-4
- NTTF's recommendations, 30-1
- NUREG-0737, 30-3
- NUREG-1560 (Individual Plant Examination Program: Perspectives on Reactor Safety and Plant Performance), 30-2
- NUREG-1742 (Perspectives Gained from the Individual Plant Examination of External Events [IPEEE] Program), 30-2
- NUREG-1860, 30-2
- onsite emergency response capabilities enhancement (Recommendation 8), 30-3
- Order EA-12-049, 30-5, 30-6
- Order EA-12-051, 30-5, 30-6
- Order EA-13-109, 30-5, 30-6
- orders, 30-5, 30-6
- Recommendation 2.1, 30-5
- Recommendation 2.3, 30-5
- recommended rulemaking activities, 30-4–30-6
- Regulatory Analysis Guidelines modification, 30-2
- Regulatory Framework Clarification (Recommendation 1), 30-2
- spent fuel pool makeup capability and instrumentation enhancement (Recommendation 7), 30-3
- “Station Blackout Mitigation Strategies Rulemaking” (Recommendation 4), 30-2–30-3
- HDPE for carbon steel piping replacement, 30-11–30-15
 - lessons learned and special design considerations, 30-12
 - material, fabrication, and examination related issues, 30-14–30-15
 - overview, 30-11–30-12
 - structural related issues, 30-13–30-14
 - thermal gradient stress, 30-12–30-13
- LWR environment effect on nuclear plant components fatigue life, 30-7–30-11
 - fatigue considerations, 30-8–30-9
 - fatigue lives of austenitic SSs, 30-10
 - fatigue strain vs. life ($\epsilon-N$) behavior in air, 30-9
 - F_{en} for carbon and low-alloy steels, 30-10
 - F_{en} for Ni-Cr-Fe alloys, 30-10–30-11
 - NREG-6909, 30-7, 30-8, 30-9
 - NREG/CR-6909, 30-8
 - overview, 30-7–30-8
- new construction and, 30-20
 - emerging issues, 30-20
 - inspectability related issues, 30-20
 - weld residual stress mitigation, 30-20
- overview, 30-1
- RPV indications in DOEL and Tihange NPP, 30-19
 - hydrogen flaking, 30-19
- steam generator tube leaks, 30-19–30-20
 - root cause analysis, 30-19
- Nuclear Risk Management Coordinating Committee, 22-22, 22-23
- Nuclear safety-related, 6-4
- Nuclear steam supply system (NSSS), 16-1
 - control assemblies, 15-14
 - control rod drive mechanisms (CRDM), 15-14
 - core instrumentation, 15-14
 - main coolant lines, 15-15
 - pressurizer (PZR), 15-15
 - reactor coolant pumps, 15-15
 - reactor core, 15-14
 - reactor pressure vessel (RPV) and internal structures, 15-13–15-14
 - steam generators, 15-14–15-15
- Nuclear steam supply system (NSSS) factory assembly
 - NuScale's economies of small and, 32-10–32-11
- Nuclear Support (NS) Certificate, 1-15–1-16
- Nuclear Utilities Procurement Issues Committee (NUPIC), 1-18
- Nucleosynthesis, 33-1–33-2
- NUMARC 93-01, 7-16
- NUPIC. *See* Nuclear Utilities Procurement Issues Committee
- NUREG-0224, 20-3
- NUREG-0313, 19-3
- NUREG-0313, Revision 2, 19-17
- NUREG-0619, 19-9
- NUREG-0737, 30-3
- NUREG-0744, 19-15
- NUREG-0800, Standard Review Plan, 3-3
- NUREG-1368, 17-8
- NUREG-1560 (Individual Plant Examination Program: Perspectives on Reactor Safety and Plant Performance), 30-2
- NUREG-1742 (Perspectives Gained from the Individual Plant Examination of External Events [IPEEE] Program), 30-2
- NUREG-1800, 18-10, 20-16
- NUREG-1801, 18-2, 18-10, 20-16
- NUREG-1801, Rev. 2, 30-14
- NUREG-1832, 18-9
- NUREG-1860, 30-2
- NUREG-6490, 18-2
- NUREG-6909, 18-8
- NUREG-6909, Rev. 1, 5-24
- NUREG/CR-0098, 6-8, 6-9
- NUREG/CR-1815, 10-14
- NUREG/CR-3019, 10-14–10-15
- NUREG/CR-3854, 10-15
- NUREG/CR-5704, 18-8, 19-21
- NUREG/CR-5955, 17-7–17-8
- NUREG/CR-5999, 18-7
- NUREG/CR-6260, 18-7, 18-8, 19-21
- NUREG/CR-6583, 18-8, 19-21
- NUREG/CR-6816, June 2003, 17-8
- NUREG/CR-6824, July 2003, 17-9–17-10
- NUREG/CR-6909, 16-19, 16-20, 19-21, 30-8, 30-9
- NUREG/CR-6850 Fire PRA method, 29-5
- NUREG-1150 study, 22-2
- NuScale Integral System Test (NIST) facility, 32-9, 32-9f
- NuScale Plant Owners Requirements Document, 32-12
- NuScale Power, 32-1
 - CAB, 32-12
 - control room simulator, 32-1f, 32-10, 32-10f
 - economies of small, 32-10, 32-10f
 - design simplicity (size reduction and simplification), 32-10–32-11
 - innovative operations, 32-12
 - NSSS factory fabrication, 32-11
 - simplified parallel construction, 32-11–32-12
- NPM. *See* NuScale Power Module
- overview, 32-1
- plant design

NuScale Power (*continued*)

- features that prevent/mitigate events and threats, 32-11t
- overview, 32-2–32-5, 32-3f–32-5f, 32-5t
- regulator, 32-12
- response to extreme events, 32-7–32-8
 - complete station blackout, 32-8, 32-8f
 - PIRT assessments, 32-7
 - PRA model, 32-8, 32-8f
- safety, security, and asset protection, 32-5
 - DHRS, 32-6, 32-6f
 - ECCS, 32-6f–32-7f, 32-7
 - high pressure CV, 32-5–32-6
 - passive safety systems (elimination of LOCA), 32-6
- SMR deployment approach, 32-2, 32-2f. *See also* Westinghouse Small Modular Reactor
- supply chain, 32-12
- test programs, 32-8–32-10, 32-9f

NuScale Power Module (NPM), 32-1, 32-2f

- components, 32-2
- containment vessel (CV), 32-2, 32-3
- core configuration, 32-2–32-3, 32-3f
- CVCS, 32-2, 32-3
- design overview, 32-2–32-5, 32-3f–32-5f, 32-5t
- DHRS, 32-3, 32-6, 32-6f
- ECCS, 32-3, 32-6f–32-7f, 32-7
- high pressure CV, 32-5–32-6
- natural circulation flow of primary coolant and reactor core, 32-2, 32-3f
- passive safety systems (elimination of LOCA), 32-6
- power conversion unit, 32-3f
- reactor building, 32-3–32-4, 32-4f
- reactor pressure vessel, 32-2, 32-3
- safety, security, and asset protection, 32-5
- 12-unit plant
 - characteristics, 32-5t
 - concept for, 32-5, 32-5f
 - “in-line refueling,” 32-4–32-5
 - site layout for, 32-4–32-5, 32-5f

Oak Ridge National Laboratory (ORNL), 17-2, 17-8, 20-6, 20-11

OBE. *See* Operating-basis earthquake

Occidental's Cano Limon pipeline, 11-52

Octave, 6-4

OECD Pipe Failure Data Exchange (OPDE) Project, 7-3

OEM. *See* Original equipment manufacturer

Office of Pipeline Safety (OPS), 11-5

- on reportable incident, 11-3

Okrent, David, 29-2

Oliphant, Mark, 33-3

One-dimensional flow theory, 8-13

One-piece-technology, 15-15

On-line maintenance, 2-11

Online monitoring of crack growth, 19-24

Onset of nucleate boiling (ONB), 32-17

Onshore Pipeline Regulations (OPR), 11-7

Operability and functionality, 7-1

- ASME Code requirements, 7-9–7-12

- piping, 7-10

- pumps, 7-10

- reactor vessel, 7-11–7-12

- snubbers, 7-10

- valves, 7-9–7-10

evaluations

- conditions requiring assessment, 7-7–7-8

- scoping operability evaluations, 7-8–7-9

long-term operability, 7-16

mechanical components and failure modes, 7-3

- piping components, 7-3–7-6

- pumps, 7-7

- supports, 7-6

- valves, 7-7

nomenclature related to, 7-17

operability evaluation methods, 7-12–7-14

probabilistic assessment, 7-16

related definition

- functional/functionality, 7-2–7-3

- operable/operability, 7-1–7-2

short-term operability acceptance criteria, 7-14–7-16

systems, structures, or components (SSCs) and, 7-1

Operability evaluation methods, 7-12–7-14

- piping systems, 7-12

- pumps, tanks, and heat exchangers, 7-13

- specific inspections, 7-13–7-14

- supports, 7-12–7-13

- valves, 7-13

Operating-basis earthquake (OBE), 6-4, 14-2, 15-28

Operating domain, 16-9–16-10

Operating life of plant, 6-1

Operating system, 2-3. *See also* Maintenance Rule

Operational technology, API1000 PWR, 15-3–15-4

Operation and maintenance

- US-APWR, 15-30

- Westinghouse SMR, 32-20–32-21

OPR. *See* Onshore Pipeline Regulations

Optimized structural weld overlays (OWOL), 21-22

20% OP valves, 28-2

Order EA-12-049, 30-5, 30-6

Order EA-12-051, 30-5, 30-6

Order EA-13-109, 30-5, 30-6

O'Regan, Patrick J., 22-1

Original equipment manufacturer (OEM), 28-5, 28-6, 28-8

O-ring-type gaskets, 9-2

ORNL. *See* Oak Ridge National Laboratory

Oscillating lift force, 8-10

Overpressure, 28-1

Overpressure Protection (Part 9, VIII-2), 24-13

Overpressure Protection Report, 19-15

OWN. *See* Owners Certificate of Authorization

Owner, 6-5

Owners Certificate of Authorization (OWN), 1-15. *See also* Nuclear certification programs

Owner's Design Specification, 19-20

Owner's Review of the Design Report, 1-5, 1-6

OWOL. *See* Optimized structural weld overlays

Paccioli's puzzle, 29-1

Part 54, license renewal rule, 18-2

Partial-penetration welded nozzles, 21-10

Passive containment cooling system (PCCS), 15-5, 15-6, 16-12–16-14. *See also* Passive safety features, BWR

Passive core cooling system (PXS), 15-5–15-6

Passive failure, 6-5

Passive residual heat exchanger removal system (PRHR HX), 15-4

Passive residual heat removal (PRHR), 15-5, 15-6

- Passive safety features, BWR, 16-10–16-15. *See also* Boiling water reactor
- gravity-driven core cooling system (GDCS), 16-10–16-12
 - isolation condenser system, 16-14–16-15
 - passive containment cooling system (PCCS), 16-12–16-14, 16-13
 - standby liquid control system (SLCS), 16-14
- Passive safety-related systems, 15-5–15-6
- Passive safety systems
- NuScale Power plant, 32-6
 - Westinghouse SMR, 32-14
- Passive structures and components, 18-4
- PBMR. *See* Pebble bed modular reactor
- PCCS. *See* Passive containment cooling system
- PCCV. *See* Prestressed concrete containment vessel
- PDD-63. *See* Presidential Decision Directive 63
- PDI. *See* Performance demonstration initiative
- PE4710, 30-14
- Peak ground acceleration (PGA), 15-28
- Peak stress, 17-3
- Peak stress index, 3-28
- Pearson method, 11-25
- Pebble bed modular reactor (PBMR), 1-33, 17-8, 25-1–25-2
- Peening, 21-25
- Peer Reviews of PRAs, 22-6
- Pellet density, 15-24
- Penetrant testing (PT), 19-9
- Performance demonstration initiative (PDI), 21-18, 25-5
- Performance indicators, 11-10
- Performance monitoring, 2-3. *See also* Maintenance Rule
- Performance Test Code PTC-25, 28-3
- Peterson cubic equation, 5-4
- PF coils. *See* Poloidal field coils
- PGA. *See* Peak ground acceleration
- Phenolic materials, 26-6
- Phenomena identification and ranking table (PIRT) assessments
- NuScale Power plants and, 32-7
- Phosphorus, 16-19
- PIMS. *See* Pipeline Integrity Management System
- Pin type devices, 28-3–28-4
- Pipe
- bulk flow and propagative flow modeling in, 8-8–8-10
 - movement, and fluid disturbances, 8-7
 - rupture, and fluid disturbances, 8-6
 - whip, 6-5
- Pipe break loads, 6-17
- computation of, 6-17
- Pipe failure, 7-3–7-6
- Figure 7.3 (Piping Failure Trends in Commercial Nuclear Power Plants), 7-4
 - Figure 7.4 (U.S. Failure Data), 7-4
 - Figure 7.5 (Pipe Failures by Calendar), 7-5
 - Figure 7.6 (Piping Failures Caused by Stress Corrosion Cracking), 7-5
 - Figure 7.7 (U.S. Pipe Failure Data by Safety Classification), 7-6
- Pipe flaw evaluation, in ASME Section XI. *See also* Section XI (flaw Acceptance Standards development and analytical evaluation procedures)
- analytical procedures and acceptance criteria for planar flaws, 27-3–27-4
 - in buried metallic pipe, 27-15–27-19
 - Acceptance Standards for metal loss, 27-17
 - level 2 analytical evaluation method, 27-17–27-19
 - metal loss characterization, 27-16–27-17
 - overview, 27-16
 - revised acceptance criteria, for design intent margins maintenance, 27-6
 - for circumferential flaws for limit load prior to 2002 Addenda, 27-8
 - for circumferential flaws in 2002 Addenda, 27-9–27-11
 - plastic collapse equations for circumferential flaws and ASME Section III Primary Stress Limits, 27-7–27-8
 - structural factors specific to each service level in 2002 Addenda, 27-8–27-9
 - steps for, 27-2–27-3
 - structure of, 27-3
- Pipe leg, 3-1
- Pipeline integrity, 11-5
- plan, 11-5
- Pipeline Integrity Management System (PIMS), 11-5
- Pipeline Open Database Standard (PODS), 11-9
- Pipeline Research Council International (PRCI), 11-27
- Pipelines, 11-1. *See also* Pipe
- cathodic protection, 11-45–11-48
 - coatings, 11-41–11-45
 - corrosion control, 11-39–11-41. *See also* Corrosion
 - corrosion inhibition, 11-48
 - defect assessment methods, 11-26–11-34
 - corrosion defects, 11-29–11-31
 - dents, 11-28
 - dents and gouges, 11-28–11-29
 - gouges, 11-27–11-28
 - weld defects, 11-31–11-32
 - worked examples, 11-32–11-34
 - delivery lines, 11-3
 - failure assessment, 11-5
 - failure mechanism, 11-5
 - failure mode, 11-5
 - failures, 11-4
 - fatal events related to, 11-1
 - Figure 11.1 (Gas Pipeline Explosion), 11-1
 - Figure 11.2 (Natural Gas System Network), 11-3
 - Figure 11.3 (Amount of U.S. Transmission Line Construction by Decade), 11-3
 - Figure 11.4 (Causes of Pipeline Incidents on US Pipelines from 2002–2007), 11-4
 - Figure 11.5 (Common Failure Modes), 11-5
 - Figure 11.6 (Pipeline Integrity Management Systems), 11-7
 - Figure 11.7 (Integrity Management Process Flow Diagram [from ASME B31.8S]), 11-8
 - Figure 11.8 (API 1160 Managing System Integrity for Hazardous Liquid Pipelines), 11-8
 - Figure 11.9 (Simplified Risk Hierarchy), 11-12
 - Figure 11.10 (Example of Relative Ratings of Potential Threats), 11-13
 - Figure 11.11 (Risk Screening Matrix), 11-13
 - Figure 11.12 (Risk Assessment and Mitigation Process Template), 11-14
 - Figure 11.13 (Calculating Failure Probability from Limit State Analysis), 11-15
 - Figure 11.14 (Simple Event Tree to Predict Ignition Probability Following Rupture), 11-15
 - Figure 11.15 (Various Possible Scenarios Following Gas Pipeline Rupture), 11-16
 - Figure 11.16 (Representation of ALARP Principle), 11-16

Pipelines (*continued*)

- Figure 11.17 (Effect of Three Integrity Strategies on Risk Reduction), 11-17
- Figure 11.18 (Aftermath of Successful Hydro Test to Drive Out SCC), 11-17
- Figure 11.19 (Defect Assessment Curve), 11-18
- Figure 11.20 (Principle of Magnetic Flux Leakage), 11-18
- Figure 11.21 (Ultrasonic Tool Batched for Use in Gas Line), 11-19
- Figure 11.22 (POE Leak Risk Scenarios at 80% W.T. Probabilistic Corrosion Growth Model), 11-20
- Figure 11.23 (POE Rupture Risk Scenarios at 100% MOP), 11-21
- Figure 11.24 (Four Step ECDA Approach), 11-26
- Figure 11.25 (Part Wall and Throughwall Defects), 11-27
- Figure 11.26 (Dimensions of Longitudinal and Circumferential Through Wall Crack Defects), 11-27
- Figure 11.27 (Dents Under Pressure), 11-28
- Figure 11.28 (Method of Determining Longitudinal Extent), 11-29
- Figure 11.29 (Determination of Non Dimensional Variable B), 11-30
- Figure 11.30 (Simplified and Detailed RSTRENG Profiles), 11-31
- Figure 11.31 (Profile of Corrosion Depth), 11-31
- Figure 11.32 (Remaining Strength Assessment Representative of Metal Loss), 11-32
- Figure 11.33 (Corrosion Defect Repairs Using Type A and Type B Sleeves), 11-35
- Figure 11.34 (Composite Wrap Repairs), 11-36
- Figure 11.35 (Clock Spring™ Repair), 11-36
- Figure 11.36 (Stoppie Fitting for Line Replacement), 11-37
- Figure 11.37 (Corrosion Cell), 11-39
- Figure 11.38 (Methods of Mitigating Pipeline Corrosion), 11-41
- Figure 11.39 (History of Coating Development), 11-42
- Figure 11.40 (Multi layer Composite Coating), 11-42
- Figure 11.41 (Sources of Coating Failure on Australian Pipelines), 11-43
- Figure 11.42 (Anode Ground Bed), 11-48
- Figure 11.43 (Helicopter Borne Lidar Used for Surface Topography and Leak Detection), 11-50
- Figure 11.44 (Buried Fibre Optic Ground Movement Sensor), 11-51
- Figure 11.45 (Synthetic Aperture Radar Scanning Swaths from Orbiting Satellites), 11-51
- Figure 11.46 (Vandalized Attack on Alyeska Pipeline), 11-52
- Figure 11.47 (Gas Pipeline System Dependencies), 11-53
- gathering system, 11-2
- integrity assessment methods, 11-16
 - direct assessment, 11-20–11-26
 - hydrostatic testing, 11-16–11-18
 - in-line inspection, 11-18–11-20
- integrity management programs, 11-6–11-11. *See also* Integrity Management Program, pipeline
- older, 11-3
- operability evaluation methods, 7-12
- overview of system, 11-2–11-3
- protection, 11-41–11-48
- regulations, 11-5
- repair, 11-34–11-38
- risk assessment, 11-12–11-15
- risk mitigation, 11-15
- safety and environmental protection, 11-3–11-5
- security management programs, 11-52–11-55
 - emergency response plans, 11-54–11-55
 - government and industry response, 11-54
 - vulnerability assessments, 11-54
- short-term operability acceptance criteria for, 7-14
- societal and individual risk from, 11-1–11-2
- Table 11.1 (Comparison of Operating Cost of Various Transportation Systems), 11-2
- Table 11.2 (Approximate Fatality Rate by Mode, 2001), 11-4
- Table 11.3 (Major Threats to Transmission Pipelines ASME B31.8S), 11-7
- Table 11.4 (Index Methods for Rating Annual Probability of Occurrence), 11-13
- Table 11.5 (Matching Risk Severity with Level of Response), 11-14
- Table 11.6 (Defect Detection Capability of Various Inspection Tools), 11-20
- Table 11.7 (Attributes of Various Pipeline Protection Methods), 11-22–11-25
- Table 11.8 (Summary of Strengths and Weakness of Various Assessment Techniques), 11-32
- Table 11.9 (Relevant Codes and Standards for Making Repairs), 11-35
- Table 11.10 (Permissibility of Corrosion Repair Technique), 11-37
- Table 11.11 (Permissibility of Crack Repair Technique), 11-38
- Table 11.12 (Permissibility of Mechanical Damage Repair Technique), 11-38
- Table 11.13 (Pipeline Corrosion Prevention), 11-304
- Table 11.14 (M Galvanic Series of Common Commercial Metals and Alloys in Brine), 11-40
- Table 11.15 (Advantages and Disadvantages of Pipeline Coatings), 11-44
- Table 11.16 (Classification of Pipeline Coating Tests), 11-45–11-46
- third party damage, awareness and control of, 11-48–11-52
 - line marking and locating, 11-49
 - remote sensing of encroachment, 11-50–11-52
 - remote sensing of leaks, 11-49–11-50
 - right of way patrols, 11-49
- threats to integrity of, 11-4
- transmission line, 11-2–11-3
- transportation, cost effectiveness and importance of, 11-2
- visual inspection of, 7-13
- Pipeline Safety Improvement Act of 2002, U. S., 11-4, 11-20, 11-52
- PIPESTRESS, 6-11
- Pipe-to-soil meters, 11-48
- Pipe-whip restraint, 6-5
- Piping and Fitting Dynamic Reliability Program, 7-12
- Piping network, 6-5
- Piping run, 6-5
- Piping system, seismic analysis of, 14-2–14-6. *See also* Seismic protection of pressure piping systems
 - alternate seismic rules (new), 14-4
 - boundary conditions, 14-3
 - code Class 2 and Class 3 piping, 14-5–14-6
 - code Class 1 piping, 14-4–14-5
 - damping, 14-3–14-4
 - geometric and material properties, 14-3
 - geometry, 14-3
 - seismic loading input, 14-3
- Piping systems
 - B31 code, 23-1
- Piping thickness, 16-19
- Piping vibration
 - ASME/ANSI O&M Standard on, 3-4–3-5
 - allowable stresses in Standard, 3-5
 - Figure 3.2 (Allowable Peak Stress vs. Number of Cycles for Stainless Steel), 3-5
 - O&M Part 3 Standard, 3-4–3-5

- case studies on problems related to, 3-33–3-35
- Table 3.1 (Motor-Driven Feedwater Pump Discharge Piping), 3-33
- Table 3.2 (Auxiliary Feedwater Pump), 3-33
- Table 3.3 (Safety-Injection Piping), 3-33
- Table 3.4 (Feedwater-Recirculation Piping), 3-34
- Table 3.5 (Condensate Piping), 3-34
- Table 3.6 (Service Water Piping), 3-34
- Table 3.7 (Main Steam-Bypass Piping), 3-34
- Table 3.8 (Main Steam-Turbine Leads), 3-34
- Table 3.9 (Chemical- and Volume-Control Piping), 3-35
- Table 3.10 (Heater-Vent Piping), 3-35
- Table 3.11 (Heater-Drain Piping), 3-35
- causes of, 3-5
 - cavitation and flashing, 3-7–3-8
 - flow turbulence, 3-7
 - pump-induced pressure pulsations, 3-5–3-7
 - vortex shedding, 3-8–3-9
 - water- and steamhammer, 3-9–3-12
- characteristics of
 - dynamic-transient vibration, 3-1
 - steady-state vibration, 3-1
- and design considerations, 3-12
 - low- and high-tuning and damping, 3-13–3-14
 - single-degree-of-freedom response, 3-12
- and design guidelines
 - design practices, 3-15–3-16
 - plant design stage, 3-15
 - prevention and control, 3-14–3-15
- future plans, for enhancing OM-3 standard, 3-35–3-36
- as problems in power plants, 3-1–3-2
- problems of, addressing of, 3-2
 - industry Codes and Standards, 3-2–3-3
 - requirements for nuclear power plants, 3-3–3-4
 - vibration acceptance criteria, 3-4
- testing and analysis, 3-16
 - acceptable vibration limits, determination of, 3-28–3-29
 - acoustical response of piping, 3-31–3-33
 - piping structural response, 3-25–3-28
 - shell-mode vibration, 3-30–3-31
 - system walkdown procedures, 3-21–3-25
 - vibration measurements, 3-16–3-21
- Piping weld inlay/on-lay, 21-22
- Piping weld overlay, 21-21–21-22
- PIRT assessments. *See* Phenomena identification and ranking table assessments
- Plasmas, physics of, 33-13–33-14
- Plastic collapse equations
 - for circumferential flaws and ASME Section III Primary Stress Limits, 27-7–27-8
- Plastic deformation, 17-3
- Plastic instability, 14-1
- Plastic strain concentration factors, 17-7
- Plutonium, double containment for
 - elimination of, 10-17
 - 1974 final rule, 10-12–10-13
 - 1973 proposed rule, 10-11
- Plutonium for vitrified high level waste, 1997 proposed rule, 10-17
- PMI. *See* Positive Material Identification
- PODS. *See* Pipeline Open Database Standard
- POE. *See* Probability of Exceedance
- Poisson's ratio, 14-3
- Poloidal field (PF) coils, ITER, 33-5, 33-7, 33-7f
- Polyester, 26-6
- Polyethylene (PE), 26-5
- Polyphenylene (PPE), 26-5
- Polypropylene (PP), 26-5
- Polyvinyl chloride (PVC), 26-5
- Polyvinylidene fluoride (PVDF), 26-5
- Positive displacement pumps, 8-7–8-8
- Positive Material Identification (PMI), 31-4
- Post-fabrication cleanup
 - corrosion resistance and, 26-3
- Postmanufacturing surface processing, 16-18
- Postulated flaw size and location, 20-2–20-3
- Postulated pipe break, 6-5
- Postweld heat treatment (PWHT), 19-12, 19-19, 26-2
- Power piping, ASME B31.1, 4-18
- Power plant piping, causes of damages in, 14-1
- Power reactor innovative small module (PRISM) reactor, 17-8
- Power source buildings, 15-29
- Power spectral density (PSD), 6-5
- Power supplies
 - ITER plant, 33-20–33-11
- PPI TR-3, 26-6, 26-7
- PPI TR-4, 26-6, 26-7
- PRA. *See* Pressurized water reactors; Probabilistic risk assessment
- PRCI. *See* Pipeline Research Council International
- PRDs. *See* Pressure relief devices
- Preapplication Safety Evaluation Report, 17-8
- Predictive maintenance activities, 2-10
- Preheat, 19-19
- Presidential Decision Directive 63 (PDD-63), 11-54
- Pressure relief devices (PRDs), 28-1–28-11
 - API Standards, 28-9
 - API 520, Part 1 (Sizing and Selection), 28-9
 - API 520, Part 2 (Installation), 28-10
 - API 521 (Pressure Relieving and Depressurizing Systems), 28-10
 - API 526 (Flanged Steel Pressure Relief Valves), 28-10
 - API 527 (Valve Seat Tightness), 28-10
 - API 2000 (Venting Atmospheric and Low Pressure Storage Tanks), 28-10
 - API Documents (Updates, Interpretations, and Membership), 28-10–28-11
 - API Std 2510 (Design and Construction of LPG Installations), 28-10
- ASME Codes
 - Appendix 11 (Mandatory) (Capacity Conversion for Safety Valves), 28-7
 - Appendix M (Non-Mandatory) (Installation and Operation), 28-7
 - ASME B31.1 (Power Piping), 28-8–28-9
 - ASME B31.3 (Process Piping), 28-9
 - ASME IV (Heating Boilers), 28-6
 - ASME Section I (Power Boilers), 28-5–28-6
 - ASME Section VIII (Division 1 – Pressure Vessels), 28-6–28-7
 - ASME Section VIII, Divisions 2 and 3 (High Pressure Vessels), 28-8
 - ASME Section X (Fiber-Reinforced Plastic Pressure Vessels), 28-8
- jurisdictional requirements and, 28-5
- National Board (NB-18) Pressure Relief Device Certification (The Redbook), 28-8

Pressure relief devices (PRDs) (*continued*)

- pressure relief valve inlet pressure drop (the 3% rule), 28-7
- pressure relief valve outlet pressure drop (the 10% rule), 28-7–28-8
- pressure vessels with internal pressures of 15 psi and less, 28-8
- history, 28-2
 - boiler explosions vs. steam pressure (1880–1980), 28-2f
 - Code markings updates, 28-4
 - liquid capacity certification, 28-2
 - new technology and new Code Rules implementation, 28-4
 - 20% OP valves, 28-2
 - pin type devices, 28-3–28-4
 - rupture disk certification, 28-3
 - service issues, 28-4
- overview, 28-1
- terminology, 28-1
 - accumulation, 28-1
 - non-reclosing device, 28-1
 - overpressure, 28-1
 - pressure relief valve, 28-1
 - relief valve, 28-1
 - safety relief valve, 28-1
 - safety valve, 28-1
- Pressure relief valve, 28-1
- Pressure relief valve inlet pressure drop (the 3% rule), 28-7
- Pressure relief valve outlet pressure drop (the 10% rule), 28-7–28-8
- Pressure stress intensity factors, 20-5–20-6
- Pressure suppression containments, 16-8
- Pressure temperature ratings
 - flanges, 23-6
- Pressure-temperature requirements, 20-3
- Pressure Testing Requirements (Part 8, VIII-2), 24-13
- Pressure Vessel Design*, 9-30
- Pressure vessel fabrication, 16-9
- Pressure Vessel Research Council (PVRC), 5-7, 9-8, 9-32, 24-11
- Pressure vessels
 - with internal pressures of 15 psi and Less, 28-8
- Pressurized thermal shock (PTS), 20-2, 20-14
- Pressurized water reactors (PWRs), 15-22, 16-1, 16-4, 22-11, 25-2, 29-5
 - cracks in J-groove weld of PWR vessel heads, 25-2–25-3, 25-3f
 - generation III+. *See* Generation III+ PWR
 - LWR environments effect on fatigue life of components, 30-7, 30-8
 - mitigation capabilities enhancement, 30-2
 - nozzles, 19-11
- Pressurized water reactor (PWR) vessel alloy 600
 - alloy 82 and 182 weld metal, 21-3
 - alloy 600 base metals, 21-1–21-3
 - alternative life cycle management, 21-26–21-27
 - ASME BPVC reactor vessel inspection requirements, 21-11
 - augmented inspection requirements for alloy 82/182 dissimilar metal butt welds in PWR primary, 21-12–21-13
 - augmented inspection requirements for RPV BMI nozzles, 21-12
 - augmented inspection requirements for RPV top-head nozzles, 21-11–21-12
 - BMI penetrations, 21-3–21-4
 - boric acid wastage due to larger leaks, 21-14–21-15
 - butt welds, 21-4
 - core support attachments, 21-4
 - crack growth, 21-15–21-18
 - crack initiation, 21-15
 - degradation predictions, 21-15–21-20
- Figure 21.1 (Locations with Alloys 600/82/182 Materials in Typical PWR Vessel), 21-2
- Figure 21.2 (Typical Control Rod Drive Mechanism [CRDM] Nozzle), 21-3
- Figure 21.3 (Typical Bottom-Mounted Instrument [BMI] Nozzle), 21-4
- Figure 21.4 (Typical Reactor Vessel Inlet/Outlet Nozzle), 21-4
- Figure 21.5 (Typical Core Support LUG), 21-4
- Figure 21.6 (Alloy 600 Crack Growth Rate at 338° C Plotted vs. Hydrogen Concentration), 21-7
- Figure 21.7 (Typical Small Volume of Leakage from CRDM Nozzle), 21-7
- Figure 21.8 (Large Volume of Wastage on Davis-Besse Reactor Vessel Head), 21-8
- Figure 21.9 (Through-Wall Crack and Part-Depth Circumferential Crack in V.C. Summer Reactor Vessel Hot-Leg Outlet Nozzle), 21-9
- Figure 21.10 (Leak from South Texas 1 BMI Nozzle), 21-10
- Figure 21.11 (Schematic of RPV Top-Head Nozzle Geometry and Nature of Observed Cracking), 21-13
- Figure 21.12 (Plan and Cross-Section Through Corroded Part of Davis-Besse Reactor Vessel Head), 21-14
- Figure 21.13 (Cross-Section Through Davis-Besse Reactor Vessel Head), 21-15
- Figure 21.14 (Deterministic Crack Growth Rate Curves for Thick-Wall Alloy 600 Wrought Material and for Alloy 182/132 and Alloy 82 Weld Materials), 21-16
- Figure 21.15 (Log-Normal Fit to 19 Weld Factors for Screened MRP Database of CGR Data for Alloy 82/182/132), 21-17
- Figure 21.16 (Crack Growth Rate Predictions for Circumferential Crack in RPV Top-Head Nozzle at Various Assumed Operating Temperatures with Initial Crack Assumption = 30° Through-Wall Crack at Maximum Stress Azimuth in High Angle Nozzle), 21-17
- Figure 21.17 (Crack Growth Rate Predictions for Circumferential Cracks in RPV Main Coolant Loop Dissimilar Metal Nozzle Butt Weld at Operating Temperatures Typical of Reactor Inlet and Outlet Nozzles), 21-18
- Figure 21.18 (Probability of Nozzle Failure (NSC) as a Function of Variations in Top-Head Temperature and Inspection Intervals), 21-19
- Figure 21.19 (Probability of Nozzle Leakage as a Function of Variations in Top-Head Temperature and Inspection Intervals), 21-20
- Figure 21.20 (Pressurizer Dissimilar Metal Butt Weld Flaw Indications Compared to Critical Flaw Size Probability Estimates), 21-20
- Figure 21.21 (Schematic of RPV Top-Head Nozzle Flaw Embedment Repair), 21-21
- Figure 21.22 (Schematic of Weld Overlay Repair Applied to RPV Outlet Nozzle), 21-21
- Figure 21.23 (Schematic of RPV Top-Head Nozzle Weld Replacement Repair), 21-22
- Figure 21.24 (Half-Nozzle Repair Method Used for BLI Nozzle Repair), 21-23
- Figure 21.25 (Schematic of Mechanical Nozzle Seal Assembly Repair), 21-24
- Figure 21.26 (Typical Results of Strategic Planning Economic Analysis for RPV Head Nozzles), 21-27
- flaw embedment, 21-21
- flaw removal, 21-21
- head replacement, 21-26

- inspection methods and requirements, 21-10–21-13
 mechanical nozzle repair, 21-23–21-24
 miscellaneous alloy 600 parts, 21-4
 nondestructive examinations, 21-10–21-11
 operating experience, 21-6–21-10
 overview, 21-1
 piping weld inlay/on-lay, 21-22
 piping weld overlay, 21-21–21-22
 precursor PWSCC at RCS locations, 21-6
 primary water stress corrosion cracking (PWSCC), 21-5–21-6
 probabilistic analysis, 21-18–21-20
 remedial measures, 21-24–21-26
 repairs, 21-20–21-24
 risk of rupture assessment, 21-26
 risks of leaks, 21-26
 RPV bottom-head penetrations, 21-10
 RPV nozzle butt welds, 21-8–21-10
 RPV top-head penetrations, 21-3, 21-7–21-8
 rupture of critical size flaws, 21-13
 safety considerations, 21-13–21-15
 small leaks, 21-13
 strategic planning, 21-26–21-27
 stress improvement, 21-25–21-26
 surface treatment, 21-25
 Table 21.1 (Factors on Crack Initiation and Growth Time at Typical PWR Temperatures), 21-6
 Table 21.2 (Surface Cracking Indications in Reactor Coolant Loop Alloy 82/182 Butt Welds in US PWRs, Through 2012 [Largest Axial and Circumferential Indications Listed in Each Weld]), 21-9
 temperature reduction, 21-24
 visual inspections, 21-10
 water chemistry changes, 21-24
 weld or component replacement, 21-22–21-23
 Pressurized water reactor (PWR) vessel integrity
 aging management of PWR vessel internals, 20-15–20-18
 ASME BPVC Section XI, Appendix G, 20-3–20-7
 brittle fracture prevention, codes and regulations for, 20-2–20-8
 10 CFR 50, Appendix G, 20-2
 cracking at nozzle penetrations and dissimilar metal welds, 20-18–20-20
 Figure 20.1 (M_m Factor for Membrane Stress Intensity Factor from ASME Section XI, Appendix G), 20-4
 Figure 20.2 (M_t Factor vs. Thickness for Bending Stress Intensity Factor from ASME Section XI, Appendix G), 20-4
 Figure 20.3 (Linearized Representation of Stresses for Surface Flaws), 20-5
 Figure 20.4 (Examples of 50°F/hr. Cooldown Curves Using the Original and Revised Appendix G Stress Intensity Factor Methods), 20-6
 Figure 20.5 (Assumed Axial Flaws in Circumferential Welds), 20-7
 Figure 20.6 (Circumferential Flaws in Girth Welds), 20-7
 Figure 20.7 (Fixed LTOP Setpoint Affects Operating Window), 20-8
 Figure 20.8 (Charpy V-Notch Surveillance Data Showing RT_{NDT} Shift Due to Irradiation), 20-8
 Figure 20.9 (ASME Code K_{IC} and K_{IR} Toughness Curves), 20-9
 Figure 20.10 (Static Fracture Toughness Data (K_{IC}) Now Available, Compared to K_{IC}), 20-10
 Figure 20.11 (Original K_{IC} Reference Toughness Curve, with Supporting Data), 20-10
 Figure 20.12 (K_{IC} Reference Toughness Curve with Screened Data in the Lower Temperature Range), 20-10
 Figure 20.13 (Original ASME K_{IC} Data and New Variable T_{KIC-T}), 20-11
 Figure 20.14 (Original K_{IC} Toughness Data versus $T - T_0$), 20-12
 Figure 20.15 (Fracture Toughness Data Normalized to 1T and Compared to Code Case N-629 Curve), 20-12
 Figure 20.16 (Comparison of Residuals from ASTM E900-02 and Recent NRC Embrittlement Trend Curve Equations), 20-13
 Figure 20.17 (Estimates of Crack Initiation Compared to P-T Limits for Normal Cooldown Transient), 20-13
 Figure 20.18 (Relationship between Maximum Postulated Defect [ASME BPVC Section III] and Allowable Surface Indications [ASME BPVC Section XI]), 20-14
 Figure 20.19 (Framework for Implementation of Aging Management Using Inspections and Flaw Evaluation), 20-18
 Figure 20.20 (Examination Volume for Nozzle Base Metal and Examination Area for Weld and Nozzle Base Metal), 20-19
 LTOP setpoints, 20-7–20-8
 margin in P-T operating limit curves, 20-13–20-14
 overview, 20-1–20-2
 reference toughness curves, 20-8–20-13
 Section III, Appendix G and WRC 175, 20-2
 Section XI, Appendix G, improvement to, 20-14–20-15
 Pressurizer (PZR), 15-4, 15-15, 15-25
 Westinghouse SMR, 32-15
 Prestressed concrete containment vessel (PCCV), 15-28
 Preventative maintenance activities, 2-10
 PRHR. *See* Passive residual heat removal
 Primary creep, 17-12
 Primary loading, 19-18
 Primary stress, 17-3
 Primary Water Chemistry Guidelines, 21-24
 Primary water stress corrosion cracking (PWSCC), 20-19, 20-20, 22-6, 25-2, 27-2, 27-4, 30-20
 causes of, 21-5–21-6
 crack growth rate, 27-11
 description of, 21-5
 environment, 21-6
 material susceptibility, 21-5
 tensile stresses, 21-5–21-6
 Princeton University Plasma Physics Laboratory (website), 33-13
 PRISM reactor. *See* Power reactor innovative small module reactor
 Probabilistic analysis, degradation predictions, 21-18–21-20
 Probabilistic assessment, of operability, 7-16
 Probabilistic fracture mechanics (PFM), 19-7, 20-13, 21-18
 for inspection exemption, 19-6–19-8
 Probabilistic risk assessment (PRA), 15-4, 16-10, 17-11, 18-5. *See also* American Society of Mechanical Engineers (ASME) Probabilistic Risk Assessment (PRA) Standard
 applications
 fire protection licensing basis using NFPA 805, 29-5–29-6
 flexible AOT/completion times, 29-6
 in-service inspection, 29-5
 license renewal and cost/benefits evaluation in SAMA analyses, 29-6
 relief for nuclear plant technical specifications, 29-4–29-5
 risk informed treatment of missed surveillances, 29-6
 special treatment requirements (Graded QA), 29-6
 surveillance frequency control programs, 29-6
 background, 29-1
 decision analysis and, 29-2

- Probabilistic risk assessment (PRA) (*continued*)
- evolution, 29-1–29-2
 - flow chart for capability evaluation, 22-5f
 - history, 29-1
 - early nuclear PRAs, 29-2
 - insights from utility applications
 - Fire PRA methods, 29-7
 - Fukushima accident and, 29-6–29-7
 - graded QA and, 29-7
 - models, 29-7
 - new nuclear plant designs and, 29-7
 - public health risk from US nuclear plants and, 29-6
 - quality of applications, 29-7
 - risk informed technical specifications, 29-7
 - risk metrics and safety goals, 29-7
 - risk monitors, 29-6
 - seismic PRAs, Fukushima accident and, 29-7
 - socialization of, 29-7
 - techniques, plant availability and, 29-7
 - training and qualifications, 29-7
 - US nuclear plant regulation and, 29-6
 - overview, 29-2
 - peer reviews of, 22-6
 - PRA Standards and technical adequacy of
 - industry standards, 29-4
 - Regulatory Guides, 29-4
 - regulatory interface with nuclear plant, 29-2–29-3
 - design requirements, 29-3
 - evolution in concept of safety, 29-3
 - General Design Criteria (GDC), 29-3
 - maintenance rule a(4) and configuration risk management, 29-4
 - Mitigating Systems Performance Index, 29-4
 - NRC Policy Statement, 29-3–29-4
 - Reactor Oversight Process (ROP), 29-4
 - risk-informed analysis and, 22-1–22-23
 - ASME B&PV Section XI in-service inspection, 22-6–22-10
 - ASME B&PV Section XI repair and replacement, 22-11–22-15
 - ASME Operation & Maintenance (OM) Code, 22-15–22-19
 - ASME PRA Standard ASME/ANS RA-Sb-2013, 22-2–22-6
 - background, 22-1–22-2
 - future plans, 22-20–22-23
 - overview, 22-1
 - regulatory and industry interactions, 22-19–22-20
 - scenarios, 29-2
 - Probabilistic risk assessment (PRA) model
 - NuScale Power plants and, 32-8, 32-8f
 - Probabilistic safety analysis (PSA). *See* Probabilistic risk assessment
 - Probabilistic Seismic Hazard Assessments (PSHA), 30-5
 - Probability. *See also* Probabilistic risk assessment
 - evolution of concept, 29-1–29-2
 - Probability distributions, 20-13
 - Probability of core melt, 15-18
 - Probability of Exceedance (POE) methodology, 11-19
 - Process piping, ASME B31.3, 4-18
 - Programmed maintenance, 2-2. *See also* Maintenance Rule
 - Proof test, 6-5
 - Propagative flow, 8-8–8-10
 - Proposed Rule Making*, 10-2
 - Proton-proton reaction (PPI), 33-2–33-3, 33-3f
 - vs. deuterium–tritium fusion reaction, 33-3, 33-3f
 - Prototype, 6-5
 - PSD. *See* Power spectral density
 - PSHA. *See* Probabilistic Seismic Hazard Assessments
 - PT. *See* Penetrant testing
 - PTS. *See* Pressurized thermal shock
 - PULS (computer program), 6-2
 - Pulsation dampers, 3-15
 - PULSIM (computer program), 6-2
 - Pump-induced pressure pulsations, 3-5–3-7
 - Pumps, 15-4
 - failure modes for, 7-7
 - inservice test requirements for, 7-10
 - Figure 7.10 (Pumps Vibration Limits), 7-11
 - Table 7.6 (Inservice Test Parameters for Pumps), 7-10
 - Table 7.7 (Test Parameters Ranges for Pumps), 7-10
 - Table 7.8 (Test Parameters Ranges for Pumps), 7-11
 - operability evaluation, 7-13
 - visual inspection of, 7-14
 - PVRC. *See* Pressure Vessel Research Council
 - PVRC method, 9-8
 - PWHT. *See* Postweld heat treatment
 - PWR. *See* Pressurized water reactors
 - PWR Owners Group, 21-1
 - PWSCC. *See* Primary water stress corrosion cracking
 - QA. *See* Quality assurance
 - QAI-1–1995, 1-6, 1-18
 - QAI Committee. *See* Qualification for Authorized Inspection Committee
 - QAI Main Committee, 1-6
 - QSC. *See* Quality System Certificate
 - Quad Cities Unit 2 (QC2) plant, 30-15
 - Qualification for Authorized Inspection (QAI) Committee, 1-18, 1-19, 1-25
 - Quality assurance (QA)
 - nonmetallic materials, 26-11
 - Quality Assurance (QA) Program, 1-6–1-7
 - Quality assurance requirements for 10 CFR 71
 - 1977 final rule, 10-13
 - 1973 proposed rule, 10-12
 - Quality System Certificate (QSC), 1-15. *See also* Nuclear certification programs
 - “Quantifying and Controlling Risks,” 29-2
 - Quantitative risk assessment (QRA). *See* Probabilistic risk assessment
 - Radiation monitors, 16-15
 - Radioactive equipment, 15-28
 - Radioactive materials, 10-2
 - Radioactive materials, transportation of, U.S. regulations for. *See* U.S. transportation regulations for radioactive materials, development of
 - Radioactive sodium, 17-5
 - Radio building, Westinghouse SMR, 32-19
 - Radiographic and Ultrasonic Examination (UW-11, UW-12), VIII-1, 24-7–24-9
 - Radwaste building, 15-8
 - RAGAGEP (Recognized And Generally Accepted Good Engineering Practice) documents, 28-9
 - Rasmussen Report, 29-2
 - RCC-MR, 33-7
 - RCCV. *See* Reinforced concrete containment vessel
 - RCIC. *See* Reactor core isolation cooling
 - RCPs. *See* Reactor coolant pumps

- RCS. *See* Reactor coolant system
- Reaction-type dampeners, 3-7
- Reactor assembly, ESBWR, 16-10
- Reactor building (R/B), 15-12, 15-29
- Reactor building complex
 auxiliary building, 15-29
 power source buildings, 15-29
 reactor building, 15-29
- Reactor coolant loop (RCL), 15-29
- Reactor coolant pumps (RCP), 15-3, 15-9, 15-15, 15-22, 15-25, 32-20
- Reactor coolant system (RCS), 15-3, 15-6, 15-15, 20-15, 32-19, 32-20
 CRDM and driveline, 15-25
 fuel, 15-25
 incore instrumentation system, 15-25
 pressurizer, 15-25
 reactor coolant pumps, 15-25
 reactor internals, 15-25
 reactor pressure vessel, 15-25
 steam generators, 15-25
 thermocouple instrumentation, 15-25
- Reactor core, 15-14
- Reactor core isolation cooling (RCIC) system, 16-7
- Reactor Development & Technology (RDT) Standard, 17-3
- Reactor internals, 15-3, 15-25
- Reactor Internals Issue Task Group (RI-ITG), 20-15
- Reactor oversight process (ROP), 29-4, 30-4
- Reactor pressure boundary piping, BWR
 cracking, cause of, 19-16–19-17
 remedial/mitigation/repair measures, 19-17
 weld overlay repairs (WOR), 19-17–19-20
- Reactor pressure vessel (RPV), 15-3, 15-25, 16-16, 20-9
 BMI nozzles, 21-12
 bottom-head penetrations, 21-10
 indications in DOEL and Tihange NPP, 30-19
 and internal structures, 15-13–15-14
 nozzle butt welds, 21-8–21-10
 NPM, 32-2, 32-3
 top-head nozzles, 21-11–21-12
 top-head penetrations, 21-3, 21-7–21-8
- Reactor pressure vessel internals (RPVI), 15-14
- Reactor recirculation valves (RRVs), ECCS, 32-7
- Reactor Safety Study (RSS), 22-1, 29-2
- Reactor system design, 16-3–16-5
- Reactor vent valves (RVV), ECCS, 32-7
- Reactor vessel (RV), 15-25
 surveillance programs, 20-8
- Reciprocating pumps, 3-7
- Recirculation pumps, 16-7
- Rectangular flanges, 9-30
- Red book, 9-8
- Reference toughness curves
 alternative shift prediction method: E900 trend curves, 20-12–20-13
 initial RT_{NDT} and shift due to irradiation, 20-8–20-9
 K_{IC} versus K_{IR} reference toughness, 20-9–20-11
 master curve reference toughness, 20-11–20-12
- Refueling water storage pit (RWSP), 15-26, 15-27
 in-containment, 15-27
- Registered Professional Engineer (RPE), 1-5
 certification, 24-12
- Regulator, NuScale, 32-12
- Regulatory Guide 1.161, 19-15
- Regulatory Guide 1.177, 29-5
- Regulatory Guide 1.200, 29-6
 on technical adequacy of PRAs, 29-4, 29-5
- Regulatory Guide 1.207, 19-21
- Regulatory Guide 1.60 spectrum, 6-8
- Regulatory interface, nuclear plant PRAs and, 29-2–29-3
 design requirements, 29-3
 evolution in concept of safety, 29-3
 General Design Criteria (GDC), 29-3
 maintenance rule a(4) and configuration risk management, 29-4
 Mitigating Systems Performance Index, 29-4
 NRC Policy Statement, 29-3–29-4
 Reactor Oversight Process (ROP), 29-4
- Reinforced concrete containment vessel (RCCV), 16-9
- Reinspection Years (RIY), 21-12
- Reliability, 2-3. *See also* Maintenance Rule
- Reliability, US-APWR, 15-24
- Reliability Integrity Management (RIM) Program, 25-4
- Relief valve, 28-1
- Relief-valve discharge loads, 6-14
 closed discharge system and, 6-14
 computation of, 6-14
 open discharge system and, 6-14
- Remote in-vessel manipulator, ITER and, 33-11
- Repair programs, 1-7–1-8
- Repairs, cracking/leakage, 21-20–21-24
 flaw embedment, 21-21
 flaw removal, 21-21
 mechanical nozzle repair, 21-23–21-24
 piping weld inlay/on-lay, 21-22
 piping weld overlay, 21-21–21-22
 weld or component replacement, 21-22–21-23
- Request for additional information (RAI), 18-5
- Required input motion (RIM), 6-5
- Required response spectrum (RRS), 6-5
- Residual heat removal (RHR), 15-18, 16-7
- Residual heat removal system (RHRS), 15-15–15-16, 15-26
- Residual stress, 21-5, 21-25
- Residual stresses, in piping welds, 27-11–27-13, 27-11f
 current activities in ASME Section XI, 27-12–27-13
 finite element calculations, 27-12
 improvement, 27-12
- Resistive temperature devices (RTDs), 3-18
- Resonance frequency, 6-5
- Response spectra (RS) piping analysis, for calculating acceptable
 vibration limits, 3-29
- Response spectrum, 6-5
- Responsibilities and Duties (Part 2, VIII-2), 24-12
- Reverse flanges, 9-21–9-22
- Reversing dynamic loads, 14-4
- Revised ASME BPVC Section XI, Appendix C (2002 Addenda),
 19-19–19-20
- Revised Rules for Stress Multipliers* (ASME), 24-8
- Revised stress intensity factor, 20-5
- RFA design. *See* Robust Fuel Assembly design
- RHRS. *See* Residual heat removal system
- Rigid, 6-5
- Rigid range, 6-5
- RI-ISI. *See* Risk-informed in-service inspection
- RIM. *See* Required input motion
- RIM Program. *See* Reliability Integrity Management Program

- Ring-type gaskets, 9-2
- RIP-50 TG. *See* Risk-Informed Part 50 Task Group (RIP-50 TG)
- RISA (FE programs), 6-11
- Risk
 - defined, 29-1
 - evolution of concept, 29-1–29-2
- Risk-informed analysis
 - PRA and, 22-1–22-23
 - ASME B&PV Section XI in-service inspection, 22-6–22-10
 - ASME B&PV Section XI repair and replacement, 22-11–22-15
 - ASME Operation & Maintenance (OM) Code, 22-15–22-19
 - ASME PRA Standard ASME/ANS RA-Sb-2013, 22-2–22-6
 - background, 22-1–22-2
 - future plans, 22-20–22-23
 - overview, 22-1
 - regulatory and industry interactions, 22-19–22-20
- Risk-informed in-service inspection (RI-ISI), 22-2
- Risk-Informed Part 50 Task Group (RIP-50 TG), 22-20
- Risk informed treatment
 - of missed surveillances, PRAs and, 29-6
- Risk Management Strategic Plan (BNCS), 22-20, 22-22
- “Risk triplet,” 29-1
- RIY. *See* Reinspection Years
- Robust Fuel Assembly (RFA) design
 - Westinghouse SMR, 32-13, 32-18, 32-18f
- Rock, 6-5
- Rod cluster control assemblies (RCCA), 15-14
- Roofing systems, temporary, 12-7
- ROP. *See* Reactor oversight process
- Rowley, C. Wesley, 22-1
- RPE. *See* Registered Professional Engineer
- RPE (Registered Professional Engineer) certification, 24-12
- RPV. *See* Reactor pressure vessel
- RRS. *See* Required response spectrum
- RRVs. *See* Reactor recirculation valves
- RSTRENG approach, 11-30
- RTDs. *See* Resistive temperature devices
- RT_{NDR} . *See* Nil-ductility reference temperature index
- Ruggedness, 6-5
- Rule 10 CFR 54.4, 18-4
- Rupture disk certification, 28-3
- 2009 Russian Dam Accident, 31-3
- Russo, J. Edward, 29-2
- RVV. *See* Reactor vent valves, ECCS
- RWSP. *See* Refueling water storage pit

- Safe end material, 19-16
- Safeguard buildings, 15-12–15-13
- Safe shutdown earthquake (SSE), 6-5, 14-2, 15-28
 - ground motion, 14-1. *See also* Seismic hazard
- Safety
 - evolution in concept of, PRAs and, 29-3
- Safety and security
 - NuScale Power plants, 32-15
 - DHRS, 32-6, 32-6f
 - ECCS, 32-6f–32-7f, 32-7
 - high pressure CV, 32-5–32-6
 - passive safety systems (elimination of LOCA), 32-6
 - Westinghouse SMR, 32-14, 32-19–32-20, 32-20f
- Safety considerations
 - ITER, 33-11–33-12
 - Safety considerations, PWSCC cracks and leak
 - boric acid wastage for larger leaks, 21-14–21-15
 - leaks, small, 21-13
 - rupture of critical size flaws, 21-13
- Safety evaluation (SE), 19-3
 - of PRISM reactor, 17-8
- Safety evaluation report (SER), 18-5
 - NUREG-0968, 17-4, 17-5
- Safety factor, brittle fracture prevention, 20-3
- Safety features, AP1000 plant, 15-4–15-7
 - containment isolation, 15-6
 - fission product release, 15-7
 - in-vessel retention of core damage, 15-7
 - main control room emergency habitability system, 15-6
 - passive containment cooling system, 15-6
 - passive core cooling system (PXS), 15-5–15-6
 - passive residual heat removal (PRHR) system, 15-6
 - passive safety-related systems, 15-5
- Safety features in US-APWR, 15-25–15-28
 - advanced accumulator system, 15-26
 - combustible gas control, 15-27–15-28
 - containment spray system, 15-26
 - core debris cooling under severe accident conditions, 15-27
 - electrical power system, 15-26
 - elimination of low-head safety injection system, 15-26
 - four electrical trains, 15-26
 - four mechanical trains, 15-26
 - full digital I&C, 15-27
 - gas turbine generator, 15-26
 - in-containment refueling water storage pit, 15-27
 - main control room emergency habitability system, 15-27
 - safety injection system, 15-26
- Safety functions, for SSCs, 7-1. *See also* Operability and functionality
 - piping, 7-1
 - supports, 7-1
 - valves, 7-1
- Safety injection, 15-18
- Safety injection pump (SIP), 15-25, 15-26
- Safety injection system, 15-26
- Safety injection system/residual heat removal system (SIS/RHRS), 15-15–15-16
- Safety/relief valves (SRV), 8-4, 16-9, 28-1
- Safety reviews, license renewal process. *See also* License renewal and aging management
 - integrated plan assessment, 18-2–18-3
 - principles and process, 18-2
 - time limited aging analysis (TLAA), 18-3
- Safety system
 - design of, 16-5–16-7
 - ESBWR, 16-11
- Safety valve, 28-1
- SAM. *See* Seismic anchor motion
- SAMGs. *See* Severe accident management guidelines
- SAR. *See* Synthetic aperture radar
- Satellite surveillance, 11-50–11-52
- SAW. *See* Submerged arc welds
- SBLOCA. *See* Small break loss-of-coolant accidents
- SBWR. *See* Simplified boiling water reactor
- SCADA. *See* Supervisory Control and Acquisition Data
- SCC. *See* Stress corrosion cracking
- Schoemaker, Paul J. H., 29-2

- SCI PG-20, 26-2
- SCNA. *See* Subcommittee on Nuclear Accreditation
- Scoping, LRA, 18-4, 18-5
- Screening, LRA, 18-4, 18-5
- Scum busting nozzle, 6-16
- SDF system. *See* Single-degree-of-freedom system
- SDOs. *See* Standards Developing Organizations
- Secondary missiles, 6-18. *See also* Missiles
- Secondary stress, 17-3
- Section III (ASME), 25-1
- Section III, Nuclear Vessels, 1-2, 1-3
- Class A rules, 1-3
 - Class B rules, 1-3
 - Class C rules, 1-3
- Section III, Subsection NH, "Class 1" components in elevated temperature service, 17-11–17-12
- Section VIII, Division 1, 1-3
- Section VIII, Division 1 (Rules for Construction of Pressure Vessels)
- common rules
 - ASME Code Case 2695, 24-9
 - background, 24-9
 - design rules, 24-3
 - VIII-1 vs. VIII-2 design rules, 24-3, 24-4t, 24-15
 - document size, 24-2
 - example problems
 - Appendix L, 24-9
 - ASME PTB-4-2013, 24-9–24-10
 - Mandatory appendices, 24-2
 - Non-Mandatory appendices, 24-2
 - overview, 24-1
 - scope of vessels, 24-2
 - technical background of code rules, 24-9
 - technical issues
 - design procedure for combined loading, 24-3–24-4
 - ellipsoidal and torispherical head rules, 24-6
 - low temperature operation (UCS-66), 24-6–24-7
 - nozzle reinforcement rules, 24-4–24-6
 - radiographic and ultrasonic examination (UW-11, UW-12), 24-7–24-9
 - U-2(g) clause, over-use of, 24-2
 - writing style and organization, 24-2
- Section VIII, Division 2, 1-3
- Section VIII, Division 2 (Alternative Rules for Pressure Vessels)
- ASME PTB-1-2009 *ASME Section VIII Division 2 Criteria and Commentary*, 24-21
 - beta testing, 24-13–24-14
 - beta test results, 24-14, 24-15t, 24-16t
 - common rules
 - ASME Pressure Vessel Code Case 2695, 24-18
 - overview, 24-14–24-15
 - VIII-2 Committee decision, 24-18–24-19
 - VIII-1 vs. VIII-2 design rules, 24-3, 24-4t, 24-15
 - design validation, 24-13
 - development objectives, 24-11
 - development process, 24-11
 - document format, 24-20–24-21
 - example problems, 24-21
 - organization of, 24-11–24-12
 - Part 1 (General Requirements), 24-12
 - Part 2 (Responsibilities and Duties), 24-12
 - Part 3 (Material Requirements), 24-12
 - Part 4 (Design-By-Rule Requirements), 24-12
 - Part 5 (Design-By-Analysis Requirements), 24-12–24-13
 - Part 6 (Fabrication Requirements), 24-13
 - Part 7 (Examination Requirements), 24-13
 - Part 8 (Pressure Testing Requirements), 24-13
 - Part 9 (Overpressure Protection), 24-13
 - overview, 24-11
 - use in new construction, 24-12
- Section XI (flaw Acceptance Standards development and analytical evaluation procedures)
- flaw evaluation procedures
 - analytical procedures and acceptance criteria for planar flaws, 27-3–27-4
 - steps for, 27-2–27-3
 - structure of, 27-3
 - flaws evaluation in buried metallic pipe, 27-15–27-19
 - Acceptance Standards for metal loss, 27-17
 - level 2 analytical evaluation method, 27-17–27-19
 - metal loss characterization, 27-16–27-17
 - overview, 27-16
 - IWA-3300, 27-2
 - IWB-3514, 27-3
 - IWB-3600, 27-3
 - IWB-3640, 27-3
 - IWB-3642, 27-3
 - IWB-3643, 27-3
 - overview, 27-1–27-2
 - revised acceptance criteria for flaws in piping for design intent margins maintenance, 27-6
 - for circumferential flaws for limit load prior to 2002 Addenda, 27-8
 - for circumferential flaws in 2002 Addenda, 27-9–27-11
 - plastic collapse equations for circumferential flaws and ASME Section III Primary Stress Limits, 27-7–27-8
 - structural factors specific to each service level in 2002 Addenda, 27-8–27-9
 - revisions to flaw Acceptance Standards, 27-4–27-6
 - for consistency improvement, 27-5
 - for materials susceptible to stress corrosion cracking, 27-5–27-6
 - stress corrosion cracking in nuclear piping items, 27-4
 - stress corrosion cracking in piping items (developments)
 - crack growth rates, 27-11
 - structural integrity evaluation of dissimilar metal welds based on EPFM, 27-13
 - weld residual stresses, 27-11–27-13
 - temporary acceptance of flaws in moderate energy classes 2 and 3 piping (evaluation procedures and acceptance criteria), 27-15
 - transition temperatures for onset of upper shelf behavior in ferritic piping, 27-13–27-14
 - wall thinning in piping (evaluation procedures and acceptance criteria)
 - Code Case N-597-2 (overview), 27-14
 - Code Case N-597-2, activities to address NRC conditions on, 27-14–27-15
 - Code Case N-597-2, NRC conditions on, 27-14
- Section XI (in-service inspection)
- Code Cases
 - and Code Rules development, 22-7
 - N-560, 22-8
 - N-577, 22-8–22-9
 - N-578, 22-9–22-10
 - N-711, 22-10

- Section XI (in-service inspection) (*continued*)
 - N-716, 22-10
 - N-747, 22-10
 - Nonmandatory Appendix R, 22-10
 - overview, 22-6–22-7
- Section XI (Inservice Inspection of Nuclear Reactor Coolant Systems), 25-1
 - lessons learned from operating experience, 25-1–25-5
 - construction repairs, 25-4–25-5
 - globalization efforts, 25-1
 - IGSCC, 25-2
 - J-groove weld of PWR vessel heads, cracks in, 25-2–25-3, 25-3f
 - knowledge and younger engineers, 25-3
 - NDE advancement, 25-5
 - new designs of reactors, 25-1–25-2
 - PWSCC, 25-2
 - RIM Program development, 25-4
 - system based code development, 25-3–25-4
- Section XI (Repair and Replacement)
 - background on risk-informed regulation initiative, 22-11
 - Code Case N-660, 22-12–22-13
 - consequence ranking methodology, 22-12
 - Code Case N-662, 22-13–22-15
 - alternative provisions, 22-14
 - IWA-4130 Alternative Requirements, 22-14
 - IWA-4120 Applicability, 22-14
 - IWA-4300 Design, 22-15
 - IWA-4180 Documentation, 22-14
 - IWA 4500 Examination and Test, 22-15
 - IWA-4170 Inspection, 22-14
 - IWA-4200 Items Used for Repair/Replacement Activities, 22-14–22-15
 - IWA-4150 Repair/Replacement Program, 22-14
 - IWA-4140 Responsibilities, 22-14
 - IWA-4110 Scope, 22-14
 - IWA-4400 Welding, Brazing, Defect Removal, and Installation, 22-15
 - Code Cases, scope of, 22-11–22-12
- Section XI, Inservice Inspection, 1-7
- Section XI code (Rules for Inservice Inspection of Nuclear Power Plant Components), 25-1
- Section XI Committee, 19-2
- Section XI Division 2 (Rules for Inspection and Testing of Components of Gas-Cooled Plants), 25-2
- SECY-98-300 NRC paper, 22-11
- Seismic anchor motion (SAM), 14-2, 14-6
- Seismic Category I, 6-5
- Seismic hazard, 14-1–14-2
- Seismic II/I piping system protection, 14-6
- Seismic loading input, 14-3
- Seismic loads, 17-6
- Seismic margin assessments (SMA), 14-2
- Seismic/non-seismic interface, 14-6
- Seismic PRA
 - Fukushima accident and, 29-7
- Seismic Probabilistic Risk Analysis (SPRA), 30-5
- Seismic protection of pressure piping systems
 - alternate seismic rules (new), 14-4
 - boundary conditions, 14-3
 - code Class 2 and Class 3 piping, 14-5–14-6
 - code Class 1 piping, 14-4–14-5
 - damping, 14-3–14-4
 - geometric/material properties, 14-3
 - geometry of piping system, 14-3
 - overview, 14-1
 - piping systems, seismic analysis of, 14-2–14-6
 - seismic anchor motion (SAM) analysis, 14-6
 - seismic hazard, 14-1–14-2
 - seismic II/I piping system protection, 14-6
 - seismic loading input, 14-3
 - seismic/non-seismic interface, 14-6
- Seismic stress ratcheting, 14-1
- Sellers, Craig D., 22-1
- SER. *See* Safety evaluation report
- Service issues, PRDs and, 28-4
- Service Level A, 6-5
- Service Level B, 6-5
- Service Level C, 6-5
- Service Level D, 6-5
- Service water system (SWS), 15-7
- Severe accident management guidelines (SAMGs), 30-3
- Shaw, K. R., 28-3
- SHE. *See* Standard hydrogen electrode
- Shear layer instability response time, 8-12
- Shear stress dyadic, 8-12
- Shell-mode vibration, 3-30–3-31
- Shielded metal arc welding (SMAW), 21-3
- Shielded metal arc welds (SMAW), 27-4
- Shippingport Atomic Power Plant (Pennsylvania), 29-2, 29-3
- Shock reflection
 - bubbly liquid mixture and, 8-26–8-27
 - Figure 8.31 (Moving Normal Shock in Flow Passage), 8-23
 - Figure 8.32 (Shock Reflecting from Flexible Interface), 8-24
 - Figure 8.33 (Reflected Shock, Rigid Surface), 8-24
 - Figure 8.34 (Shock Reflecting from Slightly Compressible Fluid), 8-24
 - Figure 8.35 (Reflected and Transmitted Shock Pressure at Air/Water Interface), 8-25
 - Figure 8.36 (Transmitted and Reflected Shock Pressure, Bubbly Mixture), 8-27
 - Figure 8.37 (Bubble Mixture Density Behind Shock), 8-27
 - Figure 8.38 (Bubbly Mixture Velocity Behind Transmitted Shock), 8-27
 - Figure 8.39 (Transmitted Shock Speed in Bubbly Mixture), 8-27
 - Figure 8.40 (Sound Speed in Bubbly Mixture Behind Transmitted Shock), 8-27
 - flexible interface and, 8-23–8-24
 - at interface of bubbly liquid, 8-22–8-27
 - moving shock in perfect gas, 8-23
 - nomenclature related to, 8-22–8-23
 - normal shock moving, 8-23
 - and observations, 8-27
 - rigid interface and, 8-24
 - shock transmission at pure liquid interface, 8-24–8-26
 - Table 8.1 (Example Properties, Undisturbed Air and Water), 8-26
- Short-term operability acceptance criteria, 7-14
 - on ASME Section III, Appendix F, 7-14
 - for piping, 7-14
 - for supports, 7-14–7-16
- Shrinkage stresses, 19-18
- Shrink sleeve, 11-43–11-44
- Shroud, 19-1–19-4
 - evaluation with multiple indications, 19-3–19-4
 - inspection uncertainty, 19-3

- irradiated stainless steel fracture toughness, 19-3
- repair/replacement, 19-4
- SCC growth rate relationships, 19-2–19-3
- Simonen, Fredric A., 22-1
- Simple-beam analogy
 - for allowable deflection limits, 3-27
 - for allowable vibration limit, 3-25, 3-29
- Simplified analysis method, 17-3
- Simplified boiling water reactor (SBWR), 16-2, 16-3
- Simplified design analysis methods, 17-12
- Sine beat, 6-5
- Single-degree-of-freedom (SDF) system, 3-12
- SIP. *See* Safety injection pump
- SIS/RHRS. *See* Safety injection system/residual heat removal system
- SLCS. *See* Standby liquid control system
- Sleeve repairs, 11-35–11-36
- Slip-on flanges, 9-16
- Slosh guard, 16-12
- Slug flow, 6-5
- SMA. *See* Seismic margin assessments
- Small break loss-of-coolant accidents (SBLOCA), 32-5, 32-9
- ‘Small form’ of licensed material, 10-3
- Small modular reactors (SMR), 25-4
 - NuScale approach to deployment of, 32-2, 32-2f
 - Westinghouse SMR. *See* Westinghouse Small Modular Reactor
- Small-tap lines, 3-15
- SMAW. *See* Shielded metal arc welding; Shielded metal arc welds
- SMRs. *See* Small modular reactors
- Snapshot recording, 3-17
- Snubbers, 7-6, 14-3
 - inservice test requirements for, 7-10
 - short-term operability acceptance criteria for, 7-15–7-16
 - vibration-limiting effects of, 3-22–3-23
- Socialization, of PRAs, 29-7
- Socket-welding, 23-6
 - flanges, 9-16, 9-18, 23-5
- Sodium tetraborate decahydrate (NaTB), 15-26
- Soil-structure interaction (SSI), 15-29
- Solution heat treatment (SHT), 19-17
- South Texas Project (STP), 29-6
- Southwest Research Institute, 3-25
- Sparger design configuration, 19-11
- Special Working Group (SWG), 24-7
- Specification packages, 10-2
- Spectacle flanges, 16-13
- Spectrum-consistent time history, 6-5
- Spent fuel pools, 15-16
 - makeup capability and instrumentation enhancement (NRC Task Force recommendation 7), 30-3
 - mitigation capabilities enhancement, 30-2
- Split-ring flanges, 9-24
- SPRA. *See* Seismic Probabilistic Risk Analysis
- Spring back, 11-28
- Spring hangers, 7-15
- Squib-type valves, 16-12
- SRP-LR. *See* Standard review plan for license renewal
- SRV. *See* Safety/relief valves
- SSCs. *See* Structure, system, or component
- SSE. *See* Safe shutdown earthquake
- SSI. *See* Soil-structure interaction
- SSSI. *See* Structure soil-structure interaction
- STAAD (FE programs), 6-11
- Stainless steel
 - chromium-nickel-molybdenum, 15-14
 - low-Carbon chromium-nickel, 15-14
- Standard, defined, 23-2
- Standard drag force, 8-10, 8-11
- Standard hydrogen electrode (SHE), 16-18
- Standard plant design, 17-8
- Standard review plan for license renewal (SRP-LR), 18-8–18-9
 - administrative information, 18-9
 - Branch Technical Position RLSB-1, 18-9
 - GALL Report, 18-9
 - Subsection 1, 18-9
 - Subsection 2, 18-9
 - Subsection 3, 18-9
 - Subsection 4, 18-9
 - Subsection 5, 18-9
- Standard Review Plan for Review of License Renewal Applications for Nuclear Power Plants, 20-16
- Standards Developing Organizations (SDOs), 22-22
- Standby liquid control system (SLCS), 16-14. *See also* Passive safety features, BWR
 - ESBWR, 16-14
- Standby system, 2-3. *See also* Maintenance Rule
- Standstill seal, 15-15
- Station Blackout (SBO), 15-18
 - Emergency Preparedness (EP) enhancements, 30-3–30-4
 - mitigation capability enhancement (NRC Task Force recommendation 5), 30-2–30-3
- Steady-state vibrations, 3-1, 6-5. *See also* Piping vibration
- Steam dryers, 16-1, 19-6
- Steam-dryer-support-bracket cracking, 19-14–19-15
- Steam Generator Blowdown System, 15-16
- Steam generator(s) (SG), 15-3, 15-14–15-15, 15-22, 15-25
 - Westinghouse SMR, 32-15, 32-16–32-17, 32-17f
- Steam generator tube leaks, 30-19–30-20
 - root cause analysis, 30-19
- Steam generator tube sheet evaluation, 17-5–17-6
- Steam hammer, piping failure and, 31-3
- Steam supply line, 16-15
- Steel containment, 15-8
- Strain concentration factors, 5-2
- Strain-controlled fatigue data, 5-1–5-2
- Strain rate, 5-18, 5-21
- Strain theory, 17-3
- Strategic planning process, leakage risks
 - alternative life cycle management approaches, 21-26–21-27
 - boric acid wastage, 21-26
 - leaks, risk assessment, 21-26
 - predicting time to PWSCC, 21-26
 - risk of nozzle ejection, 21-26
- Stress, 14-5, 14-6
 - categories, 17-3
 - distribution, 19-18
 - improvement, 19-17, 21-25–21-26
 - relaxation, 481
- Stress-based FMP, 18-7, 18-8
- Stress concentration factors, 5-2
- Stress corrosion, 17-8
- Stress corrosion cracking (SCC), 7-3, 16-17, 17-8, 20-17, 21-2
 - crack growth rate relationships for, 19-22–19-24
 - flaw Acceptance Standards revisions for materials susceptible to, 27-5

- Stress corrosion cracking (SCC) (*continued*)
- BWR environment, 27-5–27-6
 - PWR environment, 27-6
 - growth rate relationships, 19-2–19-3
 - in nuclear piping items, 27-4
 - in piping items (recent developments)
 - crack growth rates, 27-11
 - structural integrity evaluation of dissimilar metal welds based on EPFM, 27-13
 - weld residual stresses, 27-11–27-13
- Stress indices, 4-6. *See also* Flexibility factors
- C_1 and K_1 for internal pressure loading, 4-6–4-9
 - butt-welding tees, 4-8–4-9
 - elbows, 4-8
 - C_2 and K_2 for moment loading, 4-9
 - definition of, 4-6
 - in Table NB-3338.2(c)-1, 4-6, 4-7
 - for thermal gradient loadings, 4-9–4-11
- Stress intensification factors, 4-1, 4-2. *See also* Flexibility factors
- ASME ST-LLC 07-02, 4-6
 - in B31.1 and B31.3, 4-18
 - Code guidance for, 4-4–4-5
 - design margin, 4-3–4-4
 - EPRI reports, 4-5–4-6
 - Figure 4.1 (Markl-Type Fatigue Tests and Illustration of Limit Load Criterion), 4-2
 - Figure 4.2 (Design Margins for SA106 GRADE B), 4-4
 - Figure 4.3 (Test Data from Hinnant), 4-5
 - Figure 4.4 (Example Piping System), 4-6
 - Figure 4.5 (In-Plane Stress Intensification Factor), 4-7
 - Figure 4.6 (Out-of-Plane Stress Intensification Factors), 4-8
 - girth butt weld and, 4-3
 - Markl tests and, 4-3
 - terminology and symbols related to, 4-1–4-2
- Stress intensification factors (SIF), 20-5, 21-17, 31-5
- revised, 20-5
- Strouhal number, 3-8
- Structural bolts, 7-15
- Structural integrity, 6-5
- Structural integrity evaluation
- localized areas, detailed analysis of, 17-3–17-4
 - materials representations, 17-3
 - models and tests, 17-4
 - modes of failure, 17-3
 - simplified analysis method, 17-3
 - stress categories, 17-3
- Structural integrity licensing concerns
- creep fatigue evaluation, 17-6–17-7
 - elastic follow-up in piping, 17-6
 - elevated temperature seismic effects, 17-6
 - inelastic analysis, material property representation for, 17-5
 - intermediate piping transition weld, 17-7
 - notch weakening, 17-4–17-5
 - plastic strain concentration factors, 17-7
 - steam generator tube sheet evaluation, 17-5–17-6
 - weldment cracking, 17-4
- Structural integrity of welds, 17-11–17-12
- Structure, 6-5
- Structures, systems, and components (SSC), 2-1, 6-2, 7-1, 29-3. *See also* Maintenance Rule
- design bases for, 14-1, 14-2
 - non-safety-related, 2-4, 2-5
 - risk-significant, 2-3
 - safety-related, 2-4
 - US-APWR safety-related, 15-28
- Structures and components (SC)
- long-lived, 18-4
 - passive, 18-4
- Structure soil-structure interaction (SSSI), 15-29
- Structure-to-electrolyte resistance, 11-47
- Stub tube
- cracking, 19-12–19-13
 - roll expansion repair, 19-12
- Stuxnet malware, 11-53
- Subcommittee B Threaded Fittings (Except Steel), Flanges and Flanged Fittings (ASME B16 Standard), 23-2, 23-4, 23-5t
- B16.1, 23-4
 - B16.4, 23-4
 - B16.5, 23-4
 - B16.42, 23-4
 - B16.45, 23-4
- Subcommittee C Steel Flanges and Flanged Fittings (ASME B16 Standard), 23-2, 23-5–23-6, 23-5t
- B16.5, 23-5–23-6
 - B16.36, 23-6
 - B16.47, 23-6
 - B16.48, 23-6
- Subcommittee F Steel Threaded and Welding Fittings (ASME B16 Standard), 23-2, 23-6–23-7, 23-7t
- B16.7, 23-7
 - B16.9, 23-7
 - B16.11, 23-6
 - B16.25, 23-6–23-7
 - B16.49, 23-7
 - B16.53, 23-7
- corrosion protection and, 23-6
- Subcommittee G Gaskets for Flanged Joints (ASME B16 Standard), 23-2, 23-7, 23-7t
- Subcommittee G (Gaskets for Flanged Joints)
- B16.20, 23-7
 - B16.21, 23-7
- Subcommittee J Copper and Copper Alloy Flanges, Flanged Fittings and Solder Joint Fittings (ASME B16 Standard), 23-2, 23-7, 23-8t
- Subcommittee L Gas Shutoffs and Valves (ASME B16 Standard), 23-2, 23-8, 23-8t
- Subcommittee N Steel Valves and Face to Face and End to End Dimensions of Valves (ASME B16 Standard), 23-2, 23-8–23-9, 23-9t
- B16.5, 23-9
 - B16.10, 23-8
 - B16.34, 23-9
 - B16.36, 23-9
 - B16.47, 23-9
- Subcommittee on Design (SC-D), 17-12, 17-13
- Subcommittee on Materials (SC-II), 17-12
- Subcommittee on Nondestructive Examination (SC-V), 17-12
- Subcommittee on Nuclear Accreditation (SCNA), 1-15
- Subcommittee on Nuclear Power (SC-III), 17-12
- Subcommittee on Pressure Vessels (SC-VIII), 17-12
- Subcommittee on Welding (SC-IX), 17-12
- Subcriticality, 16-14
- Subgroup of SC XI, 19-1

- Subgroup on Elevated Temperature Design, 17-12
- Subgroup on Fatigue Strength, 16-19
- Submerged arc welds (SAW), 27-4
- Submerged structures, fluid forces on, 8-10–8-11
- Subscale tests, 8-11–8-12. *See also* Fluid-structure interaction
- Subsection NH, 17-2, 17-8, 17-9, 17-11, 17-12
- Subsections NB, 17-8, 17-9
 - in Section III, 19-1
- Superimposed backpressure, 28-7
- Supervisory Control and Acquisition Data (SCADA), 11-49
- Supply chain, NuScale, 32-12
- Supporting requirements (SRs), PRAs and, 22-6
- Supports
 - failures, 7-6
 - Figure 7.8 (Standard Support Failures by Failure Mode), 7-6
 - Figure 7.9 (Standard Support Failures by Root Cause), 7-7
 - operability evaluation methods, 7-12–7-13
 - visual inspection of, 7-14
- Supports, short-term operability acceptance criteria for, 7-14–7-15
 - component standard supports, 7-15
 - concrete expansion anchors, 7-15
 - integral welded attachments, 7-15
 - linear-type supports, 7-15
 - snubbers, 7-15–7-16
 - spring hangers, 7-15
 - structural bolts, 7-15
- Surface treatment, 21-25
- Surge line routing, 15-15
- Surry Power Station, 31-4
- Surveillance frequency control programs, PRAs and, 29-6
- SWS. *See* Service water system
- Synthetic aperture radar (SAR), 11-50–11-52
- Synthetic time history, 6-5
- System, 6-5
- System based code development, 25-3–25-4
- Systems, structures, and components (SSC), 18-4
- Systems-Based Code, development of, 22-21–22-22

- Taiwan Power Company (TPC), 16-2
- Tanks, operability evaluation, 7-13
- Taper-hub flanges, 9-8
- Taylor Forge method, 9-30
- TCWS. *See* Tokamak cooling water system
- Technical Bases for Revision to the License Renewal Guidance Documents (NUREG-1833), 18-9
- Technical issues safety research needs, June 2006, NGNP, 17-10
- Technical specifications (TSs), 7-1–7-2. *See also* Operability and functionality
- Teflon expansion joints, 31-2t
- Temperature, 21-6
 - indexing, 20-2
 - reduction, 21-24
- TENPES. *See* Thermal and Nuclear Power Engineering Society
- Tensile stresses, 21-5–21-6
- Terminal end, 6-5–6-6
- Terrestrial-scale fusion, 33-2–33-4. *See also* Fusion
 - power production theories, 33-4
- Tertiary creep behavior, 17-11
- Test programs, NuScale Power, 32-8–32-9, 32-9f
- Test response spectrum (TRS), 6-6
- TF coils. *See* Toroidal field coils
- TFI. *See* Transverse field inspection

- TG-CSEF Steels, 26-2
- Theory of Special Relativity* (1905), 33-2
- Thermal aging embrittlement, 20-17
- Thermal and Nuclear Power Engineering Society (TENPES), 19-21
- Thermal expansion, 14-3
- Thermal gradient loadings, stress indices for, 4-9–4-11
- Thermal gradient stress
 - indices, 4-10
 - polyethylene piping, 30-11–30-12
- Thermal loading, 20-4
- Thermal shield, ITER, 33-9
- Thermal shock, 6-14
- Thermal stress, 14-4
- Thermal stress intensity factor (K_t), 20-5, 20-6
- Thermocouple instrumentation, 15-4, 15-25
- Thermoplastic materials, 26-5–26-6
 - components, 26-7
 - fabrication process, 26-11
 - joining of components (and subcomponents), 26-8, 26-9f
- Thermoset plastic materials, 26-6
 - components, 26-6, 26-7–26-8
 - fabrication process, 26-11
 - secondary bonding and joining, 26-9, 26-9f–26-10f
- Threaded flanges, 23-5
- Three Mile Island (TMI) accident, 22-1, 29-2, 29-3, 32-9
- The 3% rule (pressure relief valve inlet pressure drop), 28-7
- The 10% rule (pressure relief valve outlet pressure drop), 28-7–28-8
- Through-wall bending effects, 7-13
- TI 2515/173, “Review of the Implementation of the Industry Groundwater Protection Voluntary Initiative,” 30-11
- TIG. *See* Tungsten inert gas
- Tightness-based design, flange joints, 9-32
 - Figure 9.15 (Gasket Stress *versus* Tightness Parameter), 9-33
 - new ASME flange design rules, 9-33–9-34
 - Pressure Vessel Research Council (PVRC) approach, 9-32–9-33
 - Table 9.6 (Tightness Factors for Service Class), 9-33
 - Table 9.7 (Assembly Efficiency), 9-34
- Tihange-2 NPP, RPV indications in, 30-19
- Time limited aging analysis (TLAA), 18-3. *See also* License renewal and aging management
 - criteria for, 18-3
 - defined, 18-3
 - license renewal review process, 18-3
 - metal fatigue, 18-6–18-8
- Title 10, Code of Federal Regulations, Part 71 (10 CFR 71), 10-1–10-6.
 - See also* U.S. transportation regulations for radioactive materials, development of
- TLAA. *See* Time limited aging analysis
- TMDL. *See* Total maximum daily load
- Tokamak concept, 1-32
- Tokamak cooling water system (TCWS), 33-10
- Tokyo Electric Power Company (TEPCO), 16-2
- Torispherical head rules, of VIII-1, 24-6
- Toroidal field (TF) coils, ITER, 33-5–33-7, 33-7f
- “Total integrity,” 25-4
- Total maximum daily load (TMDL), 12-4
- Total system or component damping, 6-11. *See also* Damping
- Training and qualifications, PRA, 29-7
- TransAdriatic Pipeline, 11-2
- Trans-Alaska pipeline, 11-52
- Transfer function, 6-6
- Transient vibrations, 6-6

- Transition temperatures
 - for onset of upper-shelf behavior in ferritic piping, 27-13–27-14
- Transportation of Explosives and other Dangerous Articles Act, 10-3
- Transportation Security Administration (TSA), 11-54
- Transverse field inspection (TFI), 11-19
- Triaxial-input excitations, 6-10
- Triaxial stress limits, 9-4
- Tritium (hydrogen-3), 33-1, 33-3
- TSA. *See* Transportation Security Administration
- TSs. *See* Technical specifications
- TSTF-505 Rev 1, 29-6
- Tungsten inert gas (TIG), 21-3
- Turbine building (T/B), 15-8, 15-13, 15-29
- Turbine island, Westinghouse SMR, 32-19
 - balance of plant design, 32-19
- 12-unit NuScale power plant. *See also* NuScale Power Module
 - characteristics, 32-5t
 - concept for, 32-5, 32-5f
 - “in-line refueling,” 32-4–32-5
 - site layout for, 32-4–32-5, 32-4f
- U-1(c)(2)(h)(1) (Vessels Not Exceeding the Design Pressure of 15 psig), 28-6
- UFSAR. *See* Updated Final Safety Analysis Report
- UG-11, 24-7–24-9
- UG-12, 24-7–24-9
- UG-22, 24-3
- UG-32, 24-6
- UG-37, 24-4, 24-5
- UG-140 (Overpressure Protection by System Design), 28-6, 28-8
 - Non-Self-Limiting (UG-140[b]), 28-7
 - Self-Limiting (UG-140[a]), 28-6
- U-2(g) clause, over-use of, 24-3
- UG-127(d) (Open Vents), 28-6, 28-8
- Ultrasonic testing (UT), 15-30, 19-3
- Uncertainties, probability distributions and, 29-2
- Uncoupled, 6-6
- United Kingdom pipeline Regulator, 11-5
- United Kingdom’s Pipeline Safety Regulations, 1996, 11-5
- United States
 - nuclear fusion in, 33-13
- United States Geological Survey (USGS), 14-1
- United States Nuclear Regulatory Commission (USNRC), 14-1, 25-2, 32-21
 - IE Bulletin No. 83-02, 25-5
- Unreinforced fabricated tee (UFT), 4-19
- Updated Final Safety Analysis Report (UFSAR), 7-2
- Upper-shelf energy (USE), 19-15, 19-16
- Uranium-235, 33-3
- URD. *See* Utility Requirement Document
- U.S. Bureau of Labor Statistics, 25-3
- U.S. Department of Homeland Security, 22-23
- U.S. National Pipeline Mapping System, 11-9
- U.S. transportation regulations for radioactive materials, development of, 10-1
 - additional regulatory guidance, NRC, 1985, 10-14
 - NUREG/CR-3019, 10-14–10-15
 - NUREG/CR-3854, 10-15
 - background related to, 10-1–10-2
 - changes between 1973 and 1978, 10-11
 - double containment for plutonium, 1974 final rule, 10-12–10-13
 - double containment for plutonium, 1973 proposed rule, 10-11
 - 1978 effective rule, 10-13
 - quality assurance requirements for 10 CFR 71, 1977 final rule, 10-13
 - quality assurance requirements for 10 CFR 71, 1973 proposed rule, 10-12
- DOT changes, 10-6
 - 1968 final rule, 10-7–10-9
 - 1968 proposed rule, 10-6–10-7
- double containment issues, 1997 proposed rule, 10-17
- licensing responsibilities from DOT to AEC, transfer of, 10-9
 - approval of type B, large quantity and fissile material packagings, 1973 final rule, 10-10–10-11
 - approval of type B, large quantity and fissile material packagings, 1971 proposed rule, 10-9–10-10
- miscellaneous amendments, 1968, 10-9
- NRC Regulatory Guide (Reg. Guide) 7.6, 10-13–10-14
- NUREG/CR-1815, 1981, 10-14
- Reg. Guides 7.11 and 7.12, 1991, 10-16
- Title 10, Code of Federal Regulations, Part 71 (10 CFR 71), 10-2
 - 1966 final rule, 10-5–10-6
 - 1983 final rule, 10-14
 - 1995 final rule, 10-16–10-17
 - 2004 final rule, 10-18–10-23
 - major changes to, 1988 proposed rule, 10-15–10-16
 - 1965 proposed rule, 10-2–10-5
 - 1979 proposed rule, 10-14
 - 2002 proposed rule, 10-17–10-18
- U.S.A. Standards (USAS), 1-2
- U.S.A. Standards Institute, 1-2
- US advanced pressurized water reactor (US-APWR)
 - access building, 15-29
 - ASME Code aspects, 15-30
 - configuration, building, 15-28–15-29
 - Figure 15C.1 (Improvement of Reactor Design), 15-23
 - Figure 15C.2 (Improvement of Reactor Design), 15-23
 - Figure 15C.3 (US-APWR Reactor Coolant Systems), 15-23
 - Figure 15C.4 (US-APWR High Efficiency and High-Reliability Turbine Generator), 15-23
 - Figure 15C.5 (US-APWR Computerized Main Control Room), 15-24
 - Figure 15C.6 (US-APWR Fuel Assembly), 15-24
 - Figure 15C.7 (US-APWR Distinctive Safety System), 15-25
 - Figure 15C.8 (US-APWR Advanced Accumulator), 15-26
 - Figure 15C.9 (US-APWR in Containment Refueling Water Storage Pit [RWSP]), 15-27
 - Figure 15C.10 (US-APWR Compact Arrangement of Power Block), 15-28
 - Figure 15C.11 (US-APWR Plant), 15-28
 - Figure 15C.12 (The CSDRS [Horizontal Damping 5%]), 15-29
 - Figure 15C.13 (Illustration of US-APWR Steel Concrete Structure Module), 15-30
 - Figure 15C.14 (Illustration of US-APWR Large Equipment Module), 15-30
 - flexible core operation, 15-25
 - fuel economy, enhanced, 15-24
 - future direction of, 15-31
 - and Japanese APWR, 15-22
 - modularization and construction, 15-29–15-30
 - operational technology, 15-22–15-25
 - operation and maintenance, 15-30
 - plant design concept, 15-22
 - reactor building complex, 15-29
 - reliability, improved, 15-24
 - safety features, 15-25–15-28

- Table 15C.2 (US-APWR Probabilistic Risk Assessment Metrics), 15-28
- Table 15C.3 (Stress Criteria for ASME Code Section III, Class 1, Component and Supports and Class CS Core Supports), 15-30
- Table 15C.1 (US-APWR Feature Comparison with the Japanese APWR and Current Four-Loop Plant), 15-22
- turbine building, 15-29
- US-APWR. *See* US advanced pressurized water reactor
- USAS. *See* U.S.A. Standards
- USAS B31.1.0, 1-3
- USAS B31.7-1969, 1-4
- USAS B31.7 Code for Nuclear Piping, 1-3
- USE. *See* Upper-shelf energy
- User's Design Specification (UDS), 24-12
- USNRC. *See* Nuclear Regulatory Commission
- USNRC Regulatory Guide 1.68, 3-3-3-4
- US nuclear plants
- insights from PRAs applications
 - public health risk, 29-6
 - regulation, 29-6
- UT. *See* Ultrasonic testing
- Utility Requirements Document (URD), 15-4, 15-27
- Vacuum conditions, piping failure and, 31-5-31-6, 31-6f
- Vacuum vessel
- ITER, 33-7-33-8, 33-8f
- Valves
- failure modes for, 7-7
 - operability evaluation methods, 7-13
 - standardization of, 23-1-23-9. *See also* American Society of Mechanical Engineers (ASME) B16 Standard
 - visual inspection of, 7-14
- Valves, inservice test requirements for, 7-9-7-10
- Table 7.2 (Inservice Test Requirements for Valves), 7-9
 - Table 7.3 (Leakage Criteria for Category A Valves), 7-9
 - Table 7.4 (Example of Typical PWR Leakage Rates), 7-9
 - Table 7.5 (Stroke-Time Acceptance Criteria for Active Category A and B Valves), 7-9
- Valves and Fittings Institute, 23-1
- Vapour sensing, for leak detection in pipelines, 11-49
- Variable frequency drives (VFD), 32-16, 32-21
- VDU. *See* Visual display units
- Verification testing, 17-12
- Vertical stability coils, ITER, 33-8
- Very high temperature gas-cooled reactors (VHTGR), 17-1
- Very high temperature reactor (VHTR). *See also* Codes for very high temperature generation IV reactors
- 17-10 CFR Part 50, NUREG-1860, July 2006, 17-10-17-11
 - codes and procedures for HTGR components, 17-8-17-9
 - design features and technology uncertainties for NGNP, 17-10
 - material behavior in HTGR environments, 17-9-17-10
 - material engineering research needs for advanced reactors, 17-8
 - materials and design bases in ASME Code Case N-47, NUREG/CR-5955, 17-7-17-8
 - NGNP technical issues safety research needs, 17-10
 - overview, 17-2
 - regulatory issues for structural design of, 17-7-17-11
 - safety evaluation of PRISM reactor, 17-8
- Very near infra red (VNIR), 11-51
- Vessel attachment weld cracking
- steam-dryer-support-bracket cracking, 19-14-19-15
 - vessel-to-shroud support weld cracking, 19-13-19-14
- Vessel steam pipe rupture force, on vessel internals, 8-15-8-16
- compressible/acoustic theory for transient steam flows, 8-16-8-17
- compressible flow transient in pipe, general solution, 8-17
- decompression loads on steam dryer, 8-20-8-21
- example calculation, 8-21-8-22
- Figure 8.17 (Disturbance Propagating in Compressible Fluid), 8-16
- Figure 8.18 (Compressibility Effects, Compression), 8-16
- Figure 8.19 (Compressibility Effects, Decompression), 8-17
- Figure 8.20 (Compressible Flow Transient in Pipe), 8-17
- Figure 8.21 (Discharge Pressure and Velocity, Pipe Rupture), 8-17
- Figure 8.22 (Expansion Fan), 8-18
- Figure 8.23 (Velocity Arriving at Vessel), 8-18
- Figure 8.24 (Pressure Arriving at Vessel), 8-19
- Figure 8.25 (Acoustic Point Source), 8-19
- Figure 8.26 (Model for Flow Into Steam Line from Vessel), 8-20
- Figure 8.27 (Spherical Point Source), 8-21
- Figure 8.28 (Source Images for Decompression Propagation between Vessel Wall and Dryer), 8-21
- Figure 8.29 (Normalized Dryer Pressure Opposite Steamline), 8-22
- function $f(V)$, 8-18
- nomenclature related to, 8-16
- pipe rupture boundary condition, 8-17
- steam discharge velocity from vessel, 8-18-8-20
- Vessel-to-shroud support weld cracking, 19-13-19-14
- VFD. *See* Variable frequency drives
- VHTGR. *See* Very high temperature gas-cooled reactors
- VHTR. *See* Very high temperature reactor
- Vibration, piping failure and, 31-4-31-5
- high-frequency, 31-5
 - low-frequency, 31-5
- Vibration acceptance criteria, 3-4
- Vibrational mode shapes, for sample piping system, 3-26
- Vibration isolators, 3-14
- Vibration monitoring groups (VMGs), 3-5
- VMG-1, 3-5
 - VMG-2, 3-5
 - VMG-3, 3-5
- Vibration-monitoring system, 3-16-3-21
- accelerometers, use of, 3-18
 - acoustic emissions, measurement of, 3-18
 - for continuous monitoring, 3-17
 - data recording and evaluation, 3-19-3-20
 - displacement transducers in, 3-17-3-18
 - force transducers, use of, 3-19
 - frequency analyses of time history trace, 3-20
 - hardware transducers in, use of, 3-16
 - pressure transducers, use of, 3-19
 - for snapshot recording, 3-17
 - and strain measurements, 3-18-3-19
 - temperature information in, 3-18
 - use of, 3-19
- Vibratory loads, 6-13. *See also* Vibratory loads
- design considerations
 - flow induced vibration, 6-13-6-14
 - mechanical vibration, 6-13
 - pulsation, 6-13 - and operating conditions, 6-13
 - vibratory stress, computation of, 6-13
- Vibratory stress, 6-13
- Victaulic Couplings, 31-2t
- VIII-1. *See* Section VIII, Division 1 (Rules for Construction of Pressure Vessels)

- VIII-2. *See* Section VIII, Division 2 (Alternative Rules for Pressure Vessels)
- Vinyl Ester, 26-6
- VIPER, 19-12
- Viscous damping, 6-11
- Visual display units (VDU), 15-27
- Visual examinations, 20-18
- Visual inspections, 21-10
- Visual testing (VT), 19-3
- Visual walkdown procedure, 3-21–3-22
- VMGs. *See* Vibration monitoring groups
- VNIR. *See* Very near infra red
- VOF. *See* Volume of fluid
- Void swelling, 20-17
- Volume of fluid (VOF) methods, 6-15–6-16
examples
Kettle type WHB, 6-15–6-16
scum busting nozzle, 6-16
use of, 6-15
- Volumetric inspection frequency, 21-12
- Von Mises yield criterion, 17-3
- Vortex shedding, 8-8, 8-12
and piping steady-state vibration, 3-8–3-9
- VRC. *See* Pressure Vessel Research Council
- VT. *See* Visual testing
- VVS. *See* Vertical ventilated storage
- Wais reports, on *i*-factors, 4-5
- Walkdown procedures, 3-21. *See also* Piping vibration
dynamic-transient vibration and, 3-21–3-22
Inspector's perceptions in, 3-24–3-25
steady-state vibration and, 3-22–3-23
- Wall thinning in piping (evaluation procedures and acceptance criteria, Section XI)
Code Case N-597-2 (overview), 27-14
Code Case N-597-2, activities to address NRC conditions on, 27-14–27-15
Code Case N-597-2, NRC conditions on, 27-14
- WASH-3, 29-3
- WASH-740, 29-3
- WASH-1400, 22-1, 22-2
- WASH-1400 report, 29-2
- Waste building, 15-13
- Waste heat boiler (WHB), 6-15. *See also* Multi-phase flow analysis, with CFD
- Water chemistry, 19-24
stress improvement remedies and, 19-17
- Water chemistry changes
hydrogen concentration, adjustments of, 21-24
lithium concentrations and pH, 21-24
zinc additions to reactor coolant, 21-24
- Water chemistry control, 16-18. *See also* Materials selection
- Water Chemistry Improvement (HWC), 25-2
- Water conductivity, 19-23
- Water hammer, 3-2, 3-9–3-12
piping failure and, 31-3
- Water slugging, 3-2, 3-11–3-12
- Weibull statistics, 20-11, 20-12
- Weld(s)
flaws, 21-5
or component replacement, 21-22–23
shrinkage, 491
structural integrity of, 17-11–17-12
- Weld cracking, vessel attachment
steam-dryer-support-bracket cracking, 19-14–19-15
vessel-to-shroud support weld cracking, 19-13–19-14
- Weld cracking, vessel-to-shroud support, 19-13–19-14
- Weld defects, 11-31–11-32
- Welding neck flange, 23-5
- Welding Research Council (WRC) Bulletin 107, 7-12
- Welding Research Council (WRC) Bulletin 297, 7-12
- Welding Research Council (WRC) Bulletin 352, 7-12
- Weld inlays, 21-22
- Weldment cracking, 17-4
- Weld overlay (WOL), 21-21, 21-26
- Weld overlay repairs (WOR), 19-17–19-20. *See also* Boiling water reactor internals
Code Case 504, 19-18
dissimilar metal weld overlays, 19-19
impact of revised ASME BPVC Section XI, Appendix C (2002 Addenda), 19-19–19-20
- Weld residual stresses (WRS), 27-11–27-13, 27-11f, 30-20. *See also* Stress corrosion cracking
current activities in ASME Section XI, 27-12–27-13
finite element calculations, 27-12
improvement, 27-12
- West, Raymond A., 22-1
- Westinghouse Small Modular Reactor (SMR), 32-12
construction code, 32-21
economics, 32-13–32-14
large component rail shipment, 32-14f
licensing, 32-21
modularization and construction, 32-20, 32-20f
NSSS vs. iPWR design, 32-13, 32-13f
objectives, 32-14
operation and maintenance, 32-20–32-21
plant design
nuclear island, 32-15–32-19. *See also* Nuclear island, Westinghouse SMR
overview, 32-13, 32-13f
radio building, 32-19
site, 32-14, 32-14f
turbine island, 32-19
safety and security, 32-14, 32-19–32-20, 32-20f
vs. AP1000 plant, 32-13, 32-13f
- WHB. *See* Waste heat boiler
- WOL. *See* Weld overlay
- WOR. *See* Weld overlay repairs
- Work sequencing, 12-6–12-7
- WPMR. *See* Whole Pool Multi-Rack
- WRC. *See* Welding Research Council
- Writing style and organization
Section VIII, Division 1 (Rules for Construction of Pressure Vessels), 24-2
- XM-19 high strength stainless steel, 16-17
- XRF. *See* X-ray fluorescence
- Yield strength, 21-5
- Zero period acceleration (ZPA), 6-6, 6-11, 14-2, 15-29
- Z-factor, 27-13
- Zinc additions to reactor coolant, 21-24
- ZIRLO™ cladding tube, 15-24
- ZPA. *See* Zero period acceleration
- ZPA frequency, 6-6