

**Corrigendum: *Journal of Hydroinformatics* 19(1), 97–114,
doi: 10.2166/hydro.2016.006. Sustainable groundwater
modeling using single- and multi-objective optimization
algorithms, S. Sadeghi-Tabas *et al.***

The authors regret that there were errors in Equations (1) and (2). The equations should be corrected to read as follows.

Equation (1):

$$\frac{\partial}{\partial x} \left(k_x \frac{\partial h}{\partial x} \right) + \frac{\partial}{\partial y} \left(k_y \frac{\partial h}{\partial y} \right) + \frac{\partial}{\partial z} \left(k_z \frac{\partial h}{\partial z} \right) = \frac{S_s \partial h}{\partial t} \mp R \quad (1)$$

where k_x , k_y and k_z denote the hydraulic conductivity

tensors, h , S_s and R represent pressure head, specific storage and recharge or discharge (positive and negative) components of the aquifer, respectively.

Equation (2):

$$\frac{\partial}{\partial x} \left(k_x h \frac{\partial h}{\partial x} \right) + \frac{\partial}{\partial y} \left(k_y h \frac{\partial h}{\partial y} \right) = S_y \frac{\partial h}{\partial t} \quad (2)$$

where, S_y denotes the specific yield.