

**Corrigendum: *Journal of Hydroinformatics* 19(1), 97–114,  
doi: 10.2166/hydro.2016.006. Sustainable groundwater  
modeling using single- and multi-objective optimization  
algorithms, S. Sadeghi-Tabas *et al.***

The authors regret that there were errors in Equations (1) and (2). The equations should be corrected to read as follows.

Equation (1):

$$\frac{\partial}{\partial x} \left( k_x \frac{\partial h}{\partial x} \right) + \frac{\partial}{\partial y} \left( k_y \frac{\partial h}{\partial y} \right) + \frac{\partial}{\partial z} \left( k_z \frac{\partial h}{\partial z} \right) = \frac{S_s \partial h}{\partial t} \mp R \quad (1)$$

where  $k_x$ ,  $k_y$  and  $k_z$  denote the hydraulic conductivity

tensors,  $h$ ,  $S_s$  and  $R$  represent pressure head, specific storage and recharge or discharge (positive and negative) components of the aquifer, respectively.

Equation (2):

$$\frac{\partial}{\partial x} \left( k_x h \frac{\partial h}{\partial x} \right) + \frac{\partial}{\partial y} \left( k_y h \frac{\partial h}{\partial y} \right) = S_y \frac{\partial h}{\partial t} \quad (2)$$

where,  $S_y$  denotes the specific yield.