

Examination of a coupled supply- and demand-induced stress function for root water uptake modeling

Na Liu, Huade Guan, Zidong Luo, Cicheng Zhang, Hailong Wang and Xinping Zhang

ABSTRACT

Vegetation water use is closely related to its biophysical functioning and is often under stress from various environmental factors. However, commonly used root water uptake models only consider the stress from root zone moisture availability. There is a need to incorporate the stress from both the above-ground factors and root zone water condition. In this study, a newly developed coupled supply- and demand-induced (S&D) root water uptake model is examined with measurements on two tree species, Guihua in the subtropical monsoon climate and Drooping Sheoak in the Mediterranean climate. The results show that the S&D model outperforms a supply-constraint water stress function (the S-shape model) for both studied species. The S&D model predicts 67% and 84% temporal variability in the measured water stress for Guihua and Drooping Sheoak, respectively. The improvement of the S&D model over the S-shape model is more significant for Guihua than for Drooping Sheoak, which might be associated with the specific climate conditions. A two-step parameterization approach is adopted in this study for the S&D model, and is recommended for future applications. These results further support the validity of the S&D model, and should be considered for the root water uptake modeling.

Key words | root water uptake, S&D model, S-shape model, transpiration

Na Liu

Zidong Luo

Cicheng Zhang

Xinping Zhang (corresponding author)

College of Resource and Environmental Science,

Hunan Normal University,

Changsha 410081,

China

E-mail: zxp@hunnu.edu.cn

Huade Guan

Hailong Wang

School of the Environment,

Flinders University,

Adelaide,

South Australia 5001,

Australia

INTRODUCTION

Forest ecological systems are closely related to global change, because forests can influence climate through the exchanges of energy, water, carbon dioxide, and other chemical compositions with the atmosphere (Bonan 2008). Vegetation changes affect regional water balance (Yuan *et al.* 2012), and vegetation influences the water balance through root water uptake, transpiration and other means (Janeau *et al.* 2015). In the soil–plant–atmosphere system, plant roots play a key role in transporting water and nutrition. The root water uptake process reduces the potential for deep percolation although root induced macropores may increase hydraulic conductivity in soil, which facilitates percolation (Guan *et al.* 2010). Thus, plant root water uptake is an important process in the water cycle and soil water

balance. It is a key subject of ecohydrology, land process modeling, and watershed hydrologic modeling.

According to the research scale, root water uptake models can be categorized into microscopic and macroscopic types (Yang & Hao 1999; Ji *et al.* 2006; Wang *et al.* 2011). A single radial root water uptake microscopic model with uniform water absorption characteristics was proposed by Gardner (1960). Based on this, a model of non-uniform root systems, including root hydraulic characteristics and soil-root-interface interaction, was developed (Cowan 1965; Molz 1976; Raats 1975). These models have not become dominant in application due to their numerous parameters and the requirement of complex root distribution representation.

A macroscopic model lumps the root zone into a root distribution function, which has broader applications in root zone soil water dynamic simulation for its simplicity. In such models, root water uptake is represented as a sink term in the root zone based on a root distribution function and water potential in different layers of the root zone. Two types of approaches have been developed. The first approach, proposed by Nimah & Hanks (1973), is based on a hydraulic gradient between soil and hydraulic resistance in the soil and root continuum. This approach has been adopted in root zone hydrological models such as LEACHM (Hutson & Wagenet 1991). It is difficult to parameterize the root resistance in such a model. The second approach, introduced by Feddes *et al.* (1978), treats root water uptake as a potential rate (depending on root distribution and the atmospheric demand) reduced by a stress function of soil water potential. This approach has been used in HYDRUS. The Feddes piecewise linear model (Feddes *et al.* 1978) and the S-shape non-linear model (van Genuchten 1987) are two commonly used water stress models. Both models simulate root water uptake as a potential rate (or the atmospheric demand) multiplied by a stress factor which is a function of root zone water condition. However, it is known that the stress on plant water use comes not only from the root zone moisture availability, but also from the atmospheric conditions which determine the evaporative demand (i.e., potential evapotranspiration) for root water uptake. Some land surface models consider these atmospheric factors (e.g., vapor pressure deficit, temperature and solar radiation), which are included in Jarvis-type canopy conductance models (Wang *et al.* 2014).

Thus, there is a need to incorporate the stress from the above-ground factors and root zone water availability into the root water uptake function to test whether root water uptake simulation can be improved. In fact, this has been attempted in HYDRUS (Šimuněk *et al.* 2005), in which two threshold soil water potentials (parameter h_3) of the Feddes model are prescribed for two thresholds' potential transpiration (PT) rates. This model is difficult to use for two reasons: (1) two thresholds do not provide flexibility to represent a spectrum of stress from varying atmospheric factors; and (2) the parameters are difficult to determine. Recently, Yang *et al.* (2013) proposed a new function for root water uptake modeling based on the S-shape model

function in which, besides soil water potential, PT is used as a second factor to represent lumped stress from the atmospheric demand. In their model, the influence of both root zone water potential (which was determined by water supply) and the atmospheric demand are considered and represented. Thus, this model is now referred to as the coupled supply- and demand-induced stress function (the S&D model hereafter) for root water uptake modeling. The S&D model was previously tested with a short period of measurements on a tree species in a Mediterranean climate. It requires more rigorous testing over a longer period of measurements and in different environments.

The objective of this paper is to test the S&D model for two tree species in two climate zones (subtropical monsoon vs. Mediterranean type), by comparing the S&D modeling results with a supply-constraint water stress function (the S-shape model). A two-step parameterization method is suggested and discussed as well.

METHODOLOGY

Experiments

The experiments were performed at two sites with distinctive climates, Changsha in the central south of China, and Adelaide in South Australia. The climate condition and studied tree species of the two sites are shown in Figure 1.

Changsha (112.967 °E, 28.183 °N), the capital city of Hunan province in China, with an elevation of 70 m above sea level, has a subtropical monsoon climate characterized by hot and wet summers, and cold and dry winters. Precipitation is concentrated in spring and early summer, followed by a seasonal dryness in July and August, with a mean annual temperature of 17 °C and mean annual precipitation of 1,360 mm. The experiment was conducted at a plantation site on the outskirts of the city, from April 19 to September 24 of 2013. Two *Osmanthus fragrans* (common name in China: Guihua) trees (labeled as No. 1 and No. 2) were chosen for this study. Guihua is a typical tree species in the subtropical monsoon climate zone.

The other site is on the campus of Flinders University (138.572 °E, 35.039 °S) in Adelaide, South Australia, with an elevation of 100 m. The climate of Adelaide is




Figure 1 | Climatic characteristics and the examined trees at the two study sites: Changsha and Adelaide.

Mediterranean type with long and hot summers, and mild and rainy winters, with a mean annual rainfall of 550 mm and mean annual temperature of 17.3 °C. Drooping Sheoak (*Allocasuarina verticillata*) was selected as our study species, not only because it was a typical species in South Australia, but also because it is the species examined in Yang *et al.* (2013). The measurement was performed over two periods: January 21 to April 15 and October 29 to December 31 of 2012. Root zone hydrological studies often do not have direct soil water potential and transpiration measurements, in which the root water uptake function is often calibrated with measured root zone soil water content (Musters & Bouten 2000; Vrugt *et al.* 2001). Such exercises lump uncertainties from the determination of soil hydraulic properties, root distribution and root water uptake parameterization together, leading to difficulty in model calibration. Recent progress in monitoring stem water potential (Yang *et al.* 2013; Wang *et al.* 2014) provides a robust tool to separate parameterization of the root water uptake function from other parts of the root zone hydraulic properties.

Stem water potential was measured with thermocouple stem psychrometers (PSY1; ICT International Pty Ltd,

Australia) at a 30-min interval. Details about this equipment can be found in Yang *et al.* (2013) and Wang *et al.* (2014). Previous studies (Ritchie & Hinckley 1975; Hinckley *et al.* 1978) have shown that water potential along the soil-plant continuum tends to be in equilibrium at dawn. Therefore, in this study, the predawn stem water potential was chosen as a surrogate for the root zone soil water potential to examine the water stress function for root water uptake modeling.

Transpiration was measured with the heat-pulse sap flow sensors at a 30-min interval. For each tree, two sets of sap flow probes were installed on the sunlit and shaded sides of the trunk, at a height of 0.7 m above ground. A software 'sap flow tool' obtained from the provider was used to calculate the daily transpiration; the whole tree transpiration was estimated from the average value of the two sides.

Micrometeorological conditions were measured from a standard automatic weather station, located in both experimental sites. Wind speed, relative humidity, air temperature and solar radiation were used to estimate PT using the Food and Agriculture Organization of the United Nations reference evapotranspiration (ET) equation

(Allan et al. 1998),

$$ET_0 = \frac{0.408\Delta(Rn - G) + \gamma \frac{900}{T + 273} u_2 (e_s - e_a)}{\Delta + \gamma(1 + 0.34u_2)} \quad (1)$$

where ET_0 is reference evapotranspiration [mm day^{-1}], R_n is net radiation at the crop surface [$\text{MJ m}^{-2} \text{day}^{-1}$], G represents soil heat flux density [$\text{MJ m}^{-2} \text{day}^{-1}$], T is mean daily air temperature at 2 m height [$^{\circ}\text{C}$], u_2 is wind speed at 2 m height [m s^{-1}], e_s and e_a are saturation vapour pressure [kPa] and actual vapour pressure [kPa], respectively, $e_s - e_a$ is the saturation vapour pressure deficit (or VPD) [kPa], Δ is the slope vapour pressure curve [$\text{kPa } ^{\circ}\text{C}^{-1}$], and γ is a psychrometric constant [$\text{kPa } ^{\circ}\text{C}^{-1}$].

It is difficult to accurately estimate transpiration and PT for individual trees. For transpiration estimates, a large uncertainty comes from the fact that an effective surface area required to convert volumetric sap fluxes to transpiration rates is not known. For PT, the uncertainty comes from the difficulty of accurately estimating radiation energy partitioning. We used ET_0 (Equation (1)), which was developed based on a type of densely distributed short grass, to represent the PT of the tree and adjusted the effective surface area so that the time series of PT envelops that of transpiration over the whole measurement period. Figures 2 and 3 show the calculated transpiration, PT estimated with ET_0 and precipitation measured with the automatic weather stations for Guihua and Drooping Sheoak, respectively. Since it is the ratio of transpiration (T) over PT, rather than true

transpiration and true PT that is examined in this study, we consider this treatment of the data to be acceptable.

Leaf-scale data, including net photosynthetic rate, stomata conductance, transpiration rate and VPD of sunlit leaves and shaded leaves were measured by a Li-6400 photosynthetic analyzer from May 13 to August 30 in sunny days for Guihua No. 1. The measurements were taken about 2–5 times a day, from 8:00 to 16:00 h. Previous studies (Kemp et al. 1997; Gao et al. 2002) have established models to investigate the relationship between leaf-scale data, such as stomata conductance and leaf scale transpiration, and the soil water potential. This relationship is obtained based on leaf-level measurements on Guihua, and compared to that derived from the whole-tree measurements from sap flow meters and stem psychrometers.

Theoretical background

In the soil-plant-atmosphere continuum, suppose the change of water storage in the plant is negligible (Tyree & Yang 1990), the root water uptake rate equates to the plant's actual transpiration rate. When a plant is under water stress, the actual transpiration is less than the PT. The equation of transpiration can be written as:

$$T = \beta(\bar{h}) * PT \quad (2)$$

where T is the actual transpiration (mm day^{-1}), PT is the potential transpiration (mm day^{-1}), $\beta(\bar{h})$ is the stress




Figure 2 | Daily PT, actual transpiration (T) for two Guihua trees and rainfall during the experiment period.




Figure 3 | Daily PT, actual transpiration (T) for the Drooping Sheoak tree and rainfall during the experiment period.

function, and \bar{h} is the equivalent root zone soil water potential (MPa). \bar{h} is not the mathematical average of water potential in the root zone, because roots uptake water preferentially from the wet part of the root zone to meet the atmospheric demand. As a result of this phenomenon, compensation root water uptake models have been developed (Li et al. 2001; Šimunek & Hopmans 2009; Willingen et al. 2012). Thus, \bar{h} should represent the equivalent water potential of the whole root zone at which root water uptake stress currently occurs. Predawn stem water potential provides a good approximate of \bar{h} .

How to determine the stress function is key to the calculation of the actual transpiration or root water uptake rates. The S-shape function (Equation (3)), proposed by van Genuchten & Hoffman (1984), is commonly used for root zone hydrological simulation.

$$\beta(\bar{h}) = \frac{1}{1 + \left(\frac{\bar{h}}{h_{50}}\right)^p} \quad (3)$$

where h_{50} is the soil water potential (MPa) at which the water uptake rate is reduced by 50% from the potential rate, p is an empirical coefficient.

The S-shape function only considers the limitation from the 'supply' side. The results in Yang et al. (2013) show that the amount of water demanded by the atmospheric condition (i.e. PT), may pose stress on vegetation water use, and should be included in the stress function. Therefore,

stress from both 'supply' and 'demand' sides is included in the S&D function:

$$\beta(\bar{h}, PT) = f(\bar{h}) * g(PT) = \frac{1}{1 + \left(\frac{\bar{h}}{h_{50}}\right)^p} * (aPT + b) \quad (4)$$

where f is an S-shape function of root zone soil water potential, g is a linear function of PT, describing the stress from the atmospheric demand, PT means potential transpiration (mm day^{-1}), and a (day mm^{-1}) and b are fitted parameters.

Model calibration and mathematical justification

In order to examine the process of calibration and the applicability of the S&D model in different climate zones, we tested the model for both sites. For the Guihua site, we used one Guihua tree to parameterize the function and tested it with the second one. At the Drooping Sheoak site, due to only one Drooping Sheoak being measured, the odd-day data were used to fit the function and those of the even-day to test the effectiveness of the model.

A new stepwise parameterization method is adopted in this study. This is different from the method used by Yang et al. (2013) who calibrated the two parts in Equation (4) simultaneously. We found that determination of the four parameters simultaneously with all data did not come to consistent results for h_{50} . This may be due to high correlation between PT and root zone water potential, particularly for

the Mediterranean climate. To avoid this problem, we calibrate the supply-induced stress first using the days with low PT values. We assume that in these low PT days, the atmospheric demand is small, the demand-induced stress is minimal and can be neglected. The data are fitted with the least sum of square method for the S-shape function, to obtain the parameter values of h_{50} and p . After, these two parameters are determined, all data are fitted with the least sum of square method for the S&D model function to obtain the values of a and b .

Although the S&D model is constructed based on our understanding of the environmental stress on transpiration, mathematically an overfitting problem may exist given that it has two more parameters than the S-shape model.

The Bayesian information criterion (*BIC*) (Schwarz 1978), considered to be the most strict statistical indicator to pose a penalty on additional parameters in a model (Hawkins 2003), was adopted to test if the S&D model is also mathematically sound. The *BIC* can be calculated according to

$$BIC = n^* \log\left(\frac{SSE}{n}\right) + k^* \log(n) \quad (5)$$

where SSE is the sum of square error, n is the number of data points, and k is the number of predictor parameters. A model with additional parameters is accepted if *BIC* is smaller than that of a simpler model (e.g., Guan et al. 2013).

Model validation and evaluation

To compare the S&D model and the S-shape model, two commonly used model evaluation indicators: root-mean-square

error (*RMSE*) (Liu et al. 2015) and the Nash–Sutcliffe coefficient of efficiency (*NSE*) (Nash & Sutcliffe 1970; Legates & McCabe 1999), are selected for the effectiveness evaluation of the two models. The calculation formula of the *NSE* is:

$$NSE = 1 - \frac{\sum_{i=1}^n (Q_m - Q_s)^2}{\sum_{i=1}^n (Q_m - \overline{Q_m})^2} \quad (6)$$

where *NSE* is the Nash–Sutcliffe coefficient of efficiency, Q_m is the measured value, Q_s is the simulated value, $\overline{Q_m}$ is the average value of measurements and n is the number of data. If *NSE* = 1, the result indicates the credibility of the model is perfect, while if *NSE* = 0, the result shows the effect of the model is nil.

RESULTS AND DISCUSSION

Model parameterization

Relative humidity near 100% occurs during rainy days, and stem water potential responds sensitively to the rainfall events (Yang et al. 2013), therefore they are excluded from parameterization and examination of the water stress function.

Based on the relationship between predawn stem water potential and T/PT for Guihua and Drooping Sheoak from field measurements, Equation (3) is fitted with Guihua No. 1 and Drooping Sheoak odd-day data. The results for h_{50} and p are shown in Table 1. With the same input data, Equation (4) is fitted stepwisely for four parameters of the S&D model, with the values of h_{50} , p , a and b shown in Table 1.

Table 1 | The calibration and validation results for Guihua and Drooping Sheoak (n is the number of data points)

Target trees	Calibration					Validation		
	Models	h_{50} MPa	p	a Day mm^{-1}	b	<i>BIC</i>	<i>RMSE</i>	<i>NSE</i>
Guihua No. 1	S-shape	−0.75	0.62			−191.736		
	S&D	−1.1	0.47	−0.14	1.36	−208.455		
Guihua No. 2	S-shape						0.146 ($n = 107$)	0.369
	S&D						0.105 ($n = 107$)	0.674
Drooping Sheoak odd days	S-shape	−0.48	0.56			−116.469		
	S&D	−1.04	0.51	−0.09	1.22	−122.718		
Drooping Sheoak even days	S-shape						0.091 ($n = 57$)	0.761
	S&D						0.076 ($n = 57$)	0.844

The *BIC* value is -191.7 and -208.5 for Guihua No. 1 with the S-shape model and the S&D model, respectively, and -116.5 and -122.7 for the odd days of Drooping Sheoak with the S-shape model and the S&D model, respectively. This result supports the hypothesis that it is worthwhile to have the S&D model for root water uptake stress simulation.

The value of h_{50} represents how plants are sensitive to water stress. As we can see from Table 1, the value of h_{50} is -0.75 MPa and -0.48 MPa in the S-shape model for Guihua and Drooping Sheoak respectively. From the S&D model, the value of h_{50} for Guihua and Drooping Sheoak is -1.1 MPa and -1.04 MPa, respectively. Previously, water stress has been examined for the Drooping Sheoak. The h_{50} resulting from this study with the S-shape model (-0.48 MPa) is close to that (-0.52 MPa) of Yang et al. (2013). The h_{50} by the S&D model in this study (-1.04 MPa) is quite different from the -0.49 MPa in Yang et al. (2013), but close to the -0.87 MPa in a study with a more rigorous model considering stress from both root zone and micrometeorological conditions (Wang et al. 2014). The value of a for Guihua and Drooping Sheoak is -0.14 day mm^{-1} and -0.09 day mm^{-1} , respectively. The value for Drooping Sheoak is close to -0.084 day mm^{-1} in Yang et al. (2013). The value of a represents the impact of PT: the more negative the value of a , the more sensitive the tree is to PT. Therefore, for the same amount of PT, water stress on Guihua is stronger than on Drooping Sheoak. This may be associated with the corresponding climatic conditions. The study area for Drooping Sheoak has a hot and dry summer, which causes large PT values (based on the measured data, PT is about 4.76 mm day^{-1}). We imagine trees in such an environment may adapt to the PT-induced stress, leading to a smaller PT dependency. While for the Guihua site, it is hot and relatively humid in summer. PT (based on the measured data, PT is about 3.43 mm day^{-1}) is not as high as that at the Drooping Sheoak site; trees in such an environment become more sensitive to PT-induced stress.

Model testing

Testing with the leaf-scale measurements

Leaves of the whole tree include sunlit leaves and shaded leaves, whose sensitivity to water potential is not the same due to different light conditions. Sunlit leaves receive more

sunlight, leading to an increase in leaf temperature when the root zone water supply is limited (Han et al. 2006). A higher temperature increases stomata vapor pressure so that the leaves' internal and external vapor pressure difference increases (Zhang et al. 2000), leading to increasing stress. On the other hand, shaded leaves receive less sunlight and the temperature difference between leaf and air is smaller. Thus, sunlit leaves may be more sensitive to the root zone soil water potential than shaded leaves. The h_{50} fitted by a reasonable model for a whole tree would have a value between the value of h_{50} in shaded leaves and sunlit leaves. We fitted the h_{50} with the S-shape model (Figure 4); in the model function, T is the actual leaf-level transpiration (mm h^{-1}), T_0 is the maximum leaf-level transpiration (mm h^{-1}), and h_{50} and p are empirical coefficients, as in Equation (2).

For the sunlit leaves, the fitted value of h_{50} is -0.5 MPa (Figure 4). For the shaded leaves, the relationship between root zone soil water potential and leaf scale transpiration rate is not obvious and it is difficult to obtain the value of h_{50} for such circumstances (Figure 5). The shaded leaves' transpiration rates do not vary with root zone soil water potential over the measurement range, indicating that the value of h_{50} may be lower than -2.5 MPa. The h_{50} value of the whole tree should lie between the h_{50} value of sunlit leaves and that of shaded leaves. Thus, the reasonable value of h_{50} for Guihua should be lower than -0.5 MPa. Fitting the root water uptake function for Guihua No. 1, the value of h_{50} is -0.75 MPa for the S-shape model and




Figure 4 | Fitting result of the relationship between root zone water potential and the sunlit leaf transpiration rates.




Figure 5 | The relationship between the shaded leaf transpiration rates and root zone water potential.

–1.1 MPa with the S&D model, both are lower than –0.5 MPa, indicating both models reveal h_{50} within the range estimated from leaf scale measurements.

Testing with whole tree measurements

The stress values estimated from the S&D model and S-shape model, based on data independent from those used for model calibration, are compared with the values calculated directly from the observations (Table 1). The S&D model is better than the S-shape model for both studied species. For Guihua in the subtropical monsoon climate zone we tested these two models with data from Guihua No. 2, and the NSE of the S&D model is 0.67, while that of the S-shape model is only 0.37. For Drooping Sheoak in

the Mediterranean climate zone, we tested two models with data from even days; the NSE of the S&D model is 0.84, better than the S-shape model, which is 0.76 for the testing period.

Testing based on time series data

Another way to test the model performance is to compare simulated values with measured values in time series. The result of actual stress (actual ET over PT), model estimated stress by the S&D model and by the S-shape model, are shown in Figure 6 for Guihua and in Figure 7 for Drooping Sheoak.

For Guihua, the S&D model performs better than the S-shape model, particularly in the drought period (July to August). The estimated values from the S&D model agree well with the observed values, which explains why a plant suffers water stress from both the root zone soil water supply and the atmospheric demand.

In addition, the simulation results of both models are better in the dry period than the rainy period. Previous studies (van Genuchten & Hoffman 1984; Gavloski et al. 1992) have found that a plant suffers stress from many factors, including water stress, salt stress and meteorological factors. In the rainy period, water stress is not the major impact factor for transpiration, while in the dry period water stress is the main limiting factor for actual transpiration. This explains why both the S&D model and the S-shape model perform better in the dry period.




Figure 6 | Observed and simulated root water uptake stress variation for Guihua No. 2.




Figure 7 | Observed and simulated root water uptake stress variation for Drooping-Sheoak on even numbered days.

For Drooping Sheoak, the difference between the two models' results is not as large as that for Guihua. The estimated water stress values from both models are in good agreement with the measured values. Nevertheless, the S&D method still provides slightly better estimation (Figure 7 and Table 1).

About the model calibration approach

The h_{50} value fitted with the S&D model for Drooping Sheoak in this paper is -1.04 MPa, while Yang et al. (2013) gave -0.48 MPa. Both are based on data collected from the same site and same tree species, although in different years. It is very unlikely that this difference reflects the actual change in the response to environmental stress. More likely, the difference is an artifact due to the two calibration approaches as mentioned in the methodology section. In this study, a two-step calibration is adopted, while in Yang et al. (2013), the calibration was performed in one step. When this one-step approach is used for the data in this study, it results in a very large h_{50} (in negative value: $h_{50} = -2.74$ MPa). This inconsistency indicates the one-step approach may not be appropriate. The good testing results for both tree species under two different climate conditions suggest the reliability and robustness of the two-step calibration approach adopted in this study.

CONCLUSIONS

In this study, the S&D model is examined with measurements on two tree species located in two different climatic

areas. The results show that the S&D model outperforms the S-shape model for both studied species. It predicts 67% and 84% temporal variability in the measured water stress for Guihua in the subtropical monsoon climate and Drooping Sheoak in the Mediterranean climate, respectively. The improvement of the S&D model over the S-shape model is more significant for Guihua than for Drooping Sheoak, which might be associated with the specific climate conditions. The two-step parameterization approach adopted in this study for the S&D model appears to be more stable, and is recommended for future applications. These results further support the validity of the S&D model, which should be considered for root water uptake modeling.

ACKNOWLEDGEMENTS

This study was funded by the Construct Program of Key Discipline in Hunan Province (No. 2012001) and Hunan Bairen Program, China. Drooping Sheoak data collection was funded by the Australian National Centre for Groundwater Research and Training.

REFERENCES

- Allan, R. G., Pereira, L. S., Raes, D. & Smith, M. 1998 *Crop evapotranspiration. Guidelines for computing crop water requirements*. FAO Irrigation and Drainage Paper 56. FAO, Rome.

- Bonan, G. B. 2008 Forests and climate change: forcings, feedbacks, and the climate benefits of forests. *Science* **320**, 1444–1449.
- Cowan, I. R. 1965 Transport of water in the soil-plant-atmosphere system. *Journal of Applied Ecology* **2**, 221–239.
- Feddes, R. A., Kowalik, P. J. & Zaradny, H. 1978 Simulation of field water use and crop yield. *Simulation of Plant Growth & Crop Production*, 189 pp.
- Gao, Q., Zhao, P., Zeng, X., Cai, X. & Shen, W. 2002 A model of stomatal conductance to quantify the relationship between leaf transpiration, microclimate and soil water stress. *Plant, Cell & Environment* **25**, 1373–1381.
- Gardner, W. R. 1960 Dynamic aspects of water availability to plants. *Soil Science* **89**, 63–73.
- Gavloski, J. E., Whitefield, G. H. & Ellis, C. R. 1992 Effect of restricted watering on sap flow and growth in corn (*Zea mays* L.). *Canada Journal Plant Society* **72**, 361–368.
- Guan, H., Šimunek, J., Newman, B. D. & Wilson, J. L. 2010 Modeling investigation of water partitioning at a semiarid ponderosa pine hillslope. *Hydrological Processes* **24**, 1095–1105.
- Guan, H., Zhang, X., Makhnin, O. & Sun, Z. 2013 Mapping mean monthly temperatures over a coastal hilly area incorporating terrain aspect effects. *Journal of Hydrometeorology* **14**, 233–250.
- Han, Y., Zhang, W., Yang, M. & Liu, B. 2006 The relationship between leaf temperature and water condition in boot stage on rice. *Chinese Agricultural Science Bulletin* **22**, 214–216.
- Hawkins, D. M. 2003 The problem of overfitting. *Journal of Chemical Information & Computer Sciences* **44**, 1–12.
- Hinckley, T. M., Lassoie, J. P. & Running, S. W. 1978 Temporal and spatial variations in the water status of forest trees. *Forest Science Monograph* **20**, a0001–z0001.
- Hutson, J. L. & Wagenet, R. J. 1991 Simulating nitrogen dynamics in soils using a deterministic model. *Soil Use & Management* **7**, 74–78.
- Janeau, J. L., Grellier, S. & Podwojewski, P. 2015 Influence of rainfall interception by endemic plants versus short cycle crops on water infiltration in high altitude ecosystems of Ecuador. *Hydrology Research* **46**, 1008–1018.
- Ji, X., Kang, E., Chen, R., Zhao, W., Jin, B. & Zhang, Z. 2006 The research progress of plant root water uptake model. *Acta Botanica Boreali-Occidentalia Sinica* **6**, 1079–1086.
- Kemp, P. R., Reynolds, J. F., Pachepsky, Y. & Chen, J. L. 1997 A comparative modeling study of soil water dynamics in a desert ecosystem. *Water Resources Research* **33**, 73–90.
- Legates, D. R. & McCabe, G. J. 1999 Evaluating the use of ‘goodness of fit’ measures in hydrologic and hydroclimatic model validation. *Water Resources Research* **35**, 233–241.
- Li, K. Y., Jong, R. D. & Boisvert, J. B. 2001 An exponential root-water-uptake model with water stress compensation. *Journal of Hydrology* **252** (s 1–4), 189–204.
- Liu, T. G., Lai, J. B., Luo, Y. & Liu, L. 2015 Study on extinction depth and steady water storage in root zone based on lysimeter experiment and HYDRUS-1D simulation. *Hydrology Research* **46**, 871–879.
- Molz, F. J. 1976 Water transport in the soil-root system: transient analysis. *Water Resources Research* **12**, 805–808.
- Musters, P. A. D. & Bouten, W. 2000 A method for identifying optimum strategies of measuring soil water contents for calibrating a root water uptake model. *Journal of Hydrology* **227**, 273–286.
- Nash, J. E. & Sutcliffe, J. V. 1970 River flow forecasting through conceptual models part I-A discussion of principles. *Journal of Hydrology* **10**, 282–290.
- Nimah, M. N. & Hanks, R. J. 1973 Model for estimating of soil water, plant, and atmospheric interrelations: I. Description and sensitivity. *Soil Science Society of America* **37**, 522–527.
- Raats, P. A. C. 1975 Distribution of salts in the root zone. *Journal of Hydrology* **27** (s 3–4), 237–248.
- Ritchie, G. A. & Hinckley, T. M. 1975 The pressure chamber as an instrument for ecological research. *Advances in Ecological Research* **9**, 165–254.
- Schwarz, G. E. 1978 Estimating the dimension of a model. *Annals of Statistics* **6**, 461–464.
- Šimunek, J. & Hopmans, M. J. W. 2009 Modeling compensated root water and nutrient uptake. *Ecological Modeling* **220**, 505–521.
- Šimunek, J., Saito, H., Sejna, M. & Genuchten, T. M. 2005 *The HYDRUS-1D Software Package for Simulating the One-dimensional Movement of Water, Heat and Multiple Solutes in Variably-Saturated Media*. Version 3.0. HYDRUS Software Series 1. Department of Environmental Sciences, University of California, Riverside, CA, USA.
- Tyree, M. T. & Yang, S. 1990 Water-storage capacity of Thuja, Tsuga and Acer stems measured by dehydration isotherms. *Planta* **182**, 420–426.
- van Genuchten, M. T. 1987 *A numerical model for water and solute movement in and below the root zone*. Unpublished Research Report. US Salinity Laboratory, USDA, ARS, Riverside, CA, USA.
- van Genuchten, M. T. & Hoffman, G. J. 1984 Analysis of crop salt tolerance data. *Ecological Studies: Analysis and Synthesis* **51**, 258–271.
- Vrugt, J. A., Hopmans, J. W. & Šimunek, J. 2001 Calibration of a two-dimensional root water uptake model. *Soil Science Society of America Journal* **65**, 1027–1037.
- Wang, J., Feng, Z., Sheng, J. & Wang, D. 2011 Review on the research of plant root water uptake model. *Journal of Anhui Agriculture Science* **39**, 1928–1930.
- Wang, H., Guan, H., Deng, Z. & Simmons, C. 2014 Optimization of canopy conductance models from concurrent measurements of sap flow and stem water potential on Drooping Sheoak in South Australia. *Water Resources Research* **50**, 6154–6167.
- Willingen, P. D., Dam, J. C. V., Javaux, M. & Heinen, M. 2012 Root water uptake as simulated by three soil water flow models. *Vadose Zone Journal* **11**, 811–822.
- Yang, P. & Hao, Z. 1999 The dynamic development of plant root water uptake model. *Journal of China Agricultural University* **4**, 67–73.

- Yang, Y., Guan, H., Hutson, J. L., Hailong, W., Ewenz, C., Shang, S. & Simmons, C. T. 2013 Examination and parameterization of the root water uptake model from stem potential and sap flow measurements. *Hydrological Processes* **27**, 2857–2863.
- Yuan, F., Ren, L., Yu, Z., Zhu, Y., Xu, J. & Fang, X. 2012 Potential natural vegetation dynamics driven by future long-term climate change and its hydrological impacts in the Hanjiang River basin, China. *Hydrology Research* **43**, 73–90.
- Zhang, Q., Du, F., Xia, F. & Wang, G. 2000 Eco-physiological of photosynthesis and transpiration for *Tilia americana*. *Journal of Beihua University (Natural Science)* **5**, 436–438.

First received 2 September 2015; accepted in revised form 4 January 2016. Available online 18 February 2016