

ERRATUM: “ABCNN: Attention-Based Convolutional Neural Network for Modeling Sentence Pairs”

Wenpeng Yin, Hinrich Schütze, Bing Xiang and Bowen Zhou

Abstract

In this erratum, we correct the lack of proper attribution of two quotations.

A quotation of three sentences from (Yih et al., 2013) was not properly attributed. We sincerely apologize to Wen-tau Yih, Ming-Wei Chang, Christopher Meek and Andrzej Pastusiak for this mistake. We correct the first paragraph of Section 2, Related Work, as follows. Unchanged parts are in italics.

Non-DL on Sentence Pair Modeling. *Sentence pair modeling has attracted lots of attention in the past decades. Many tasks can be reduced to a semantic text matching problem.* In this paper, we adopt the arguments by Yih et al. (2013) who argue against shallow approaches as well as against semantic text matching approaches that can be computationally expensive:

Due to the variety of word choices and inherent ambiguities in natural language, bag-of-word approaches with simple surface-form word matching tend to produce brittle results with poor prediction accuracy (Bilotti et al., 2007). As a result, researchers put more emphasis on exploiting syntactic and semantic structure. Representative examples include methods based on deeper semantic analysis (Shen and Lapata, 2007; Moldovan et al., 2007), tree edit-distance (Punyakanok et al., 2004; Heilman and Smith, 2010) and

quasi-synchronous grammars (Wang et al., 2007) that match the dependency parse trees of the two sentences.

Instead of focusing on the high-level semantic representation, Yih et al. (2013) turn their attention to improving the shallow semantic component, lexical semantics, by performing semantic matching based on a latent word-alignment structure (cf. Chang et al. (2010)). Lai and Hockenmaier (2014) explore finer-grained word overlap and alignment between two sentences using negation, hypernym, synonym and antonym relations. Yao et al. (2013) extend word-to-word alignment to phrase-to-phrase alignment by a semi-Markov CRF. However, such approaches often require more computational resources. In addition, employing syntactic or semantic parsers – which produce errors on many sentences – to find the best match between the structured representations of two sentences is not trivial.

The first sentence of the penultimate paragraph of Section 2, Related Work, cites Mnih et al. (2014), but omits quotation marks. We correct it as follows, inserting opening and closing quotation marks. Unchanged parts are in italics.

Mnih et al. (2014) apply attention in recurrent neural networks (RNNs) to extract “information from an image or video by adaptively selecting a sequence of regions or locations and only processing the selected regions at high resolution.”

References

- Matthew W Bilotti, Paul Ogilvie, Jamie Callan, and Eric Nyberg. 2007. Structured retrieval for question answering. In *Proceedings of SIGIR*, pages 351–358.
- Ming-Wei Chang, Dan Goldwasser, Dan Roth, and Vivek Srikumar. 2010. Discriminative learning over constrained latent representations. In *Proceedings of NAACL-HLT*, pages 429–437.
- Michael Heilman and Noah A Smith. 2010. Tree edit models for recognizing textual entailments, paraphrases, and answers to questions. In *Proceedings of NAACL-HLT*, pages 1011–1019.
- Alice Lai and Julia Hockenmaier. 2014. Illinois-LH: A denotational and distributional approach to semantics. In *Proceedings of SemEval*, pages 329–334.
- Volodymyr Mnih, Nicolas Heess, Alex Graves, and Koray Kavukcuoglu. 2014. Recurrent models of visual attention. In *Proceedings of NIPS*, pages 2204–2212.
- Dan Moldovan, Christine Clark, Sanda Harabagiu, and Daniel Hodges. 2007. Cogex: A semantically and contextually enriched logic prover for question answering. *Journal of Applied Logic*, 5(1):49–69.
- Vasin Punyakanok, Dan Roth, and Wen-tau Yih. 2004. Mapping dependencies trees: An application to question answering. In *Proceedings of AI&Math*, pages 1–10.
- Dan Shen and Mirella Lapata. 2007. Using semantic roles to improve question answering. In *Proceedings of EMNLP-CoNLL*, pages 12–21.
- Mengqiu Wang, Noah A Smith, and Teruko Mitamura. 2007. What is the jeopardy model? A quasi-synchronous grammar for QA. In *Proceedings of EMNLP-CoNLL*, pages 22–32.
- Xuchen Yao, Benjamin Van Durme, Chris Callison-Burch, and Peter Clark. 2013. Semi-markov phrase-based monolingual alignment. In *Proceedings of EMNLP*, pages 590–600.
- Wen-tau Yih, Ming-Wei Chang, Christopher Meek, and Andrzej Pastusiak. 2013. Question answering using enhanced lexical semantic models. In *Proceedings of ACL*, pages 1744–1753.